Electronics Letters

VOLUME 15, 1979

THE INSTITUTION OF ELECTRICAL ENGINEERS

Electronics Letters

THE INSTITUTION OF ELECTRICAL ENGINEERS

ELECTRONICS LETTERS is published fortnightly. Price: £7·00 ($16·00) per issue; annual subscription in UK £67·00 Overseas £94·00 ($200·00). Second-class postage paid at New York, NY. All copies for North America are sent by Air Freight to New York. Airmail direct to subscriber at an additional charge of £20·00. Available also in a concurrent microfiche edition at the same subscription rate as for the printed edition. Subscribers to both the printed and microfiche editions are given a 75% discount on the price of the microfiche edition

* Except in December when only one issue is published. There are 25 issues each year

All subscription inquiries and orders should be sent to the Publication Sales Department, IEE, Station House, Nightingale Road, Hitchin, Herts. SG5 1RJ, England. Telephone Hitchin 53331 (s.t.d. 0462 53331), Telex 26117

Contributions should be addressed to the Executive Editor, *Electronics Letters*, Publishing Department, Institution of Electrical Engineers, PO Box 8, Southgate House, Stevenage, Herts. SG1 1HQ, England
There is no page charge

All other correspondence, including advertisements, should be sent to: IEE Publishing Department, PO Box 8, Southgate House, Stevenage, Herts. SG1 1HQ, England. Telephone Stevenage 3311 (s.t.d. 0438 3311), Telex 261176, Telegrams Voltampere Stevenage, England. The telephone number of the IEE London office is 01–240 1871, Telex 261176

The advantages of rapid publication given by *Electronics Letters* are nullified if subscribers are subject to excessive delays in the receipt of the journal. The Executive Editor would be grateful to learn of any difficulties subscribers may experience*.

This publication is copyright under the Berne Convention and the International Copyright Convention. All rights reserved. Apart from any copying under the UK Copyright Act 1956, part 1, section 7, whereby a single copy of an article may be supplied, under certain conditions, for the purposes of research or private study, by a library of a class prescribed by the UK Board of Trade Regulations (Statutory Instruments, 1957, no. 868), no part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means without the prior permission of the copyright owners. Permission is, however, not required to copy abstracts of papers or articles on condition that a full reference to the source is shown

The IEE appreciates that, on certain occasions, it could be very useful for organisations to be able to make copies of articles and papers. An IEE licensing arrangement exists whereby organisations entering into an agreement are legally entitled to make up to ten copies of an IEE paper or article. Full details may be obtained from the IEE Publishing Department at the above address

The appearance of the code at the bottom of an article in this journal indicates the copyright owner's consent that copies of the article may be made in the USA for personal or internal use, or for the personal or internal use of specific clients. This consent is given on the condition, however, that the copier pay the stated per-copy fee through the Copyright Clearance Center, Inc. for copying beyond that permitted by Sections 107 or 108 or the US Copyright Law. This consent does not extend to other kinds of copying, such as copying for general distribution, for advertising or promotional purposes for creating new collective works or for resale. Payment is also required for copying of articles published before 1979

The IEE is not as a body responsible for the opinions expressed by individual authors

The IEE is a member of the Association of Learned & Professional Society Publishers

Publishing Department:

PO Box 8
Southgate House
Stevenage
Herts. SG1 1HQ
England

Secretary of the IEE:

G. F. Gainsborough

Director of INSPEC and Publishing:

D. H. Barlow

Editor in Chief:

J. D. St. Aubyn

Managing Editor:

B. Dunkley

Executive Editor:

B. Goodale

Graphics Manager:

M. C. Partridge

EDITORS

P. J. B. Clarricoats *(London)*
E. A. Ash *(London)*

Advertisement Department:

IEE
PO Box 8
Southgate House
Stevenage
Herts. SG1 1HQ
England

© 1979: The Institution of Electrical Engineers

The Institution of Electrical Engineers, Savoy Place, London WC2R 0BL, England

Typeset in England by:
Santype International Ltd
Netherhampton Road
Salisbury
Wilts. SP2 8PS

Printed in England by:
C. F. Hodgson & Son Ltd
50 Holloway Road
London N7 8JL

Electronics Letters

INDEX VOLUME 15, 1979

Author index

A

Abbasi, S.A., and Brunnschweiler, A. Resolution of spreading-resistance measurements on shallow layers 290
Abbott, S.M., and Muska, W.M. Low-noise optical detection of a 1.1 Gb/s optical data stream 250
Accatino, L., and Angelucci, A. Spread in effective permittivity of alumina substrates 64
Aceves, M., and Kendall, D.L. Increase to inverse beta of Si transistors due to low-temperature treatments 282
Adams, M.J., Payne, D.N., and Ragdale, C.M. Birefringence in optical fibres with elliptical cross-section 298
Adams, M.J., Norman, S.R., Payne, D.N., and Smith, A.M. (see Norman, S.R.)
Adams, M.J., Sladen, F.M.E., and Payne, D.N. (see Sladen, F.M.E.)
Adler, E.L., and El-Nokali, M. (see El-Nokali, M.)
Aebi, V., Morkoc, H., and Andrews, J. (see Morkoc, H.)
Agrawal, J.P., and Prabhu, K.M.M. (see Prabhu, K.M.M.)
Ahlgren, D.J. Synthesis of matched b.j.t. cascode broadband amplifiers 709
Ahmed, H., and McMahon, R.A. (see McMahon, R.A.)
Ahmed, H., McMahon, R.A., Speight, J.D., and Dobson, R.M. (see McMahon, R.A.)
Ahmed, M.T., and Siddiqui, M.A. Low-sensitivity high-frequency inductance realisation [illegible] capacitor 260
Ahuja, S.S. [illegible] sional variable f.i.r. bandpa[illegible]
Ahuja, S.S., and [illegible] S.C. Variable-[illegible] bandwidth [illegible] ass filters 245
Ains[illegible], B.J., Day, C.R., [illegible] P.W., Beales, K.J., and Newns, G.R. [illegible] ation of long length[illegible] ultra-low-loss sing[illegible]-mode fibre 4[illegible]
Aitchison, C.S., and Akademir, A. (see Akademir, A.)
Aizawa, N., Ito, K., and Goto, N. (see Ito, K.)
Akademir, A., and Aitchison, C.S. A.D. convertor using digital discriminator: an experimental result 379
Akiba, S., Sakai, K., Matsushima, Y., and Yamamoto, T. Room temperature c.w. operation of InGaAsP/InP heterostructure lasers emitting at 1.56 μm 606
Akintunde, J.A., Badawi, M.H., Sealy, B.J., and Stephens, K.G. (see Badawi, M.H.)
Al-Jumaily, A.M., and Lainé, D.C. (see Lainé, D.C.)
Alcuri, L., Mamola, G., and Randazzo, E. Filtering out intersymbol interference of spread-spectrum communication systems 397
Allen, C.J., and Ambridge, T. (see Ambridge, T.)
Allen, P.E., Arreola, J.I., Tsividis, Y.P., and Sánchez-Sinencio, E. (see Arreola, J.I.)
Allen, P.J., and Holt, A.G.J. Alternative multiplication configuration in microprocessor-based digital filters 481
Allidina, A.Y., and Hughes, F.M. Self-tuning controller steady-state error 346
Allnutt, J., and Lau, P-K. (see Lau, P-K.)
Alves, A.P., and McEwan, N.J. Arbitrary polarisation microwave receiver applied to OTS reception 657
Amann, M-C. New stripe-geometry laser with simplified fabrication process 441
Amann, M.-C., and Boeck, J. High-efficiency superluminescent diodes for optical-fibre transmission 41
Amann, M.-C., and Proebster, W. Small-area GaAs-GaAlAs heterostructure light-emitting diode with improved current confinement 599
Ambridge, T., and Allen, C.J. Automatic electrochemical profiling of Hall mobility in semiconductors 648
Ambridge, T., and Ashen, D.J. Automatic electrochemical profiling of carrier concentration in indium phosphide 647
Ambridge, T., Sharpe, C.D., Lilley, P., and Elliott, C.R. (see Sharpe, C.D.)
Anand, Y., Christou, A., and Davey, J.E. (see Christou, A.)
Anandamohan, P.V. Q-sensitivity of certain RC active filters to gain-bandwidth product 95
Anday, F. Active C realisation for the general biquadratic voltage transfer functions 725
Errata 838
Anderson, A.P., Melek, M., and Brown, B.H. Feasibility of focused microwave array system for tumour irradiation 564
Anderson, A.P., Marie, K.H.S., and Bennett, J.C. (see Marie, K.H.S.)
Anderson, Jun., W.T., Davey, J.E., Christou, A., Bark, M.L., Sleger, K.J., and Dietrich, H.B. GaAs heterojunction f.e.t. with epitaxial Ge gate 11
Andrejco, M.J., Smithgall, D.H., and Saifi, M.A. (see Smithgall, D.H.)
Andrews, J., Morkoc, H., and Aebi, V. (see Morkoc, H.)
Angelucci, A., and Accatino, L. (see Accatino, L.)
Aono, Y., Furutsuka, T., Higashisaka, A., Takayama, Y., and Hasegawa, F. (see Furutsuka, T.)
Aono, Y., Sone, J., and Takayama, Y. (see Sone, J.)
Aono, Y., Takayama, Y., and Ogawa, T. (see Takayama, Y.)
Aoyama, T., Fujii, Y, Minowa, J., and Doi, K. (see Fujii, Y)
Appel-Hansen, J., and King, R.J. Experimental study of surface-wave propagation on a low-permittivity medium 101
Arambepola, B., and Rayner, P.J.W. Multi-dimensional fast-Fourier-transform algorithm 382
Arambepolar, B., and Rayner, P.J.W. Efficient transforms for multidimensional convolutions 189
Archer, J.W. TE_{on}-mode filters for the v.l.a. circular waveguide system 343
Arledge, L.A., Littlejohn, M.A., Glisson, T.H., and Hauser, J.R. (see Littlejohn, M.A.)
Arlett, P.L., Walton, A., Elkins, K., and O'Neill, K. Crystal-oscillator-based device for remote power-line temperature sensing 93
Armstrong, B.M., Moore, R.A., and Wakefield, J. Higher output from Baritt diodes using ion implantation 153
Arreola, J.I., Tsividis, Y.P., Sanchez-Sinencio, E., and Allen, P.E. Simple implementation of sampled-data filters using current multipliers, switches, and capacitors 780
Arthur, J.W., Cowan, C.F.N., and Mavor, J. (see Cowan, C.F.N.)
Asatani, K., and Sato, K-I. (see Sato, K-I.)
Ashall, C.P., and Matthews, P.A. Effect of feedback delay on tracking-loop frequency acquisition 231
Ashen, D.J., and Ambridge, T. (see Ambridge, T.)
Ashton, R.W., and Guy, R.F.E. (see Guy, R.F.E.)
Atalar, A. Modulation transfer function for the acoustic microscope 321
Atherton, D.P., and Owens, D.H. Boundedness properties of nonlinear multivariable feedback systems 559
Atzeni, C., and Manes, G.F. (see Manes, G.F.)
Atzeni, C., and Manes, G.F. (see Manes, G.F.)
Auchterlonie, L.J., and Bryant, D.L. (see Bryant, D.L.)
Auer, W., Zwick, U., Riegl, I., Haupt, H., and Heitmann, W. (see Zwick, U.)
Azan, F., Mouly, J.M., and Salset, J. Optical probe for absolute measurement of surface-acoustic-wave amplitude 80

B

Baack, C., Elze, G., Grosskopf, G., Kraus, G., Krick, F., and Küller, L. Analogue optical transmission of 26 t.v. channels 300
Errata 444
Badawi, M.H., Akintunde, J.A., Sealy, B.J., and Stephens, K.G. Effect of Si_3N_4 encapsulation on the laser-annealing behaviour of GaAs 447
Badawi, M.H., Sealy, B.J., and Stephens, K.G. Vaporisation of GaAs during laser annealing 786
Badawi, M.H., Kular, S.S., Sealy, B.J., Stephens, K.G., Sadana, D., and Booker, G.R. (see Kular, S.S.)
Badawi, M.H., and Tuck, B. (see Tuck, B.)
Baert, D. Solar-cell panel simulator 53
Báez-López, D., and Sánchez-Sinencio, E. (see Sánchez-Sinencio, E.)
Bahl, I.J., and Stuchly, S.S. Effect of finite size of ground plane on the impedance of a monopole immersed in a lossy medium 728
Bahnas, Y.Z., Nomair, M., and Soliman, A.M. (see Nomair, M.)
Bailey, M.D., and Rawson, E.G. (see Rawson, E.G.)
Bale, R.A., Roberts, J.B.G., Darby, B.J., and Eames, R. (see Roberts, J.B.G.)
Baliga, B. Enhancement- and depletion-mode vertical-channel m.o.s. gated thyristors 645
Balk, P., Bruch, H., Palm, L., and Ponse, F. (see Bruch, H.)
Ball, E., and Izatt, T.G. (see Izatt, T.G.)
Balynas, V., and Laurinvičius, A. (see Laurinvičius, A.)
Bandy, S.G., Collins, D.M., and Nishimoto, C.K. Low-noise microwave f.e.t.s fabricated by molecular-beam epitaxy 218
Bapst, U., and Gfeller, F.R. (see Gfeller, F.R.)
Bar-Ness, Y., Messer, H., and Gilboa, H. (see Messer, H.)
Bark, M.L., Anderson, Jun., W.T., Davey, J.E., Christou, A., Sleger, K.J., and Dietrich, H.B. (see Anderson, Jun., W.T.)
Barker, R.W.J., and Hart, B.L. (see Hart, B.L.)
Barley, I.W., Cochrane, P., and O'Reilly, J.J. (see Cochrane, P.)
Barna, A. Propagation delay optimisation in multistage GaAs m.e.s.f.e.t. combinational logic circuits by use of dynamic programming 147
Barsan, R.M. Step and frequency responses of c.t.d.s. with nonuniform transfer inefficiency 389

Bastida, E.M., and Donzelli, G.P. Periodic slow-wave low-loss structures for monolithic GaAs microwave integrated circuits 581
Basu, N., Dhariwal, S.R., and Gadre, R. (see Dhariwal, S.R.)
Batchelor, B.G. Streak and spot detection in digital pictures 352
Bates, R.J.S. Error probability due to Gaussian noise and near-end crosstalk 116
Bava, E., Godone, A., and De Marchi, A. (see Godone, A.)
Beales, K.J., Ainslie, B.J., Day, C.R., France, P.W., and Newns, G.R. (see Ainslie, B.J.)
Beck, A.H., and Haldar, M.K. (see Haldar, M.K.)
Becker, J.-P., and Jäger, D. Electrical properties of coplanar transmission lines on lossless and lossy substrates 88
Begemann, G., and Jacob, A. Conversion gain of m.e.s.f.e.t. drain mixers 567
Begemann, G., Kpodzo, E., and Schünemann, K. (see Kpodzo, E.)
Bell, R.R., and Thirlwell, J. Satellite slant-path attenuation statistics obtained using 20 and 30 GHz passive radiometers at Martlesham Heath 781
Belson, J., and Wilson, I.H. Changes in annealing behaviour of SiO_2 on Si resulting from H_2^+ and D_2^+ ion bombardment 420
Beneking, H., Stahlmann, R., Tsironis, C., and Ponse, F. (see Stahlmann, R.)
Benes, T., Karpinsky, J., Hlavaty, V., Rozkosny, V., and Sajal, P. (see Karpinsky, J.)
Benjamin, R. Form of Doppler processing for radars of random p.r.i. and r.f. 782
Bennett, J.C., Marie, K.H.S., and Anderson, A.P. (see Marie, K.H.S.)
Benson, F.A., Rahman, M.M., and Sitch, J.E. (see Rahman, M.M.)
Berenz, J.J., Kinoshita, J., Hierl, T.L., and Fank, F.B. High-power pulsed GaAs double-drift hybrid-Read Impatt diodes for X-band 277
Berenz, J.J., Kinoshita, J., Hierl, T.L., and Lee, C.A. Orientation dependance of n-type GaAs intrinsic avalanche response time 150
Berenz, J.J., Vichr, M., and Fank, F.B. Comparison of GaAs Impatt designs for 20 GHz 694
Berger, C.S. Optimal input for stochastic linear discrete systems as a function of input and output variables 360
Berger, H., and Schneider, M.V. (see Schneider, M.V.)
Bertoni, H.L., and Parmon, W. (see Parmon, W.)
Bhar, T.N., Dat, R., Koyama, R.Y., and Galloway, K.F. Effect of ionising radiation on mobile-ion density in m.o.s. oxides 16
Bhattacharya, P.K., Ku, J.W., Owen, S.J.T., Chiao, S.H., and Yeats, R. Evidence of trapping in device-quality liquid-phase-epitaxial $In_{1-x}Ga_xAs_yP_{1-y}$ 753
Bhattacharyya, A. Fault detection in Moore-model sequential machine using counter-cycle technique 402
Bhattacharyya, A. Very easily testable/diagnosable sequential machine 190
Bie, P.R., Calviello, J.A., and Wallace, J.L. (see Calviello, J.A.)
Birch, J., and Marriott, S.P. Appraisal of the inverted-mesa AT-cut quartz resonator for achieving low-inductance high-Q single-response crystal units 641
Blanco, C. Gain expansion and intermodulation in a m.e.s.f.e.t. amplifier 31
Blenkinsop, I.D., Griffiths, R.J.M., and Wight, D.R. (see Griffiths, R.J.M.)
Board, K., Stall, R., Wood, C.E.C., and Eastman, L.F. (see Stall, R.)
Boccon-Gibod, D., Meignant, D., and Bourgeois, J.M. (see Meignant, D.)
Boeck, J., and Amann, M.-C. (see Amann, M.-C.)
Boithias, L. Multipath propagation in line-of-sight links 209
Bonetti, R.R. Nonreciprocal directional filter: a new multipurpose ferrite device 233
Booker, G.R., Kular, S.S., Sealy, B.J., Badawi, M.H., Stephens, K.G., and Sadana, D. (see Kular, S.S.)
Borden, P.G. Substrate conduction in GaAs m.e.s.f.e.t.s. 307
Bourgeois, J.M., Meignant, D., and Boccon-Gibod, D. (see Meignant, D.)
Bowron, P., and Mohamed, A. Nonlinear modelling of f.e.t.-input operational amplifiers 473
Bradshaw, A., and Porter, B. (see Porter, B.)
Brain, M.C. Responsivity and noise characterisation of Ge avalanche photodiode throughout wavelength range 1.1-1.7 μm 821
Brand, J.R., Schaumann, R., and Laker, K.R. (see Schaumann, R.)
Brandon, P.S., and Kwok, P.C.K. (see Kwok, P.C.K.)
Brandon, P.S., and Kwok, P.C.K. (see Kwok, P.C.K.)
Brehm, G.E., Doerbeck, F.H., Macksey, H.M., and Frensley, W.R. (see Doerbeck, F.H.)
Brown, B.H., Anderson, A.P., and Melek, M. (see Anderson, A.P.)
Bruch, H., Palm, L., Ponse, F., and Balk, P. V.P.E. GaAs m.e.s.f.e.t. structure using oxygen injection during buffer layer growth 246
Brugger, U.W., and Hosticka, B.J. Alternative realisations of switched-capacitor floating inductors 698
Brugger, U.W., Hosticka, B.J., and Moschytz, G.S. Switched-capacitor simulation of floating inductors using gyrators 494
Brunnschweiler, A., and Abbasi, S.A. (see Abbasi, S.A.)
Brunwin, R., Hamilton, B., Jordan, P., and Peaker, A.R. Detection of minority-carrier traps using transient spectroscopy 349
Brunwin, R.F., Peaker, A.R., Jordan, P., and Hamilton, B. (see Peaker, A.R.)
Bruton, L.T., Rao, M.K.N., and Haslett, J.W. (see Rao, M.K.N.)
Bryant, D.L., and Auchterlonie, L.J. Measurement of the extinction cross-sections of dry and wet ice spheres at 35 GHz 52
Burrus, C.A., Dentai, A.G., and Lee, T.P. InGaAsP p-i-n photodiodes with low dark current and small capacitance 655
Burrus, C.A., Lee, T.P., Campbell, J.C., Ogawa, K., McCormick, A.R., and Dentai, A.G. (see Lee, T.P.)
Butcher, D.N., and Sealy, B.J. Changes in the thermal oxidation of gallium arsenide induced by ion implantation 51
Bylanski, P. Signal-processing operations on A-law companded speech 697
Bywater, R.E.H., Williamson, S.E., and Matley, W. (see Williamson, S.E.)
Bywater, R.E.H., Williamson, S.E., and Matley, W. (see Williamson, S.E.)

C

Čada, M., Čtyroký, J., Lyndin, N.M., Sychugov, V.A., and Schroefel, J. (see Čtyroký, J.)
Calleja, E., Garrido, J., and Piqueras, J. (see Garrido, J.)
Calviello, J.A., Wallace, J.L., and Bie, P.R. High-performance GaAs beam-lead mixer diodes for millimetre and submillimetre applications 509
Calzolari, P.U., Masetti, G., and Severi, M. Integrated n.m.o.s. operational amplifier for c.c.d. transversal filters 29
Campbell, J.C., Lee, T.P., Ogawa, K., McCormick, A.R., Dentai, A.G., and Burrus, C.A. (see Lee, T.P.)
Cancellieri, G., Mezzetti, M., Someda, C.G., and Zoboli, M. Simplified procedure for indirect tests of optical-fibre transfer functions 234
Capasso, F., Nahory, R.E., and Pollack, M.A. Temperature dependence of impact ionisation rates in GaAs between 20° and 200° C 117 Errata 507
Card, H.C., and Poon, T.C. (see Poon, T.C.)
Carlson, H.E., and Fleming, P.L. (see Fleming, P.L.)
Carlson, H.E., and Fleming, P.L. (see Fleming, P.L.)
Carpentier, M.P., and Dos Santos, A.F. New representation for the current in a horizontal wire above ground 554
Carroll, J.E., and Renner, D. (see Renner, D.)
Carru, H. Three-dimensional 'sandwich' transducer modelling by finite-element method 805
Caruso, A., Spirito, P., and Vitale, G. New semiconductor active device: the conductivity-controlled transistor 267
Chaloupka, H., Galka, M., and Schlendermann, A. Determination of antenna radiation pattern from frequency-domain measurements in reflecting environment 512
Chambers, B., and Simpson, S.H.W. (see Simpson, S.H.W.)
Chandra, A., and Eastman, L.F. Rectification at n-n GaAs: (Ga, Al)As heterojunctions 90 Errata 216
Chang, C.T. Minimum dispersion at 1.55 μm for single-mode step-index fibres 765
Chang, K., Ebert, R., and Sun, C. W-band two-diode power combiner 403
Chang, N.S., Ikuzawa, Y., and Matsuo, Y. (see Ikuzawa, Y.)
Chang, T-L. Error-feedback digital filters 348
Chao, P., Das, S.R., and Chen, Z. (see Das, S.R.)
Char, J.P., and Dadheech, S.D. Simple modification to circuit enumeration algorithm for better efficiency 191
Cheevasuvit, F., and Thajchayapong, P. (see Thajchayapong, P.)
Chen, Z., Das, S.R., and Chao, P. (see Das, S.R.)
Cherny, V.V. Confined guided modes in W-fibre with square core 281
Chevalier, G., d'Auria, L., and Maillot, P. (see d'Auria, L.)
Chiao, S.H., Bhattacharya, P.K., Ku, J.W., Owen, S.J.T., and Yeats, R. (see Bhattacharya, P.K.)
Chida, K., Hanawa, F., Nakahara, M., and Inagaki, N. Simultaneous dehydration with consolidation for v.a.d. method 835
Chida, K., Edahiro, T., Horiguchi, M., and Ohmori, Y. (see Edahiro, T.)
Chinnock, E.L., and Ogawa, K. (see Ogawa, K.)
Choi, Y.M., and Harris, D.J. (see Harris, D.J.)
Chou, C.H., and Khuri-Yakub, B.T. (see Khuri-Yakub, B.T.)
Choudhury, A.N.M.M., and Robson, P.N. Hole traps in n-InP by d.l.t.s. and transient capacitance techniques 247
Chovet, A., and Rahal, S. (see Rahal, S.)
Christou, A., Davey, J.E., and Anand, Y. Low-barrier-height epitaxial Ge-GaAs mixer diodes 324
Christou, A., Anderson, Jun., W.T., Davey, J.E., Bark, M.L., Sleger, K.J., and Dietrich, H.B. (see Anderson, Jun., W.T.)
Chu, P.L. Nondestructive refractive-index profile measurement of elliptical optical fibre or preform 357
Chu, P.L., and Saekeang, C. Nondestructive determination of refractive-index profile and cross-sectional geometry of optical-fibre preform 635
Chu, P.L., and Whitbread, T. Measurement of refractive-index profile of optical-fibre preform 295
Citerne, J., Gelin, Ph., and Petenzi, M. (see Gelin, Ph.)
Clapton, A.J. Correlation technique for improved isolation of overlapping spectra in video modulators 429
Clarke, R.N. Checking of square-law detectors used in Hartshorn and Ward dielectric measurements 183
Cochrane, P., Barley, I.W., and O'Reilly, J.J. Direct jitter measurement technique 774
Cohen, L.G., Lin, C., and French, W.G. Tailoring zero chromatic dispersion into the 1.5-1.6 μm low-loss spectral region of single-mode fibres 334
Cole, T.W. Configurations for the complex-internal-reflection (c.i.r.) light modulator 217
Collins, D.A., Meiners, L.G., and Lile, D.L. (see Meiners, L.G.)
Collins, D.M., Bandy, S.G., and Nishimoto, C.K. (see Bandy, S.G.)
Conn, D.R., and Maciejko, R. User density for 800 MHz microwave mobile radiotelephone communications 516
Conradi, J., Straus, J., and Few, I.S. (see Straus, J.)
Constant, E., Rolland, P.A., Salmer, G., and Fauquembergue, R. (see Rolland, P.A.)
Constantinides, A.G., and Yong-Ching, L. (see Yong-Ching, L.)
Cooper, K., Grierson, J.R., Leigh, P.A., O'Sullivan, P.J., and Huish, P.W. (see Grierson, J.R.)
Copeland, M.A., and Rabaey, J.M. Dynamic amplifier for m.o.s. technology 301
Cornbleet, S. Feed position for a parabolic reflector with offset pattern 211
Costa, B., Esposto, F., D'Orio, C., and Morra, P. Splice loss evaluation by means of the back-scattering technique 550
Coupe, F.G.A. Digital frequency discriminator 489
Courbet, G., Degauque, P., Demoulin, B., and Gabillard, R. Contribution of the discrete modes to the current propagating along a wire parallel to a moderate conducting earth 174
Courvoisier, M. One-step N-user programmable arbiter (Arbitre N-utilisateurs, une ressource, programmable) 430
Courvoisier, M., and Seck, J.P. Hardware implementation of generalised Petri nets 770
Cowan, C.F.N., Mavor, J., and Arthur, J.W. Noise cancellation and inverse filtering using a compact high-performance c.c.d. adaptive filter 35
Cowan, C.F.N., Geddes, R.C., Mavor, J., and Dickson, J.F. (see Geddes, R.C.)
Cozens, J.R., and Dyott, R.B. Higher-mode cutoff in elliptical dielectric waveguides 558
Cozens, J.R., Dyott, R.B., and Morris, D.G. (see Dyott, R.B.)
Čtyroký, J., Čada, M., Lyndin, N.M., Sychugov, V.A., and Schroefel, J. Novel beam-to-waveguide coupler for $LiNbO_3$ optical waveguides 519
Culshaw, B. Minimisation of modal noise in optical-fibre connectors 529
Culshaw, B., and Hutchings, M.J. Optical-fibre flowmeter 659
Czarnul, Z., Kiruthi, G., and Newcomb, R.W. M.O.S. neural pulse modulator 823

D

d'Auria, L., Chevalier, G., and Maillot, P. Libido using Eros: halfduplex optical link 820
D'Auria, L., Nouchi, I., and Jacques, A. (see Nouchi, I.)
D'Inzeo, G., Giannini, F., and Sorrentino, R. Novel microwave integrated lowpass filters 258
D'Orio, C., Costa, B., Esposto, F., and Morra, P. (see Costa, B.)
Dadheech, S.D., and Char, J.P. (see Char, J.P.)
Daino, B., De Marchis, G., and Piazzolla, S. Analysis and measurement of modal noise in an optical fibre 755
Dalgleish, J.F., and Pacey, G.K. (see Pacey, G.K.)
Darby, B.J., Roberts, J.B.G., Bale, R.A., and Eames, R. (see Roberts, J.B.G.)
Das, S.R., Chao, P., and Chen, Z. Transition matrices in multiple preset experiments and initial state identification of synchronous sequential machines 777
Dat, R., Bhar, T.N., Koyama, R.Y., and Galloway, K.F. (see Bhar, T.N.)
Davey, J.E., Anderson, Jun., W.T., Christou, A., Bark, M.L., Sleger, K.J., and Dietrich, H.B. (see Anderson, Jun., W.T.)
Davey, J.E., Christou, A., and Anand, Y. (see Christou, A.)
Davidson, D., and Nackoney, O.G. (see Nackoney, O.G.)
Davis, J.R. Discharge mechanisms in floating-gate e.p.r.o.m. cells 20
Dawsey, J.R., Vokes, J.C., Hughes, B.T., Wight, D.R., and Shrubb, S.J.W. (see Vokes, J.C.)
Day, C.R., Ainslie, B.J., France, P.W., Beales, K.J., and Newns, G.R. (see Ainslie, B.J.)
De Blok, C.M., and Matthijsse, P. (see Matthijsse, P.)
De Marchi, A., Godone, A., and Bava, E. (see Godone, A.)
De Marchis, G., Daino, B., and Piazzolla, S. (see Daino, B.)
De Marchis, G., and Piazzola, S. (see Piazzola, S.)
De Oliveira, A.D., Wright, S., and Wilson, M.G.F. (see Wright, S.)
Debrie, R., and Pignard, J. Continuous measurement of electron density in unmagnetised plasmas by a self-oscillating probe 799
Degauque, P., Courbet, G., Demoulin, B., and Gabillard, R. (see Courbet, G.)
Dejhan, K., Pookaiyaudom, S., and Watanachaiprateep, C. (see Pookaiyaudom, S.)
Demoulin, B., Courbet, G., Degauque, P., and Gabillard, R. (see Courbet, G.)
Dennis, T.J. Quantiser selection for interframe differential pulse code modulation of television pictures 142
Dennis, T.J., and Pearson, D.E. (see Pearson, D.E.)
Dentai, A.G., Burrus, C.A., and Lee, T.P. (see Burrus, C.A.)
Dentai, A.G., Lee, T.P., Campbell, J.C., Ogawa, K., McCormick, A.R., and Burrus, C.A. (see Lee, T.P.)
Denyer, P.B., and Mavor, J. Monolithic 256-point programmable transversal filter 710
Derewonko, H., Laviron, M., and Lepage, J. X- and KU-Band internally matched packaged GaAs F.E.T. 8
Deutsch, G., Lindner, G., Lübke, K., and Thim, H.W. High-bit-rate pulse regeneration and modulation of injection lasers with a planar Gunn device 285
DeWinter, J.C., Kaminow, I.P., Nahory, R.E., Pollack, M.A., and Stulz, L.W. (see Kaminow, I.P.)
DeWinter, J.C., Nahory, R.E., and Pollock, M.A. (see Nahory, R.E.)
Dhariwal, S.R., Basu, N., and Gadre, R. Open-circuit to short-circuit switching: method for lifetime measurement in solar cells 456
Di Vita, P., and Rossi, U. Backscattering measurements in optical fibres: separation of power decay from imperfection contribution 467
Dickson, J.F., and Fox, J. (see Fox, J.)
Dickson, J.F., Geddes, R.C., Cowan, C.F.N., and Mavor, J. (see Geddes, R.C.)
Dietrich, H.B., Anderson, Jun., W.T., Davey, J.E., Christou, A., Bark, M.L., and Sleger, K.J. (see Anderson, Jun., W.T.)
Dilworth, I.J., and Evans, B.G. Cumulative crosspolarisation and canting angle distributions 603
Djurich, B.M., and Zivaljevich, C.M. Filters for data transmission with minimum intersymbol interference 288
Dmitrevsky, S., Lane, W.A., and Salama, C.A.T. (see Lane, W.A.)
Dobrovolsky, A.A., Lemanov, V.V., Smolensky, G.A., and Sherman, A.B. S.A.W. convolver using secondary electrons 437
Dobson, R.M., McMahon, R.A., Ahmed, H., and Speight, J.D. (see McMahon, R.A.)
Doerbeck, F.H., Macksey, H.M., Brehm, G.E., and Frensley, W.R. Ion-implanted GaAs X-band power f.e.t.s. 576
Doi, K., Fujii, Y., Minowa, J., and Aoyama, T. (see Fujii, Y)
Donzelli, G.P., and Bastida, E.M. (see Bastida, E.M.)
Dos Santos, A.F., and Carpentier, M.P. (see Carpentier, M.P.)
Downing, O.J., and Thorpe, P.L.M. Proposed technique for reduction of contouring in quantised (monochrome) image signals 5
Drukier, I., Wade, P.C., and Rutkowski, D. (see Wade, P.C.)
Dubost, G., Samson, J., and Frin, R. Large-bandwidth flat cylindrical array with circular polarisation and omnidirectional radiation 102
Dunn, F.A., Tomlinson, W.J., Wagner, R.E., and Strnad, A.R. (see Tomlinson, W.J.)
Dunning-Davies, J., and Stephenson, F.W. (see Stephenson, F.W.)
Durrani, T.S., and Murukutla, N.L.M. Convergence of adaptive lattice filters 833
Durrani, T.S., and Murukutla, N.L.M. Recursive algorithm for adaptive lattices 831
Dutronc, J., Evans, B.G., and Ganem, H. (see Evans, B.G.)
Dutta Roy, S.C., and Ahuja, S.S. (see Ahuja, S.S.)
Dyott, R.B., Cozens, J.R., and Morris, D.G. Preservation of polarisation in optical-fibre waveguides with elliptical cores 380
Dyott, R.B., and Cozens, J.R. (see Cozens, J.R.)

E

Eames, R., Roberts, J.B.G., Darby, B.J., and Bale, R.A. (see Roberts, J.B.G.)
Eastman, L.F., and Chandra, A. (see Chandra, A.)
Eastman, L.F., Jervis, T.R., and Woodard, D.W. (see Jervis, T.R.)
Eastman, L.F., Stall, R., Wood, C.E.C., and Board, K. (see Stall, R.)
Ebert, R., Chang, K., and Sun, C. (see Chang, K.)
Edahiro, T., Horiguchi, M., Chida, K., and Ohmori, Y. Spectral loss characteristics of $GeO_2-P_2O_5$-doped silica graded-index fibres in long-wavelength band 274
Edahiro, T., Kawachi, M., Sudo, S., and Takata, H. OH-ion reduction in v.a.d. optical fibres 482
Edahiro, T., Sudo, S., Kawachi, M., Jinguji, K., and Inagaki, N. Phosphor-doped silica cladding v.a.d. fibres 726
Edahiro, T., Okamoto, K., Kawana, A., and Miya, T. (see Okamoto, K.)
Edahiro, T., Shibata, N., Kawachi, M., and Sudo, S. (see Shibata, N.)
Ehlers, E.R., and Kotzebue, K.L. (see Kotzebue, K.L.)
Eilley, E.S., Hughes, J.B., and Glynn, G.J. (see Hughes, J.B.)
El-Nokali, M., and Adler, E.L. Charge storage in s.a.w. memory correlators 323
Elkins, K., Arlett, P.L., Walton, A., and O'Neill, K. (see Arlett, P.L.)
Elliott, C.R., Sharpe, C.D., Lilley, P., and Ambridge, T. (see Sharpe, C.D.)
Elze, G., Baack, C., Grosskopf, G., Kraus, G., Krick, F., and Küller, L. (see Baack, C.)
Emerson, N.G., and Sealy, B.J. Effects of laser irradiation of GaAs observed by d.l.t.s. 553
Englefield, C.G., Gupta, R.K., and Goud, P.A. (see Gupta, R.K.)
Enomoto, T., Ishihara, T., Yasumoto, M., and Shida, S. High-performance c.c.d. channel filter for a p.c.m. codec 817
Enomoto, T., Yasumoto, M., and Watanabe, K. Two-dimensional inverse filter using floating-gate tapped c.c.d.s. 280
Esposto, F., Costa, B., D'Orio, C., and Morra, P. (see Costa, B.)
Eto, Y., and Hirano, Y. Automatic selective equaliser for telephone facsimile transmission 144
Evans, B.G., Ganem, H., and Dutronc, J. Measurement and simulation of satellite systems single-channel-per-carrier frequency-modulation spectra 194
Evans, B.G., and Dilworth, I.J. (see Dilworth, I.J.)
Evans, B.G., Upton, S.A.J., and Holt, A.R. (see Upton, S.A.J.)
Evans, F.J., and Schizas, C. Digraph analysis of large-scale systems: the system primitive 613
Eve, M., and Smith, D.W. New automatic-gain-control system for optical receivers 146

F

Fallmann, W., Riedling, K., and Olcaytug, F. (see Riedling, K.)
Fank, F.B., Berenz, J.J., Kinoshita, J., and Hierl, T.L. (see Berenz, J.J.)
Fank, F.B., Berenz, J.J., and Vichr, M. (see Berenz, J.J.)
Faruque, S.M., Viswanathan, T.R., Singhal, K., and Vlach, J. (see Viswanathan, T.R.)
Fauquembergue, R., Rolland, P.A., Constant, E., and Salmer, G. (see Rolland, P.A.)
Feldmann, M., Henaff, J., Lacroix, B., and Rebourg, J.C. Design of minimum-phase charge-transfer transversal filters 226
Felsen, L.B. Evanescent-wave tracking: new approach to the analysis of large reflector and aperture antennas 531
Fernando, K.V.M., and Nicholson, H. Double-sided least-squares problem 624
Few, I.S., Straus, J., and Conradi, J. (see Straus, J.)
Fidler, J.K., and Nightingale, C. Slope-normalised sensitivity: a new sensitivity measure 54
Filanovsky, I.M., and Stromsmoe, K.A. More active RC filters using the d.v.c.c.s./d.v.c.v.s. 466
Filicori, F., Scalas, M.R., and Naldi, C. Nonlinear circuit analysis through periodic spline approximation 597
Fincham, W.F., and Nikias, C.L. Optimally sensitive controller for digital systems 537
Fincham, W.F., and Nikias, C.L. (see Nikias, C.L.)
Fleming, P.L., and Carlson, H.E. Reflection-mode amplifier utilising GaAs active-medium-propagation devices 787
Fleming, P.L., and Carlson, H.E. Two-stage amplifier utilising GaAs active-medium-propagation devices 406
Forssell, B. Quantitative analysis of 2-f.s.k. traffic detection 386
Fox, J., and Dickson, J.F. New charge-differencing technique for c.c.d. transversal filters 229
France, P.W., Ainslie, B.J., Day, C.R., Beales, K.J., and Newns, G.R. (see Ainslie, B.J.)
Freidin, B., and Velmre, E. (see Velmre, E.)
French, W.G., Cohen, L.G., and Lin, C. (see Cohen, L.G.)
Frensley, W.R., Doerbeck, F.H., Macksey, H.M., and Brehm, G.E. (see Doerbeck, F.H.)
Frey, J., and Wada, T. Mobility, transit time and transconductance in submicrometre-gate-length m.e.s.f.e.t.s. 26
Frin, R., Dubost, G., and Samson, J. (see Dubost, G.)
Fujii, Y., Minowa, J., Aoyama, T., and Doi, K. Low-loss 4 x 4 optical matrix switch for fibre-optic communication 427
Fujii, Y., Minowa, J., and Suzuki, N. Demountable multiple connector with precise V-grooved silicon 424
Fujiki, M., Oikawa, S., and Katayama, Y. (see Oikawa, S.)
Fujita, M., Nakamura, K., Ihara, T., and Hayashi, R. Seasonal variations of attenuation statistics in millimetre-wave earth-satellite link due to bright-band height 654
Fukai, I., Washisu, S., and Suzuki, M. (see Washisu, S.)
Furlan, J. Injection transistor-transistor logic (i.t.t.l.) 223
Furman, T.R., Ladany, I., and Marinelli, D.P. (see Ladany, I.)
Furutsuka, T., Higashisaka, A., Aono, Y., Takayama, Y., and Hasegawa, F. GaAs power m.e.s.f.e.t.s. with a graded recess structure 417
Furuya, K., Sakakibara, Y., Suematsu, Y., and Itaya, Y. (see Sakakibara, Y.)

G

Gabillard, R., Courbet, G., Degauque, P., and Demoulin, B. (see Courbet, G.)
Gadre, R., Dhariwal, S.R., and Basu, N. (see Dhariwal, S.R.)
Gajda, G., Stuchly, M.A., and Stuchly, S.S. Mapping of the near-field pattern in simulated biological tissues 120
Galka, M. New resonant scatterer for measuring microwave magnetic field distributions 243
Galka, M., Chaloupka, H., and Schlendermann, A. (see Chaloupka, H.)
Gallagher, J.G. Mode dispersion of trapezoidal cross-section dielectric optical waveguides by the effective-index method 734
Galloway, K.F., Bhar, T.N., Dat, R., and Koyama, R.Y. (see Bhar, T.N.)
Gambling, W.A., Matsumara, H., and Ragdale, C.M. Zero total dispersion in graded-index single-mode fibres 474
Ganem, H., Evans, B.G., and Dutronc, J. (see Evans, B.G.)

Gardiol, F.E., and Mazumder, S.R. (see Mazumder, S.R.)
Garibotto, G., and Lambarelli, L. Fast on-line implementation of two-dimensional median filtering 24
Garrett, C., Hall, P.S., and Wood, C. (see Hall, P.S.)
Garrido, J., Calleja, E., and Piqueras, J. Argon-ion bombardment effects on the electrical characteristics of platinum-silicon Schottky diodes 815
Gautier, H., Ledu, P., and Maerfeld, C. Two-dimensional acoustic scanning of optical images 186
Gautier, H., Ledu, P., and Maerfeld, C. Two-dimensional high-speed acoustic Fourier transform of optical images 177
Gazey, B.K., Koymen, H., and Smith, B.V. (see Koymen, H.)
Geckeler, S. Compensation of profile dispersion in graded-index optical fibres 682
Geddes, R.C., Cowan, C.F.N., Mavor, J., and Dickson, J.F. Adaptive cancellation of fixed-pattern noise in c.c.d. serial-parallel-serial memory 505
Gelin, Ph., Petenzi, M., and Citerne, J. New rigorous analysis of the step discontinuity in a slab dielectric waveguide 355
Genin, R., and Konn, R. Sinusoidal frequency doubler 47
Genin, R., and Konn, R. (see Konn, R.)
Georgopoulos, C.J. Low-to-high voltage-level shifter and waveform synthesiser 178
Gfeller, F.R., and Bapst, U. Optical-fibre tap with low insertion loss 448
Ghaith, A., Le Comber, P.G., and Spear, W.E. (see Le Comber, P.G.)
Gharavi, H., and Steele, R. Noninteger sampling to subcarrier frequency ratios in d.p.c.m. of Pal signals 483
Giannini, F., D'Inzeo, G., and Sorrentino, R. (see D'Inzeo, G.)
Gibbons, J.F., Tasch, A.F. Jun., Holloway, T.C., and Lee, K.F. (see Tasch, A.F. Jun.)
Gibbs, A.J. Measurement of p.c.m. regenerator crosstalk performance 82
Gibbs, A.J., Millott, L.J., and Nicholson, G. Optimum p.c.m. regenerator performance in presence of crosstalk 490
Gibson, J.A., and Ha, T.T. (see Ha, T.T.)
Gilboa, H., Messer, H., and Bar-Ness, Y. (see Messer, H.)
Glišić, S.G. Error performance of c.p.s.k. system in the presence of interference 97
Glisic, S.G. Performance degradation of decision-directed c.p.s.k. demodulator due to uncompensated time delay of decision circuitry 331
Glisson, T.H., Littlejohn, M.A., Arledge, L.A., and Hauser, J.R. (see Littlejohn, M.A.)
Gloge, D. Effect of chromatic dispersion on pulses of arbitrary coherence 686
Glynn, G.J., Hughes, J.B., and Eilley, E.S. (see Hughes, J.B.)
Gmitrović, M.V., and Milić, M.M. (see Milić, M.M.)
Godone, A., Bava, E., and De Marchi, A. Milliwave Fabry-Perot tuning and modulation by electrically variable external reactance 370
Golecki, I., Roulet, M.E., Schwob, P., and Nicolet, M.-A. (see Roulet, M.E.)
Gómez-Oserio, J.L., and Sánchez-Sinencio, E. (see Sánchez-Sinencio, E.)
Goodman, D.J., and Johnston, J.D. Sidetone expansion for the regulation of talker loudness 492
Goodman, R.M.F. Soft-decision decoding of the teletext character code 108
Gordon, J.P., Nahory, R.E., Pollack, M.A., and Worlock, J.M. Low-noise multistage avalanche photodetector 518
Gosling, W., and Petrovic, V. (see Petrovic, V.)
Goto, N., Ito, K., and Aizawa, N. (see Ito, K.)
Goud, P.A., Gupta, R.K., and Englefield, C.G. (see Gupta, R.K.)
Graffeuil, J., Rossel, P., and Martinot, H. Light-induced effects in GaAs f.e.t.s. 439
Grant, P.M., Massey, N.R., and Mavor, J. (see Massey, N.R.)
Greene, P.D., and Henshall, G.D. (see Henshall, G.D.)
Gregorian, R., and Temes, G.C. Self-equalising sample-and-hold circuits 367
Gregorian, R., and Temes, G.C. (see Temes, G.C.)
Grenez, F. Design of f.i.r. direct-form digital filters with two quantisation steps 124
Grierson, J.R., Cooper, K., Leigh, P.A., O'Sullivan, P.J., and Huish, P.W. High-power 11 GHz GaAs hi-lo Impatt diodes with titanium Schottky barriers 13
Griffiths, J.M. Intermodulation improvement for multichannel television distribution by appropriate channel allocations and the use of 1/3rd line offsets 162
Griffiths, R.J.M., Blenkinsop, I.D., and Wight, D.R. Preparation and properties of GaAs layers for novel f.e.t. structures 629
Grosskopf, G., Baack, C., Elze, G., Kraus, G., Krick, F., and Küller, L. (see Baack, C.)
Grothe, H., Proebster, W., and Harth, W. Mg-doped InGaAsP/InP l.e.d.s. for high-bit-rate optical-communication systems 702
Gruchmann, D., and Weidal, E. (see Weidal, E.)
Gulyaev, Y.V., and Plessky, V.P. Shear surface acoustic waves at the periodically nonuniform boundary between two solids 63
Gupta, H.M., and Mohana Shankar, P. (see Mohana Shankar, P.)
Gupta, R.K., Goud, P.A., and Englefield, C.G. Improvement of intermodulation distortion in microwave m.e.s.f.e.t. amplifiers using gate-bias compensation 741
Gutmann, P. D.C. Squid with high energy resolution 372
Guy, R.F.E., and Ashton, R.W. Crosspolar performance of an elliptical corrugated-horn antenna 400

H

Ha, T.T., and Gibson, J.A. Alternative Kalman controllability criterion for nonderogatory systems 451
Haas, R.W. Improvements on a cryogenically cooled mixer for 80-120 GHz 115
Habibullah, B.S., and Mim, Lim Choo. (see Mim, Lim Choo.)
Hakamada, Y., Nakagawa, K., and Suto, K-I. (see Nakagawa, K.)
Haldar, M.K., and Beck, A.H. Simple derivation of the expression for the synchronous field in circular cylindrical cavity gyrotrons 487
Hall, P.S., Wood, C., and Garrett, C. Wide bandwidth microstrip antennas for circuit integration 458
Hall, T.J. High-linearity multimode optical fibre sensor 405
Hamilton, B., Brunwin, R., Jordan, P., and Peaker, A.R. (see Brunwin, R.)
Hamilton, B., Peaker, A.R., Brunwin, R.F., and Jordan, P. (see Peaker, A.R.)
Hamza, M., Inaba, H., Kobayasi, T., and Hirama, M. (see Inaba, H.)
Hanawa, F., Chida, K., Nakahara, M., and Inagaki, N. (see Chida, K.)
Harms, H., and Papp, A. (see Papp, A.)
Harris, D.J., and Choi, Y.M. Groove-guide connection losses at 100 GHz 687
Harrison, D.D., Richards, W.F., and Lo, Y.T. (see Richards, W.F.)
Hart, B.L. Translinear circuit principle: a reformulation 801
Hart, B.L., and Barker, R.W.J. Universal operational-amplifier convertor technique using supply-current sensing 496
Harth, W., Grothe, H., and Proebster, W. (see Grothe, H.)
Hartog, A.H. Influence of waveguide effects on pulse-delay measurements of material dispersion in optical fibres 632
Hasegawa, F., Furutsuka, T., Higashisaka, A., Aono, Y., and Takayama, Y. (see Furutsuka, T.)
Hashim, R., Moreau, J.B., and Neau, J.C. (see Moreau, J.B.)
Hashimoto, K., Nosu, K., and Ishio, H. (see Nosu, K.)
Haslett, J.W., Rao, M.K.N., and Bruton, L.T. (see Rao, M.K.N.)
Hatakeyama, I., Ohmori, Y., Okazaki, H., and Takata, H. (see Ohmori, Y.)
Hatakeyama, I., and Tachikura, M. (see Tachikura, M.)
Haupt, H., Zwick, U., Auer, W., Riegl, I., and Heitmann, W. (see Zwick, U.)
Hauser, J.R., Littlejohn, M.A., Arledge, L.A., and Glisson, T.H. (see Littlejohn, M.A.)
Hayashi, R., Fujita, M., Nakamura, K., and Ihara, T. (see Fujita, M.)
Heitmann, W., Zwick, U., Auer, W., Riegl, I., and Haupt, H. (see Zwick, U.)
Henaff, J., Feldmann, M., Lacroix, B., and Rebourg, J.C. (see Feldmann, M.)
Henshall, G.D., and Greene, P.D. Low-threshold (Ga, In) (As, P) d.h. lasers emitting at 1.55 μm grown by l.p.e. 621
Henshall, G.D., Thrush, E.J., and Selway, P.R. (see Thrush, E.J.)
Hewit, J.R. Decoupled control of robot movement 670
Hierl, T.L., Berenz, J.J., Kinoshita, J., and Fank, F.B. (see Berenz, J.J.)
Hierl, T.L., Berenz, J.J., Kinoshita, J., and Lee, C.A. (see Berenz, J.J.)
Higashisaka, A., Furutsuka, T., Aono, Y., Takayama, Y., and Hasegawa, F. (see Furutsuka, T.)
Hikita, M., Kinoshita, Y., Tabuchi, T., and Kojima, H. (see Kinoshita, Y.)
Hill, J.J. Comment on alternative approach to the design of switched-capacitor filters 650
Hill, J.R., McCaughan, D.V., Keen, J.M., and White, J.C. Charge-splitting c.c.d. tapped delay lines 204
Hill, J.R., Oliver, C.J., James, A.H., McCaughan, D.V., and White, J.C. (see Oliver, C.J.)
Hirama, M., Inaba, H., Kobayasi, T., and Hamza, M. (see Inaba, H.)
Hirano, Y., and Eto, Y. (see Eto, Y.)
Hlavaty, V., Karpinsky, J., Benes, T., Rozkosny, V., and Sajal, P. (see Karpinsky, J.)
Hlawiczka, P. Gyrotropic waveguide switching elements at optical wavelengths 109
Ho, P-T. Coherent pulse generation with a GaAlAs laser by active modelocking 526
Hodgart, M.S. High-resolution analysis of exponentially decaying transients for physics d.l.t.s. experiments 724
Holford, K. Front ends for Doppler with-sense radar 75
Holgate, D.J., and Yates, K.W. (see Yates, K.W.)
Holloway, T.C., Tasch, A.F. Jun., Lee, K.F., and Gibbons, J.F. (see Tasch, A.F. Jun.)
Holt, A.G.J., and Allen, P.J. (see Allen, P.J.)
Holt, A.R., Upton, S.A.J., and Evans, B.G. (see Upton, S.A.J.)
Hoppitt, C.E., South, C.R., and Lewis, A.V. (see South, C.R.)
Horiguchi, M., Edahiro, T., Chida, K., and Ohmori, Y. (see Edahiro, T.)
Horiguchi, T., Tanifuji, T., and Tokuda, M. (see Tanifuji, T.)
Horikoshi, Y., Machida, S., Yamada, J., Mukai, T., Tsuchiya, H., and Miya, T. (see Machida, S.)
Horton, R. Variation of Lange-coupler geometry with dielectric constant 643
Hosaka, T., Miya, T., Terunuma, Y., and Miyashita, T. (see Miya, T.)
Hosticka, B.J. Dynamic amplifiers in c.m.o.s. technology 819
Hosticka, B.J. Novel dynamic c.m.o.s. amplifier for switched-capacitor integrators 532
Hosticka, B.J., and Brugger, U.W. (see Brugger, U.W.)
Hosticka, B.J., Brugger, U.W., and Moschytz, G.S. (see Brugger, U.W.)
Hudson, J.E. Estimation of linearly constrained parameters via the Kalman filter 319 Errata 478
Hughes, B.T., Vokes, J.C., Wight, D.R., Dawsey, J.R., and Shrubb, S.J.W. (see Vokes, J.C.)
Hughes, F.M., and Allidina, A.Y. (see Allidina, A.Y.)
Hughes, J.B., Eilley, E.S., and Glynn, G.J. Modulo-N counter technique for the u.h.f. band 640
Huish, P.W., Grierson, J.R., Cooper, K., Leigh, P.A., and O'Sullivan, P.J. (see Grierson, J.R.)
Hunsperger, R.G., Irwin, K.G., and Kopeika, N.S. (see Irwin, K.G.)
Hutchings, M.J., and Culshaw, B. (see Culshaw, B.)
Hutchins, R.H., and Millar, C.A. (see Millar, C.A.)

I

Ihara, T., Fujita, M., Nakamura, K., and Hayashi, R. (see Fujita, M.)
Ikuno, H. Propagation constants of guided modes in graded-index fibre with polynomial-profile core 762
Ikuzawa, Y., Chang, N.S., and Matsuo, Y. Amplification of magnetoelastic Love waves by interaction with carrier waves in a layered composite 17
Imoto, N., Machida, S., and Ohmori, Y. (see Machida, S.)
Imoto, N., and Tsuchiya, H. (see Tsuchiya, H.)
Inaba, H., Kobayasi, T., Hirama, M., and Hamza, M. Optical-fibre network system for air-pollution monitoring over a wide area by optical absorption method 749
Inaba, H., Ito, H., and Ogawa, Y. (see Ito, H.)
Inaba, H., Ito, H., Ogawa, Y., and Makita, K. (see Ito, H.)
Inaba, H., Ito, H., Yokoyama, H., and Murata, S. (see Ito, H.)
Inagaki, N., Chida, K., Hanawa, F., and Nakahara, M. (see Chida, K.)
Inagaki, N., Edahiro, T., Sudo, S., Kawachi, M., and Jinguji, K. (see Edahiro, T.)
Ino, M., Makimura, T., Ishibashi, T., and Ohmori, M. 80 GHz silicon diamond-heatsink impatt diodes 2
Irish, R.T. Method of bandwidth extension for the Ruthroff transformer 790
Irven, J., and Robinson, A. Optical fibres prepared by plasma-augmented vapour deposition 252
Irving, D.H., and Karbowiak, A.E. Method of calculating the modal delay for optical fibres with arbitrary refractive-index profiles 160

Irwin, K.G., Kopeika, N.S., and Hunsperger, R.G. Ultraviolet photoconductive detectors in Zn_3P_2 718
Ishibashi, T., Ino, M., Makimura, T., and Ohmori, M. (see Ino, M.)
Ishibashi, T., and Sasaki, A. (see Sasaki, A.)
Ishida, Y., Katsuyama, Y., Ishihara, K., and Miyashita, T. (see Katsuyama, Y.)
Ishihara, K., Katsuyama, Y., Ishida, Y., and Miyashita, T. (see Katsuyama, Y.)
Ishihara, T., Enomoto, T., Yasumoto, M., and Shida, S. (see Enomoto, T.)
Ishii, T., Mitsui, Y., Kobiki, M., Wataze, M., Otsubo, M., and Mitsui, S. (see Mitsui, Y.)
Ishio, H., Nosu, K., and Hashimoto, K. (see Nosu, K.)
Itaya, Y., Katayama, S., and Suematsu, Y. Narrow-beam divergence of the emission from low-threshold GaInAsP/InP double-heterostructure lasers 123
Itaya, Y., Kishino, K., and Suematsu, Y. (see Kishino, K.)
Itaya, Y., Sakakibara, Y., Furuya, K., and Suematsu, Y. (see Sakakibara, Y.)
Ito, H., Ogawa, Y., and Inaba, H. Integrated bistable optical device using Mach-Zehnder interferometric optical waveguide 283
Ito, H., Ogawa, Y., Makita, K., and Inaba, H. Integrated bistable optical multi-vibrator using electro-optically controlled directional coupler switches 791
Ito, H., Yokoyama, H., Murata, S., and Inaba, H. Picosecond optical pulse generation from an r.f. modulated AlGaAs d.h. diode laser 738
Ito, K., Aizawa, N., and Goto, N. Circularly polarised printed array antennas composed of strips and slots 811
Ito, T., and Nakagawa, K. (see Nakagawa, K.)
Ito, T., Shimada, S., Matsumoto, T., Matsushita, S., Washio, K., and Minemura, K. (see Shimada, S.)
Ito, Y., Tanikawa, K., Yamamoto, T., Miura, S., Miyamoto, Y., and Kato, S. (see Tanikawa, K.)
Itoh, K., Tatekura, K., and Matsumoto, T. (see Tatekura, K.)
Iwahara, Y., Nawata, K., and Suzuki, N. (see Nawata, K.)
Iwahara, Y., Suzuki, N., Saruwatari, M., and Nawata, K. (see Suzuki, N.)
Iwai, Z., and Kawaski, Y. Adaptive observer for systems with pure time delay 329
Iwamatsu, S., and Ogawa, M. Silicon-on-sapphire m.o.s.f.e.t.s. fabricated by back-surface laser-anneal technology 827
Iwamura, H., Iwasaki, H., Kubodera, K., Torii, Y., and Noda, J. Simple polarisation-independent optical circulator for optical transmission systems 830
Iwane, G., Kawaguchi, H., Takahei, K., Toyoshima, Y., and Nagai, H. (see Kawaguchi, H.)
Iwasaki, H., Iwamura, H., Kubodera, K., Torii, Y., and Noda, J. (see Iwamura, H.)
Izatt, T.G., and Ball, E. Resolved component indicator based on digitally generated quadrature references 83
Izawa, T., Shimizu, N., and Tsuchiya, H. (see Shimizu, N.)

J

Ja, Y.H. Numerical evaluation of phase centres of corner reflector antennas 1
Ja, Y.H. Phase centre of paraboloidal antennas 784
Jack, M.A., Milne, A.D., and Virr, L.E. Compact helium speech unscrambler using charge-transfer devices 548
Jacob, A., and Begemann, G. (see Begemann, G.)
Jacques, A., Nouchi, I., and D'Auria, L. (see Nouchi, I.)
Jäger, D., and Becker, J.-P. (see Becker, J.-P.)
Jahanbegloo, M., and Temes, G.C. (see Temes, G.C.)
Jakeman, A., and Young, P. Joint parameter/state estimation 582
James, A.H., Oliver, C.J., McCaughan, D.V., Hill, J.R., and White, J.C. (see Oliver, C.J.)
James, G.L. Surface reactance of corrugated planes 751
James, S., and Wilson, I.H. Fine tuning of s.a.w. resonators using argon ion bombardment 683
Jervis, T.R., Woodard, D.W., and Eastman, L.F. Effects of ion implantation on deep levels in GaAs 619
Jeunhomme, L. Bandwidth-limited operation of nonideal graded-index fibres 149
Jeunhomme, L. Dispersion minimisation in single-mode fibres between 1.3 μm and 1.7 μm 478
Jin, Y.I. New adaptive equaliser with infinite impulse response 557
Jinguji, K., Edahiro, T., Sudo, S., Kawachi, M., and Inagaki, N. (see Edahiro, T.)
John, S. (Mrs), and Parthasarathy, R. System reduction by Routh approximation and modified Cauer continued fraction 691
Johnston, J.D., and Goodman, D.J. (see Goodman, D.J.)
Jordan, J.R. Discrete Fourier transform of correlation functions 196
Jordan, J.R. Integrated-circuit relay correlator for measurement-system applications 366
Jordan, P., Brunwin, R., Hamilton, B., and Peaker, A.R. (see Brunwin, R.)
Jordan, P., Peaker, A.R., Brunwin, R.F., and Hamilton, B. (see Peaker, A.R.)
Jordan, P.A., and Underhill, M.J. (see Underhill, M.J.)
Joshi, J.S., and Turner, J.A. High peripheral power density GaAs f.e.t. oscillator 163
Jull, E.V. Reflection circular polarisers 423

K

Kagiwada, R.S., Yen, K.H., and Lau, K.F. (see Yen, K.H.)
Kaminow, I.P., Nahory, R.E., Pollack, M.A., Stulz, L.W., and DeWinter, J.C. Single-mode c.w. ridge-waveguide laser emitting at 1.55 μm 763
Kaminow, I.P., Simpson, J.R., Presby, H.M., and MacChesney, J.B. Strain birefringence in single-polarisation germanosilicate optical fibres 677
Kanamori, M., Kawashima, M., and Matsumura, M. (see Kawashima, M.)
Kanbe, H., Susa, N., Nishioka, T., and Ohmachi, Y. (see Susa, N.)
Kanbe, H., Susa, N., and Yamauchi, Y. (see Susa, N.)
Kano, H., Yamada, Jun-ichi., Machida, S., Mukai, T., and Sugiyama, K. (see Yamada, Jun-ichi.)
Kaplan, B.Z. Rotation of a waveform generator 158
Karbowiak, A.E., and Irving, D.H. (see Irving, D.H.)
Karpinsky, J., Benes, T., Hlavaty, V., Rozkosny, V., and Sajal, P. Discrete-time linear-quadratic optimal tracking problem using future desired output values 316
Kashima, N., and Uchida, N. Relation between splice loss and mode conversion in a graded-index optical fibre 336
Katayama, S., Itaya, Y., and Suematsu, Y. (see Itaya, Y.)
Katayama, Y., Oikawa, S., and Fujiki, M. (see Oikawa, S.)
Kato, S., Miyamoto, Y., Tanikawa, K., and Sei, H. (see Miyamoto, Y.)
Kato, S., Tanikawa, K., Ito, Y., Yamamoto, T., Miura, S., and Miyamoto, Y. (see Tanikawa, K.)
Kato, Y., Kitayama, K-I., Seikai, S., and Uchida, N. Novel method for measuring cutoff wavelength of HE_{21}-, TE_{01}-and TM_{01}- modes 410
Katsuyama, Y. Single-mode propagation in 2-mode region of optical fibre by using mode filter 442
Katsuyama, Y., Ishida, Y., Ishihara, K., and Miyashita, T. Suitable parameters of single-mode optical fibre 94
Kawachi, M., Edahiro, T., Sudo, S., Jinguji, K., and Inagaki, N. (see Edahiro, T.)
Kawachi, M., Edahiro, T., Sudo, S., and Takata, H. (see Edahiro, T.)
Kawachi, M., Shibata, N., Sudo, S., and Edahiro, T. (see Shibata, N.)
Kawaguchi, H., Takahei, K., Toyoshima, Y., Nagai, H., and Iwane, G. Room-temperature c.w. operation of InP/InGaAsP/InP double heterostructure diode lasers emitting at 1.55 μm 669
Kawakami, T., and Okamura, M. InP/Al_2O_3 n-channel inversion-mode m.i.s.f.e.t.s. using sulphur-diffused source and drain 502
Kawakami, T., and Okamura, M. n-channel formation of semi-insulating InP surface by m.i.s.f.e.t. 743
Kawana, A., Okamoto, K., Edahiro, T., and Miya, T. (see Okamoto, K.)
Kawase, M., Yamashita, K., Nishimura, M., Yamanishi, T., and Sugawara, Y. Optical loss change caused by hydraulic pressure in multimode optical fibres 208
Kawashima, M., Kanamori, M., and Matsumura, M. Depletion-type m.o.s.f.e.t.s. for low-temperature operation 759
Kawaski, Y., and Iwai, Z. (see Iwai, Z.)
Keen, J.M., Hill, J.R., McCaughan, D.V., and White, J.C. (see Hill, J.R.)
Keen, N.J., Kelly, W.M., and Wrixon, G.T. Pumped Schottky diodes with noise temperatures of less than 100 K at 115 GHz 689
Kellner, W. Noninverting integrators with improved high-frequency response 257
Kelly, W.M., Keen, N.J., and Wrixon, G.T. (see Keen, N.J.)
Kendall, D.L., and Aceves, M. (see Aceves, M.)
Kernweis, N., and McIlvenna, J. (see McIlvenna, J.)
Khoe, K.D. Practical machine for electric arc splicing of optical fibres in the field 152
Khuri-Yakub, B.T., and Chou, C.H. Ultrasonic attenuation of piezoelectric PVF_2 films at high frequencies 308
Kimura, T., Machida, S., and Nagai, H. (see Machida, S.)
Kimura, T., Yamada, Jun-Ichi., Machida, S., and Takata, H. (see Yamada, Jun-Ichi.)
King, R.J., and Appel-Hansen, J. (see Appel-Hansen, J.)
Kinoshita, J., Berenz, J.J., Hierl, T.L., and Fank, F.B. (see Berenz, J.J.)
Kinoshita, J., Berenz, J.J., Hierl, T.L., and Lee, C.A. (see Berenz, J.J.)
Kinoshita, Y., Hikita, M., Tabuchi, T., and Kojima, H. Broadband resonant filter using surface-shear-wave mode and twin-turn reflector 130
Kirkby, P.A. Channelled-substrate narrow-stripe GaAs/GaAlAs injection lasers with extremely low threshold currents 824
Kiruthi, G., Czarnul, Z., and Newcomb, R.W. (see Czarnul, Z.)
Kishino, K., Suematsu, Y., and Itaya, Y. Mesa-substrate buried-heterostructure GaInAsP/InP injection lasers 134
Kitayama, K-I., Kato, Y., Seikai, S., and Uchida, N. (see Kato, Y.)
Kneidinger, M., Lechner, A., Thim, H.W., Kuch, R., and Wernisch, J. (see Lechner, A.)
Knight, R.B.D., and Stockton, J.R. (see Stockton, J.R.)
Knott, K.F. Evidence of collector-base junction burst noise 198
Kobayashi, M., and Terui, H. (see Terui, H.)
Kobayasi, T., Inaba, H., Hirama, M., and Hamza, M. (see Inaba, H.)
Kobiki, M., Mitsui, Y., Wataze, M., Otsubo, M., Ishii, T., and Mitsui, S. (see Mitsui, Y.)
Kojima, H., Kinoshita, Y., Hikita, M., and Tabuchi, T. (see Kinoshita, Y.)
Konn, R., and Genin, R. High-performance aperiodic frequency multiplying 187
Konn, R., and Genin, R. (see Genin, R.)
Kooi, P.S., Leong, M.S., and Yeo, T.S. Dipole-excited short backfire antenna with corrugated rim 421
Kooi, P.S., and Leong, M.S. (see Leong, M.S.)
Kopeika, N.S., Irwin, K.G., and Hunsperger, R.G. (see Irwin, K.G.)
Kostić, I.M. Fourier-series representation for phase density of sum of signal, noise and interference 541 Errata 731
Kotzebue, K.L., and Ehlers, E.R. Simple model of large-signal properties of 1 W f.e.t. at 5 GHz 237
Koyama, R.Y., Bhar, T.N., Dat, R., and Galloway, K.F. (see Bhar, T.N.)
Koymen, H., Smith, B.V., and Gazey, B.K. Equivalent circuits for high-frequency sonar transducers 600
Kpodzo, E., Begemann, G., and Schünemann, K. Millimetre-wave phase modulators with lumped-element circuitry 48
Kraus, G., Baack, C., Elze, G., Grosskopf, G., Krick, F., and Küller, L. (see Baack, C.)
Kressel, H., and Olsen, G.H. (see Olsen, G.H.)
Krick, F., Baack, C., Elze, G., Grosskopf, G., Kraus, G., and Küller, L. (see Baack, C.)
Krowne, C.M. Extending the low-frequency range of GaAs f.e.t. broadband microwave amplifiers using microstrip transmission lines 197
Krowne, C.M. Network condition for counter-clockwise reflection-coefficient behaviour: application to oscillators 114
Ku, J.W., Bhattacharya, P.K., Owen, S.J.T., Chiao, S.H., and Yeats, R. (see Bhattacharya, P.K.)
Kubodera, K., Iwamura, H., Iwasaki, H., Torii, Y., and Noda, J. (see Iwamura, H.)
Kubota, E., Tsubaki, K., and Sugiyama, K. (see Tsubaki, K.)
Kuch, R., Lechner, A., Kneidinger, M., Thim, H.W., and Wernisch, J. (see Lechner, A.)
Kudo, K., Yoshikawa, A., Tamama, T., Mizushima, Y., and Shigematsu, T. (see Yoshikawa, A.)
Kular, S.S., Sealy, B.J., Badawi, M.H., Stephens, K.G., Sadana, D., and Booker, G.R. Laser annealing of capped and uncapped GaAs 413
Küller, L., Baack, C., Elze, G., Grosskopf, G., Kraus, G., and Krick, F. (see Baack, C.)
Kwan, H-K. Method for designing recursive digital filters with short wordlength 128 Errata 361
Kwok, P.C.K., and Brandon, P.S. Eigenvalues of noise covariance matrix of linear array in the presence of two directional interferences 50
Kwok, P.C.K., and Brandon, P.S. Optimal radiation pattern of an array in the presence of two directional interferences 251

Kwok, P.C.K., and Lai, J.P.K. Dual-mode transmission technique for Chinese ideographs in a teletext system 268

L

Lacroix, B., Feldmann, M., Henaff, J., and Rebourg, J.C. (see Feldmann, M.)
Ladany, I., Furman, T.R., and Marinelli, D.P. Internal stress and degradation in short-wavelength AlGaAs double-heterojunction devices 342
Lai, J.P.K., and Kwok, P.C.K. (see Kwok, P.C.K.)
Lainé, D.C., and Al-Jumaily, A.M. Injection priming of a pulsed molecular-beam maser oscillator 21
Laker, K.R., Schaumann, R., and Brand, J.R. (see Schaumann, R.)
Lambarelli, L., and Garibotto, G. (see Garibotto, G.)
Lane, W.A., Salama, C.A.T., and Dmitrevsky, S. On-resistance of V-v.m.o.s. power transistors 601
Larsen, F.H. Improved algorithm for probe-corrected spherical near-field/far-field transformation 588
Lau, K.F., Yen, K.H., and Kagiwada, R.S. (see Yen, K.H.)
Lau, P-K., and Allnutt, J. Attenuation and depolarisation data obtained on 12GHz satellite-earth paths at four Canadian locations 565
Laurinvičius, A., and Balynas, V. Semiconductor isolator based on cyclotron resonance phenomenon 15
Laviron, M., Derewonko, H., and Lepage, J. (see Derewonko, H.)
Le Comber, P.G., Spear, W.E., and Ghaith, A. Amorphous-silicon field-effect device and possible application 179
Le Noane, G. Low-loss optical-fibre connection systems 12
Lechner, A., Kneidinger, M., Thim, H.W., Kuch, R., and Wernisch, J. Microwave detection with n-GaAs/N-GaAlAs heterojunctions 254
Ledu, P., Gautier, H., and Maerfeld, C. (see Gautier, H.)
Ledu, P., Gautier, H., and Maerfeld, C. (see Gautier, H.)
Lee, C.A., Berenz, J.J., Kinoshita, J., and Hierl, T.L. (see Berenz, J.J.)
Lee, K.F., Tasch, A.F. Jun., Holloway, T.C., and Gibbons, J.F. (see Tasch, A.F. Jun.)
Lee, Man Shek Switched-capacitor filters using floating-inductance simulation circuits 644
Lee, T.P., Campbell, J.C., Ogawa, K., McCormick, A.R., Dentai, A.G., and Burrus, C.A. Dual-channel 1.5 Mb/s lightwave receiver employing an InGaAsP wavelength-demultiplexing detector 388
Lee, T.P., Burrus, C.A., and Dentai, A.G. (see Burrus, C.A.)
Leheny, R.F., Nahory, R.E., and Pollack, M.A. $In_{0.53}Ga_{0.47}As$ p-i-n photodiodes for long-wavelength fibre-optic systems 713
Leigh, P.A., Grierson, J.R., Cooper, K., O'Sullivan, P.J., and Huish, P.W. (see Grierson, J.R.)
Lemanov, V.V., Dobrovolsky, A.A., Smolensky, G.A., and Sherman, A.B. (see Dobrovolsky, A.A.)
Leong, M.S., and Kooi, P.S. Rectangular-waveguide-excited short backfire antenna with corrugated rim 533
Leong, M.S., Kooi, P.S., and Yeo, T.S. (see Kooi, P.S.)
Lepage, J., Derewonko, H., and Laviron, M. (see Derewonko, H.)
Lever, K.V., and Trivedi, M. (see Trivedi, M.)
Lewis, A.V., South, C.R., and Hoppitt, C.E. (see South, C.R.)
Lewis, B., Morgan, D.P., and Metcalfe, J.G. (see Morgan, D.P.)
Lewis, J.E., and Rengarajan, S.R. (see Rengarajan, S.R.)
Lewis, P.A., and Underhill, M.J. (see Underhill, M.J.)
Ligtenberg, H.C.G., and Snijder, J. Measurement arrangement for direct capacitance/surface-potential recording on m.o.s. capacitor 523
Lile, D.L., Meiners, L.G., and Collins, D.A. (see Meiners, L.G.)
Lilley, P., Sharpe, C.D., Elliott, C.R., and Ambridge, T. (see Sharpe, C.D.)
Lin, C., Cohen, L.G., and French, W.G. (see Cohen, L.G.)
Lindner, G., Deutsch, G., Lübke, K., and Thim, H.W. (see Deutsch, G.)
Littlejohn, M.A., Arledge, L.A., Glisson, T.H., and Hauser, J.R. Influence of central valley effective mass and alloy scattering on transient drift velocity in $Ga_{1-x}In_xP_{1-y}As_y$ 586
Lo, Y.T., Richards, W.F., and Harrison, D.D. (see Richards, W.F.)
Love, A.W. Quadratic phase error loss in circular apertures 276
Love, J.D., Sammut, R.A., and Snyder, A.W. Birefringence in elliptically deformed optical fibres 615
Lovelace, D.F., Thompson, G.H.B., and Turley, S.E.H. (see Thompson, G.H.B.)
Lovelace, D.F., Turley, S.E.H., and Thompson, G.H.B. (see Turley, S.E.H.)
Lübke, K., Deutsch, G., Lindner, G., and Thim, H.W. (see Deutsch, G.)
Luukkala, M., and Penttinen, A. Photoacoustic microscope 325
Lyndin, N.M., Čtyroký, J., Čada, M., Sychugov, V.A., and Schroefel, J. (see Čtyroký, J.)

M

McCaughan, D.V., Hill, J.R., Keen, J.M., and White, J.C. (see Hill, J.R.)
McCaughan, D.V., Oliver, C.J., James, A.H., Hill, J.R., and White, J.C. (see Oliver, C.J.)
MacChesney, J.B., Kaminow, I.P., Simpson, J.R., and Presby, H.M. (see Kaminow, I.P.)
McCormick, A.R., Lee, T.P., Campbell, J.C., Ogawa, K., Dentai, A.G., and Burrus, C.A. (see Lee, T.P.)
McCormick, G.C. Relationship of differential reflectivity to correlation in dual-polarisation radar 265
Macdonald, R.I. Bidirectional analogue optical transmission using semiconductor junction transceivers 121
McEwan, N.J., and Alves, A.P. (see Alves, A.P.)
Machida, S., Imoto, N., and Ohmori, Y. Multimode fibre baseband frequency response measurement with single frequency output extracted from modulated InGaAsP laser 607
Machida, S., Nagai, H., and Kimura, T. Modulation characteristics of InGaAsP/InP l.e.d.s. at 1.5 μm wavelength 175
Machida, S., Yamada, J., Mukai, T., Horikoshi, Y., Tsuchiya, H., and Miya, T. 1.5 m optical transmission experiments using very low-loss single-mode fibres 219
Machida, S., Yamada, Jun-Ichi., Kimura, T., and Takata, H. (see Yamada, Jun-Ichi.)
Machida, S., Yamada, Jun-ichi., Mukai, T., Kano, H., and Sugiyama, K. (see Yamada, Jun-ichi.)
Maciejko, R., and Conn, D.R. (see Conn, D.R.)
McIlvenna, J., and Kernweis, N. Modified circular microstrip antenna elements 207
Macksey, H.M., Doerbeck, F.H., Brehm, G.E., and Frensley, W.R. (see Doerbeck, F.H.)
McLachlan, R.V. Simplified FEXT calculations 545
McMahon, R.A., and Ahmed, H. Electron-beam annealing of ion-implanted silicon 45
McMahon, R.A., Ahmed, H., Speight, J.D., and Dobson, R.M. Scanning-electron-beam annealing of ion-implanted p-n junction diodes 433
Maerfeld, C., Gautier, H., and Ledu, P. (see Gautier, H.)
Maerfeld, C., Gautier, H., and Ledu, P. (see Gautier, H.)
Maillot, P., d'Auria, L., and Chevalier, G. (see d'Auria, L.)
Majerfeld, A., Westbrook, L.D., and Robson, P.N. (see Westbrook, L.D.)
Makimoto, M., Nakabe, K., and Nishiki, S. 800 MHz v.c.o. for land mobile radio synthesisers 460
Makimura, T., Ino, M., Ishibashi, T., and Ohmori, M. (see Ino, M.)
Makita, K., Ito, H., Ogawa, Y., and Inaba, H. (see Ito, H.)
Malah, D., and Schwarz, T. (see Schwarz, T.)
Mamola, G., Alcuri, L., and Randazzo, E. (see Alcuri, L.)
Manes, G.F., and Atzeni, C. Baseband compatible s.a.w. processors 661
Manes, G.F., and Atzeni, C. Discrete frequency synthesis using an analogue r.o.m. 350
Marie, K.H.S., Bennett, J.C., and Anderson, A.P. Digital processing technique for suppressing the interfering outputs in the image from an inline hologram 241
Marinelli, D.P., Ladany, I., and Furman, T.R. (see Ladany, I.)
Marquardt, R. Transfer functions with equiripple passband and very low Q-factor for economical active filters 618
Marriott, S.P., and Birch, J. (see Birch, J.)
Marschall, P., Schlosser, E., and Wölk, C. New diffusion-type stripe-geometry injection laser 38
Marshall, S.A. Comment on Stable reduced-order Pade approximants using the Routh-Hurwitz array 501
Martin, K., and Sedra, A.S. Strays-insensitive switched-capacitor filters based on bilinear Z-transform 365
Martinot, H., Graffeuil, J., and Rossel, P. (see Graffeuil, J.)
Masetti, G., Calzolari, P.U., and Severi, M. (see Calzolari, P.U.)
Massaro, P.A., and Picciarelli, V. General class of multisection quarter-wave transformers for impedance matching at microwave frequencies 222
Massaro, P.A., and Picciarelli, V. Ultraspherical tapers 289
Massey, N.R., Grant, P.M., and Mavor, J. C.C.D. adaptive filter employing parallel coefficient updating 573
Matley, W., Williamson, S.E., and Bywater, R.E.H. (see Williamson, S.E.)
Matley, W., Williamson, S.E., and Bywater, R.E.H. (see Williamson, S.E.)
Matsumara, H., Gambling, W.A., and Ragdale, C.M. (see Gambling, W.A.)
Matsumoto, T. Structure simplification of optical isolator coupled with laser diode 625
Matsumoto, T., Shimada, S., Ito, T., Matsushita, S., Washio, K., and Minemura, K. (see Shimada, S.)
Matsumoto, T., Tatekura, K., and Itoh, K. (see Tatekura, K.)
Matsumoto, Y., Taguchi, K., and Nishida, K. (see Taguchi, K.)
Matsumura, M., Kawashima, M., and Kanamori, M. (see Kawashima, M.)
Matsuo, Y., Ikuzawa, Y., and Chang, N.S. (see Ikuzawa, Y.)
Matsushima, Y., Akiba, S., Sakai, K., and Yamamoto, T. (see Akiba, S.)
Matsushita, S., Shimada, S., Matsumoto, T., Ito, T., Washio, K., and Minemura, K. (see Shimada, S.)
Matthews, P.A., and Ashall, C.P. (see Ashall, C.P.)
Matthijsse, P., and De Blok, C.M. Field measurement of splice loss applying the backscattering method 795
Mauersberger, W. Generalised correlation model for designing 2-dimensional image coders 664
Mavor, J., Cowan, C.F.N., and Arthur, J.W. (see Cowan, C.F.N.)
Mavor, J., and Denyer, P.B. (see Denyer, P.B.)
Mavor, J., Geddes, R.C., Cowan, C.F.N., and Dickson, J.F. (see Geddes, R.C.)
Mavor, J., Massey, N.R., and Grant, P.M. (see Massey, N.R.)
Mavor, J., Tang, T.G., and Yeow, Y.T. (see Tang, T.G.)
Mazumder, S.R., and Gardiol, F.E. Coupled-line circuit with adjustable input conductance 91
Mazzone, A.M., and Rees, H.D. Overlength-mode transferred-electron harmonic generators 813
Meignant, D., Boccon-Gibod, D., and Bourgeois, J.M. Trap localisation in the active layer of GaAs microwave f.e.t.s. 779
Meiners, L.G., Lile, D.L., and Collins, D.A. Microwave gain from an n-channel enhancement-mode InP m.i.s.f.e.t. 578
Melek, M., Anderson, A.P., and Brown, B.H. (see Anderson, A.P.)
Mengali, U., and Pirani, G. Simple formulas for jitter accumulation in a chain of regenerative repeaters in optical-fibre transmission systems 561
Messer, H., Bar-Ness, Y., and Gilboa, H. New s.a.w. time-inversion system 214
Metcalfe, J.G., Morgan, D.P., and Lewis, B. (see Morgan, D.P.)
Mezzetti, M., Cancellieri, G., Someda, C.G., and Zoboli, M. (see Cancellieri, G.)
Mikoshiba, N., and Sasaki, H. (see Sasaki, H.)
Miler, M., and Skalsky, M. Stigmatically focusing grating coupler 275
Milić, M.M., and Gmitrović, M.V. Evaluation of the transient response of linear stationary systems to a class of excitations 614
Millar, C.A., and Hutchins, R.H. As_2S_3-p.e.s. sandwich ribbon fibre for coupling high-refractive-index integrated optics 60
Miller, D.M., and Muzio, J.C. Distribution of symmetry information in spectrum of Boolean function 816
Miller, R.L., Reed, I.S., and Truong, T.K. (see Reed, I.S.)
Miller, R.L., Truong, T.K., and Reed, I.S. (see Truong, T.K.)
Millott, L.J., Gibbs, A.J., and Nicholson, G. (see Gibbs, A.J.)
Milne, A.D., Jack, M.A., and Virr, L.E. (see Jack, M.A.)
Mim, Lim Choo., and Habibullah, B.S. Design of optimal controller for linear single-input system 660
Minasian, R.A. Modelling the m.e.s.f.e.t. output nonlinearity 515
Minemura, K., Shimada, S., Matsumoto, T., Ito, T., Matsushita, S., and Washio, K. (see Shimada, S.)
Minowa, J., Fujii, Y., and Suzuki, N. (see Fujii, Y.)
Minowa, J., Fujii, Y, Aoyama, T., and Doi, K. (see Fujii, Y)

Mitsui, S., Mitsui, Y., Kobiki, M., Wataze, M., Otsubo, M., and Ishii, T. (see Mitsui, Y.)
Mitsui, Y., Kobiki, M., Wataze, M., Otsubo, M., Ishii, T., and Mitsui, S. Flip-chip mounted GaAs power f.e.t. with improved performance in X- to Ku-band 461
Miura, S., Tanikawa, K., Ito, Y., Yamamoto, T., Miyamoto, Y., and Kato, S. (see Tanikawa, K.)
Miya, T., Terunuma, Y., Hosaka, T., and Miyashita, T. Ultimate low-loss single-mode fibre at 1.55 μm 106
Miya, T., Machida, S., Yamada, J., Mukai, T., Horikoshi, Y., and Tsuchiya, H. (see Machida, S.)
Miya, T., Okamoto, K., Edahiro, T., and Kawana, A. (see Okamoto, K.)
Miyamoto, Y., Tanikawa, K., Sei, H., and Kato, S. Meander-channel c.c.d. (m.c.c.d.) recursive filter 320
Miyamoto, Y., Tanikawa, K., Ito, Y., Yamamoto, T., Miura, S., and Kato, S. (see Tanikawa, K.)
Miyashita, T., Katsuyama, Y., Ishida, Y., and Ishihara, K. (see Katsuyama, Y.)
Miyashita, T., Miya, T., Terunuma, Y., and Hosaka, T. (see Miya, T.)
Mizushima, Y., Yoshikawa, A., Tamama, T., Kudo, K., and Shigematsu, T. (see Yoshikawa, A.)
Mohamed, A., and Bowron, P (see Bowron, P)
Mohana Shankar, P., and Gupta, H.M. Information retrieval in the presence of speckle and quantum noise 464
Moon, J.R. Application of the Cramer-Rao bound to target motion analysis 236
Moon, R.L., and Saxena, R.R. (see Saxena, R.R.)
Moore, R.A., Armstrong, B.M., and Wakefield, J. (see Armstrong, B.M.)
Moore, W.R. Fault-tolerant digital clocking systems 722
Moraga, C. Characterisation of ternary threshold functions using a partial spectrum 803
Moraga, C. Spectral characterisation of ternary threshold functions 712
Moreau, J.B., Hashim, R., and Neau, J.C. New electrostatic probe for absolute measurement of amplitude of surface acoustic wave 155
Morgan, D.P., Lewis, B., and Metcalfe, J.G. Fundamental charge distributions for surface-wave interdigital transducer analysis 583
Morkoc, H., Andrews, J., and Aebi, V. GaAs m.e.s.f.e.t. prepared by organometallic chemical vapour deposition 705
Morra, P., Costa, B., Esposto, F., and D'Orio, C. (see Costa, B.)
Morris, A.S., and Sterling, M.J.H. Model tuning using the extended Kalman filter 201
Morris, D.G., Dyott, R.B., and Cozens, J.R. (see Dyott, R.B.)
Moschytz, G.S., Brugger, U.W., and Hosticka, B.J. (see Brugger, U.W.)
Mossaheb, S. Boundedness properties of nonlinear multivariable systems 803
Mouly, J.M., Azan, F., and Salset, J. (see Azan, F.)
Mudaly, S.S. Novel computer-based infrared pedestrian data-acquisition system 371
Mukai, T., Machida, S., Yamada, J., Horikoshi, Y., Tsuchiya, H., and Miya, T. (see Machida, S.)
Mukai, T., Yamada, Jun-ichi., Machida, S., Kano, H., and Sugiyama, K. (see Yamada, Jun-ichi.)
Mukhopadhyay, S. P.I.D. equivalent of optimal regulator Errata 578
Munoz-Rodriguez, D. Multilevel code for high information rates 272
Murata, H. Moulded optical-fibre connectors using rods and balls 369
Murata, S., Ito, H., Yokoyama, H., and Inaba, H. (see Ito, H.)
Murukutla, N.L.M., and Durrani, T.S. (see Durrani, T.S.)
Murukutla, N.L.M., and Durrani, T.S. (see Durrani, T.S.)
Muska, W.M., and Abbott, S.M. (see Abbott, S.M.)
Muzio, J.C., and Miller, D.M. (see Miller, D.M.)

N

Nackoney, O.G., and Davidson, D. Rain attenuation of 12/14 GHz satellite video transmissions 703
Nagai, H., Kawaguchi, H., Takahei, K., Toyoshima, Y., and Iwane, G. (see Kawaguchi, H.)
Nagai, H., Machida, S., and Kimura, T. (see Machida, S.)
Nahory, R.E., Pollock, M.A., and DeWinter, J.C. Temperature dependence of InGaAsP double-heterostructure laser characteristics 695
Nahory, R.E., Capasso, F., and Pollack, M.A. (see Capasso, F.)
Nahory, R.E., Gordon, J.P., Pollack, M.A., and Worlock, J.M. (see Gordon, J.P.)
Nahory, R.E., Kaminow, I.P., Pollack, M.A., Stulz, L.W., and DeWinter, J.C. (see Kaminow, I.P.)
Nahory, R.E., Leheny, R.F., and Pollack, M.A. (see Leheny, R.F.)
Nakabe, K., Makimoto, M., and Nishiki, S. (see Makimoto, M.)
Nakagawa, K., Hakamada, Y., and Suto, K-I. 800 Mb/s fibre transmission test using low-loss and low-dispersion single-mode cable 747
Nakagawa, K., and Ito, T. Detailed evaluation of an attainable repeater spacing for fibre transmission at 1.3 μm and 1.55 μm wavelengths 776
Nakahara, M., Chida, K., Hanawa, F., and Inagaki, N. (see Chida, K.)
Nakamura, K., Fujita, M., Ihara, T., and Hayashi, R. (see Fujita, M.)
Naldi, C., Filicori, F., and Scalas, M.R. (see Filicori, F.)
Nandi, R. Comment on multifunction active R filter with two operational amplifiers 261
Nandi, R. Insensitive grounded-capacitor simulation of grounded inductors using current conveyors 693
Nandi, R. New equal-valued earthed-capacitor notch network using d.v.c.c.s./d.v.c.v.s. 667
Nawata, K., Iwahara, Y., and Suzuki, N. Ceramic capillary splices for optical fibres 470
Nawata, K., Suzuki, N., Iwahara, Y., and Saruwatari, M. (see Suzuki, N.)
Neau, J.C., Moreau, J.B., and Hashim, R. (see Moreau, J.B.)
Nedungadi, A. Accurate translinear sinusoidal frequency doubler 228
Nedungadi, A. Comment on Active simulation of inductors using current conveyor 112
Nelson, B.P., and White, K.I. (see White, K.I.)
Neri, R. Input impedance of thin dipoles by moment method 418
Neuman, V., Parriaux, O., and Walpita, L.M. Double-alkali effect: influence on index profile of ion-exchanged waveguides 704
Newcomb, R.W., Czarnul, Z., and Kiruthi, G. (see Czarnul, Z.)
Newns, G.R., Ainslie, B.J., Day, C.R., France, P.W., and Beales, K.J. (see Ainslie, B.J.)
Ngan, Y.C. Two-diode power combining near 140 GHz 376
Nguyen, D.T. Engineering approach to the L_∞-norm scaling of bilinear digital filters 353
Nicholson, G., Gibbs, A.J., and Millott, L.J. (see Gibbs, A.J.)
Nicholson, H., and Fernando, K.V.M. (see Fernando, K.V.M.)
Nicolet, M.-A., Roulet, M.E., Schwob, P., and Golecki, I. (see Roulet, M.E.)
Nightingale, C., and Fidler, J.K. (see Fidler, J.K.)
Nikias, C.L., and Fincham, W.F. Compact polynomial forms of sensitivity criteria 23
Nikias, C.L., and Fincham, W.F. (see Fincham, W.F.)
Nishida, K., Taguchi, K., and Matsumoto, Y. (see Taguchi, K.)
Nishida, S., Yoneyama, T., and Suzuki, T. (see Yoneyama, T.)
Nishiki, S., Makimoto, M., and Nakabe, K. (see Makimoto, M.)
Nishimoto, C.K., Bandy, S.G., and Collins, D.M. (see Bandy, S.G.)
Nishimura, M., Kawase, M., Yamashita, K., Yamanishi, T., and Sugawara, Y. (see Kawase, M.)
Nishioka, T., Susa, N., Kanbe, H., and Ohmachi, Y. (see Susa, N.)
Noda, J., Iwamura, H., Iwasaki, H., Kubodera, K., and Torii, Y. (see Iwamura, H.)
Nomair, M., Bahnas, Y.Z., and Soliman, A.M. Noise relations of inverse active networks and complementary networks 18
Norman, S.R., Payne, D.N., Adams, M.J., and Smith, A.M. Fabrication of single-mode fibres exhibiting extremely low polarisation birefringence 309
Norton, J.P. Recursive linear estimation of linearly constrained parameters 715
Nosu, K., Ishio, H., and Hashimoto, K. Multireflection optical multi/demultiplexer using interference filters 414
Nouchi, I., Jacques, A., and D'Auria, L. Characteristics against length of silicone-clad silica optical fibres 315
Nussbaumer, H.J. D.F.T. computation by fast polynomial transform algorithms 701

O

O'Neill, K., Arlett, P.L., Walton, A., and Elkins, K. (see Arlett, P.L.)
O'Reilly, J.J., Cochrane, P., and Barley, I.W. (see Cochrane, P.)
O'Sullivan, P.J., Grierson, J.R., Cooper, K., Leigh, P.A., and Huish, P.W. (see Grierson, J.R.)
Ogawa, K., and Chinnock, E.L. GaAs f.e.t. transimpedance front-end design for a wideband optical receiver 650
Ogawa, K., Lee, T.P., Campbell, J.C., McCormick, A.R., Dentai, A.G., and Burrus, C.A. (see Lee, T.P.)
Ogawa, K., and Venkatesan, T.N.C. (see Venkatesan, T.N.C.)
Ogawa, M., and Iwamatsu, S. (see Iwamatsu, S.)
Ogawa, T., Takayama, Y., and Aono, Y. (see Takayama, Y.)
Ogawa, Y., Ito, H., and Inaba, H. (see Ito, H.)
Ogawa, Y., Ito, H., Makita, K., and Inaba, H. (see Ito, H.)
Ohmachi, Y., Susa, N., Kanbe, H., and Nishioka, T. (see Susa, N.)
Ohmori, M., Ino, M., Makimura, T., and Ishibashi, T. (see Ino, M.)
Ohmori, Y., Okazaki, H., Hatakeyama, I., and Takata, H. Very low OH content P_2O_5-doped silica fibres 616
Ohmori, Y., Edahiro, T., Horiguchi, M., and Chida, K. (see Edahiro, T.)
Ohmori, Y., Machida, S., and Imoto, N. (see Machida, S.)
Oikawa, S., Fujiki, M., and Katayama, Y. Plastic optical fibre with improved transmittance 829
Okamoto, K., Edahiro, T., Kawana, A., and Miya, T. Dispersion minimisation in single-mode fibres over a wide spectral range 729
Okamura, M., and Kawakami, T. (see Kawakami, T.)
Okamura, M., and Kawakami, T. (see Kawakami, T.)
Okazaki, H., Ohmori, Y., Hatakeyama, I., and Takata, H. (see Ohmori, Y.)
Olcayto, E. Recursive formulae for ladder-network optimisation 249
Olcaytug, F., Riedling, K., and Fallmann, W. (see Riedling, K.)
Oliver, C.J., James, A.H., McCaughan, D.V., Hill, J.R., and White, J.C. Integrating-input technique for c.c.d. 497
Olsen, G.H., and Kressel, H. Vapour-grown 1.3 μm InGaAsP/InP avalanche photodiodes 141
Olver, A.D., and Saleeb, A.A. Lens-type compact antenna range 409
Opielka, D., and Rittich, D. Low-loss optical Y-branch 757
Osowski, S. Rational admittance function realisation using two operational amplifiers 85
Osowski, S. Resistive hybrid matrix realisation using operational amplifiers 426
Osowski, S. Voltage transfer function realisation using active R network: flow-graph technique 416
Otsubo, M., Mitsui, Y., Kobiki, M., Wataze, M., Ishii, T., and Mitsui, S. (see Mitsui, Y.)
Owen, S.J.T., Bhattacharya, P.K., Ku, J.W., Chiao, S.H., and Yeats, R. (see Bhattacharya, P.K.)
Owens, D.H. Asymptotic stability of differential multipass processes 446
Owens, D.H., and Atherton, D.P. (see Atherton, D.P.)

P

Pacey, G.K., and Dalgleish, J.F. Fusion splicing of optical fibres 32
Paige, E.G.S., and Whittle, P. Multistrip coupler performance for surface-skimming bulk waves on lithium tantalate 374
Pain, B.G. Alternative approach to the design of switched-capacitor filters 438
Pain, B.G. Avoiding complex matrix manipulation for switched networks 7
Pain, B.G. Some comments on notch capability of N-path filters 486
Pal, J. Stable reduced-order pade approximants using the Routh-Hurwitz array 225
Palama, G., and Russo, G.V. Minimisation of incompletely specified sequential machines: the 'really' excluded compatibility classes 690
Palm, L., Bruch, H., Ponse, F., and Balk, P. (see Bruch, H.)
Pandel, J. Sequential voltage-inversion principle for switched-capacitor filters 399
Papp, A., and Harms, H. Vibration-induced polarisation modulation of light guided in single-mode optical fibres 76
Paraskevopoulos, P.N., and Varoufakis, S.J. (see Varoufakis, S.J.)
Parker, T.E. 1/f phase noise in quartz s.a.w. devices 296

Parmon, W., and Bertoni, H.L. Ray interpretation of the material signature in the acoustic microscope 684
Parriaux, O., Neuman, V., and Walpita, L.M. (see Neuman, V.)
Parsons, J.D., and Pongsupaht, A. Diversity reception for error-rate reduction in mobile-radio data links 202
Parsons, J.D., and Pongsupaht, A. (see Pongsupaht, A.)
Parthasarathy, R., and John, S. (Mrs) (see John, S. (Mrs))
Patranabis, D., and Paul, A.N. Floating ideal inductor with one d.v.c.c.s. 545
Patranabis, D., and Paul, A.N. Novel capacitor floatation scheme 688
Paul, A.N., and Patranabis, D. (see Patranabis, D.)
Paul, A.N., and Patranabis, D. (see Patranabis, D.)
Pavlović, V.D., and Stojanović, V.S. (see Stojanović, V.S.)
Payne, D.N., Adams, M.J., and Ragdale, C.M. (see Adams, M.J.)
Payne, D.N., Norman, S.R., Adams, M.J., and Smith, A.M. (see Norman, S.R.)
Payne, D.N., Sladen, F.M.E., and Adams, M.J. (see Sladen, F.M.E.)
Peaker, A.R., Brunwin, R.F., Jordan, P., and Hamilton, B. Recombination in gallium phosphide via a deep state associated with nickel 663
Peaker, A.R., Brunwin, R., Hamilton, B., and Jordan, P. (see Brunwin, R.)
Pearson, D.E., and Dennis, T.J. Performance of interframe predictive coders for television signals under various conditions of motion 66
Penttinen, A., and Luukkala, M. (see Luukkala, M.)
Perisic, D. New approach to discrete phase-locked loop based on digital measurement of time intervals 445
Petenzi, M., Gelin, Ph., and Citerne, J. (see Gelin, Ph.)
Petermann, K. Wavelength-dependent transmission at fibre connectors 706
Petrović, G. Power spectrum of the balanced digital signal generated by Markov source 769
Petrovic, V., and Gosling, W. Polar-loop transmitter 286
Petty, M.C., and Roberts, G.G. CdTe/Langmuir-film m.i.s. structures 335
Piazzola, S., and De Marchis, G. Analytical relations between modal power distribution and near-field intensity in graded-index fibres 721
Piazzolla, S., Daino, B., and De Marchis, G. (see Daino, B.)
Picciarelli, V., and Massaro, P.A. (see Massaro, P.A.)
Picciarelli, V., and Massaro, P.A. (see Massaro, P.A.)
Piedade, M.S. Another method for the RC active simulation of double-terminated LC ladder filters 571
Pignard, J., and Debrie, R. (see Debrie, R.)
Piqueras, J., Garrido, J., and Calleja, E. (see Garrido, J.)
Pirani, G., and Mengali, U. (see Mengali, U.)
Plessky, V.P., and Gulyaev, Y.V. (see Gulyaev, Y.V.)
Pollack, M.A., Capasso, F., and Nahory, R.E. (see Capasso, F.)
Pollack, M.A., Gordon, J.P., Nahory, R.E., and Worlock, J.M. (see Gordon, J.P.)
Pollack, M.A., Kaminow, I.P., Nahory, R.E., Stulz, L.W., and DeWinter, J.C. (see Kaminow, I.P.)
Pollack, M.A., Leheny, R.F., and Nahory, R.E. (see Leheny, R.F.)
Pollard, J.M. Remarks on the convolution algorithm of Agarwal and Cooley 593
Pollock, M.A., Nahory, R.E., and DeWinter, J.C. (see Nahory, R.E.)
Pongsupaht, A., and Parsons, J.D. Novel technique for eliminating the ambiguity in p.s.k. signal detection 385
Pongsupaht, A., and Parsons, J.D. (see Parsons, J.D.)
Ponse, F., Bruch, H., Palm, L., and Balk, P. (see Bruch, H.)
Ponse, F., Stahlmann, R., Tsironis, C., and Beneking, H. (see Stahlmann, R.)
Pookaiyaudom, S., Watanachaipratreep, C., and Dejhan, K. Peak-amplitude detector for sinusoidal signals 127
Poon, R.K.L. Capacitance of a microstrip of unequal widths in a homogeneous medium 44
Poon, T.C., and Card, H.C. Incorporation of bromine into Si-SiO_2 interfaces and effects on interface state distributions 756
Popovich, M.V., and Rakovich, B.D. (see Rakovich, B.D.)
Porter, B., and Bradshaw, A. Decentralised transmission zeros of linear multivariable continuous-time systems 230
Prabhu, K.M.M., and Agrawal, J.P. Quantisation effect in data windows 25
Presby, H.M., Kaminow, I.P., Simpson, J.R., and MacChesney, J.B. (see Kaminow, I.P.)
Proebster, W., and Amann, M.-C. (see Amann, M.-C.)
Proebster, W., Grothe, H., and Harth, W. (see Grothe, H.)
Proksch, P. Energy and power of bandlimited fields in lossless nonlinear media 521
Proksch, P. General relations for nonperiodic bandlimited signals in three-dimensional electron flow 328

R

Rabaey, J.M., and Copeland, M.A. (see Copeland, M.A.)
Radhakrishna Rao, K., and Srinivasan, S. (see Srinivasan, S.)
Ragdale, C.M., Adams, M.J., and Payne, D.N. (see Adams, M.J.)
Ragdale, C.M., Gambling, W.A., and Matsumara, H. (see Gambling, W.A.)
Rahal, S., and Chovet, A. Variance noise and temperature fluctuations in semiconductors 271
Rahman, M.M., Sitch, J.E., and Benson, F.A. Transfer impedance of braided coaxial cables under applied longitudinal torsion 455
Rakovich, B.D., and Popovich, M.V. Characteristic function for quasielliptic filters 292
Randazzo, E., Alcuri, L., and Mamola, G. (see Alcuri, L.)
Rao, M.K.N., Haslett, J.W., and Bruton, L.T. Novel g.i.c. suitable for RC active-filter applications 462
Rawson, E.G., and Bailey, M.D. Bitaper star couplers with up to 100 fibre channels 432
Rayner, P.J.W., and Arambepola, B. (see Arambepola, B.)
Rayner, P.J.W., and Arambepolar, B. (see Arambepolar, B.)
Rebourg, J.C., Feldmann, M., Henaff, J., and Lacroix, B. (see Feldmann, M.)
Reddy, N.S., and Reddy, V.U. Combination of complex rectangular transforms and f.n.t. to implement fast convolution 716
Reddy, V.U., and Reddy, N.S. (see Reddy, N.S.)
Reed, I.S., Truong, T.K., and Miller, R.L. Decoding of B.C.H. and R.S. codes with errors and erasures using continued fractions 542
Reed, I.S., Truong, T.K., and Miller, R.L. (see Truong, T.K.)
Rees, H.D., and Mazzone, A.M. (see Mazzone, A.M.)
Rengarajan, S.R., and Lewis, J.E. Surface impedance of elliptical hollow conducting waveguides 637
Renner, D., and Carroll, J.E. Simple system for broad-band single-mode tuning of d.h. GaAlAs lasers 73
Reza, F. Concavity and sensitivity of electrical resistance functions 305
Richards, W.F., Lo, Y.T., and Harrison, D.D. Improved theory for microstrip antennas 42
Ridders, C.J.F. Comment on D.C. solutions of bipolar-transistor circuits 63
Riedling, K., Olcaytug, F., and Fallmann, W. Alloyed planar diodes in indium antimonide 572
Riegl, I., Zwick, U., Auer, W., Haupt, H., and Heitmann, W. (see Zwick, U.)
Rittich, D., and Opielka, D. (see Opielka, D.)
Roberts, G.G., and Petty, M.C. (see Petty, M.C.)
Roberts, J.B.G., Darby, B.J., Bale, R.A., and Eames, R. Fast s.a.w.-based discrete Fourier transformer Errata 262
Robinson, A., and Irven, J. (see Irven, J.)
Robson, P.N., and Choudhury, A.N.M.M. (see Choudhury, A.N.M.M.)
Robson, P.N., Westbrook, L.D., and Majerfeld, A. (see Westbrook, L.D.)
Rocks, M. Measurements performed on l.e.d. 4-level digital optical-fibre system for 68 Mbit/s 676
Röder, H. Quality test of semiconductor memories by jitter measurement 428
Rolland, P.A., Constant, E., Salmer, G., and Fauquembergue, R. Frequency limitation of GaAs transferred-electron devices: influence of operating d.c. and r.f. field values 373
Rooryck, M. Validity of two-path model for calculating quality of digital radio links: determination of model from measurements on analogue links 783
Rossel, P., Graffeuil, J., and Martinot, H. (see Graffeuil, J.)
Rossi, U., and Di Vita, P. (see Di Vita, P.)
Roulet, M.E., Schwob, P., Golecki, I., and Nicolet, M.-A. Electrical properties of silicon-implanted furnace-annealed silicon-on-sapphire devices 527
Rowlands, M.G. Integrated-circuit fabrication flaw detected using the supply-current analysis technique 745
Rozkosny, V., Karpinsky, J., Benes, T., Hlavaty, V., and Sajal, P. (see Karpinsky, J.)
Russo, G.V., and Palama, G. (see Palama, G.)
Rutkowski, D., Wade, P.C., and Drukier, I. (see Wade, P.C.)

S

Sadana, D., Kular, S.S., Sealy, B.J., Badawi, M.H., Stephens, K.G., and Booker, G.R. (see Kular, S.S.)
Saekeang, C., and Chu, P.L. (see Chu, P.L.)
Saifi, M.A., Smithgall, D.H., and Andrejco, M.J. (see Smithgall, D.H.)
Sajal, P., Karpinsky, J., Benes, T., Hlavaty, V., and Rozkosny, V. (see Karpinsky, J.)
Sakai, K., Akiba, S., Matsushima, Y., and Yamamoto, T. (see Akiba, S.)
Sakakibara, Y., Furuya, K., Suematsu, Y., and Itaya, Y. Direct modulation characteristics of GaInAsP/InP d.h. lasers with various stripe widths measured by sharp-pulse method 594
Salama, C.A.T., Lane, W.A., and Dmitrevsky, S. (see Lane, W.A.)
Saleeb, A.A., and Olver, A.D. (see Olver, A.D.)
Salmer, G., Rolland, P.A., Constant, E., and Fauquembergue, R. (see Rolland, P.A.)
Salset, J., Azan, F., and Mouly, J.M. (see Azan, F.)
Sammut, R.A. Analysis of approximations for the mode dispersion in monomode fibres 590
Sammut, R.A., Love, J.D., and Snyder, A.W. (see Love, J.D.)
Sammut, R.A., and Snyder, A.W. (see Snyder, A.W.)
Sammut, R.A., and Snyder, A.W. (see Snyder, A.W.)
Sammut, R.A., and Snyder, A.W. (see Snyder, A.W.)
Samson, J., Dubost, G., and Frin, R. (see Dubost, G.)
Sánchez-Sinencio, E. Comment on Multifunction active R filter with two operational amplifiers 262
Sánchez-Sinencio, E., and Báez-López, D. Comment on Inductance simulation and filter design using a single-pole amplifier approximation 465
Sánchez-Sinencio, E., and Gómez-Oserio, J.L. Switched-capacitor simulation of grounded inductors using operational-amplifier pole 169
Sanchez-Sinencio, E., Arreola, J.I., Tsividis, Y.P., and Allen, P.E. (see Arreola, J.I.)
Saruwatari, M., Suzuki, N., Iwahara, Y., and Nawata, K. (see Suzuki, N.)
Sarwate, D.V. Comment on Simple method for computing elements of order $2^k n$, where $n/2^{p-1}-1$ and $2 \leq k \leq p+1$, in $GF[(2^{p-1}-1)^2]$ 69
Sasaki, A., and Ishibashi, T. Liquid-crystal light deflector 293
Sasaki, H., and Mikoshiba, N. Directional coupling of magnetostatic surface waves in layered magnetic thin films 172
Sasaki, J., Suzuki, S., and Shinmyo, S. (see Suzuki, S.)
Sato, K-I., and Asatani, K. Analogue baseband t.v. transmission experiments using semiconductor laser diodes 794
Savage, E.B. Fast computation of s.a.w. filter responses including diffraction 538
Saxena, R.R., and Moon, R.L. Low-bandgap (1.15 eV) InGaP/InGaAs solar cell 826
Scalas, M.R., Filicori, F., and Naldi, C. (see Filicori, F.)
Schaumann, R., Brand, J.R., and Laker, K.R. Comment on practical aspects of filters using amplifier poles 493
Schizas, C., and Evans, F.J. (see Evans, F.J.)
Schlendermann, A., Chaloupka, H., and Galka, M. (see Chaloupka, H.)
Schlosser, E., Marschall, P., and Wölk, C. (see Marschall, P.)
Schneider, M.V., and Berger, H. Microelectrodes for contacting semiconductor devices 450
Schroefel, J., Čtyroký, J., Čada, M., Lyndin, N.M., and Sychugov, V.A. (see Čtyroký, J.)
Schünemann, K., Kpodzo, E., and Begemann, G. (see Kpodzo, E.)
Schwarz, T., and Malah, D. Hybrid realisation of an adaptive filter for real-time noise-cancelling applications 671
Schwob, P., Roulet, M.E., Golecki, I., and Nicolet, M.-A. (see Roulet, M.E.)
Scott, R.I.H., and Underhill, M.J. (see Underhill, M.J.)
Sealy, B.J., Badawi, M.H., Akintunde, J.A., and Stephens, K.G. (see Badawi, M.H.)
Sealy, B.J., Badawi, M.H., and Stephens, K.G. (see Badawi, M.H.)

Sealy, B.J., and Butcher, D.N. (see Butcher, D.N.)
Sealy, B.J., and Emerson, N.G. (see Emerson, N.G.)
Sealy, B.J., Kular, S.S., Badawi, M.H., Stephens, K.G., Sadana, D., and Booker, G.R. (see Kular, S.S.)
Seck, J.P., and Courvoisier, M. (see Courvoisier, M.)
Sedra, A.S., and Martin, K. (see Martin, K.)
Seevinck, E. Optimal radix for monolithic memories 736
Sei, H., Miyamoto, Y., Tanikawa, K., and Kato, S. (see Miyamoto, Y.)
Seikai, S., Kato, Y., Kitayama, K-I., and Uchida, N. (see Kato, Y.)
Selway, P.R., Thrush, E.J., and Henshall, G.D. (see Thrush, E.J.)
Senani, R. New canonic single-resistance-controlled sinusoidal oscillator using a single current conveyor 568
Senani, R. Novel active RC circuit for floating-inductor simulation 679
Severi, M., Calzolari, P.U., and Masetti, G. (see Calzolari, P.U.)
Shafai, L., and Shoamanesh, A. (see Shoamanesh, A.)
Shahani, D.T., and Simons, R.N. (see Simons, R.N.)
Shamash, Y. Time moments and Markov parameters of composite systems 131
Sharpe, C.D., Lilley, P., Elliott, C.R., and Ambridge, T. Electrochemical carrier concentration profiling in silicon 622
Shelswell, P. Transmitter drive using digital techniques to give frequency modulation 68
Sherman, A.B., Dobrovolsky, A.A., Lemanov, V.V., and Smolensky, G.A. (see Dobrovolsky, A.A.)
Shibata, N., Kawachi, M., Sudo, S., and Edahiro, T. Low-loss high-numerical-aperture optical fibre fabricated by v.a.d. method 680
Shida, S., Enomoto, T., Ishihara, T., and Yasumoto, M. (see Enomoto, T.)
Shigematsu, T., Yoshikawa, A., Tamama, T., Mizushima, Y., and Kudo, K. (see Yoshikawa, A.)
Shimada, S., Matsumoto, T., Ito, T., Matsushita, S., Washio, K., and Minemura, K. 100 km optical-fibre transmission system at 1.32 μm using high-power c.w. Nd-y.a.g. laser 484
Shimizu, N., Tsuchiya, H., and Izawa, T. Low-loss single-mode fibre connectors 28
Shinmyo, S., Suzuki, S., and Sasaki, J. (see Suzuki, S.)
Shoamanesh, A., and Shafai, L. Effect of reflector and exciter size on the radiation of circular-loop Yagi arrays 103
Shrubb, S.J.W., Vokes, J.C., Hughes, B.T., Wight, D.R., and Dawsey, J.R. (see Vokes, J.C.)
Siddiqui, M.A., and Ahmed, M.T. (see Ahmed, M.T.)
Simons, R.N., and Shahani, D.T. Long backfire antenna with insular image guide feed for dual frequency operation 78
Simpson, J.R., Kaminow, I.P., Presby, H.M., and MacChesney, J.B. (see Kaminow, I.P.)
Simpson, S.H.W., and Chambers, B. Optimisation of backscatter using the concept of complex characteristic polarisations 547
Singhal, K., Viswanathan, T.R., Faruque, S.M., and Vlach, J. (see Viswanathan, T.R.)
Singhal, K., Viswanathan, T.R., and Vlach, J. (see Viswanathan, T.R.)
Sitch, J.E., Rahman, M.M., and Benson, F.A. (see Rahman, M.M.)
Skalsky, M., and Miler, M. (see Miler, M.)
Sladen, F.M.E., Payne, D.N., and Adams, M.J. Definitive profile-dispersion data for germania-doped silica fibres over an extended wavelength range 469
Sleger, K.J., Anderson, Jun., W.T., Davey, J.E., Christou, A., Bark, M.L., and Dietrich, H.B. (see Anderson, Jun., W.T.)
Smith, A.M., Norman, S.R., Payne, D.N., and Adams, M.J. (see Norman, S.R.)
Smith, B.V., Koymen, H., and Gazey, B.K. (see Koymen, H.)
Smith, D.W., and Eve, M. (see Eve, M.)
Smith, J.G. Compensation degradation mechanism for high-efficiency GaAs Impatt diodes 74
Smithgall, D.H., Saifi, M.A., and Andrejco, M.J. Optical transmission loss of germanium borosilicate fibres as a function of drawing conditions 56
Smolensky, G.A., Dobrovolsky, A.A., Lemanov, V.V., and Sherman, A.B. (see Dobrovolsky, A.A.)
Snijder, J., and Ligtenberg, H.C.G. (see Ligtenberg, H.C.G.)
Snyder, A.W., and Sammut, R.A. Dispersion in graded single-mode fibres 269
Snyder, A.W., and Sammut, R.A. Radiation from optical waveguides: leaky-mode interpretation 58
Snyder, A.W., and Sammut, R.A. Radiation modes of optical waveguides 4
Snyder, A.W., Love, J.D., and Sammut, R.A. (see Love, J.D.)
Soliman, A.M., Nomair, M., and Bahnas, Y.Z. (see Nomair, M.)
Someda, C.G., Cancellieri, G., Mezzetti, M., and Zoboli, M. (see Cancellieri, G.)
Sone, J., and Takayama, Y. Ku- and K-band internally matched high-power GaAs f.e.t. amplifiers 562
Sone, J., Takayama, Y., and Aono, Y. 14-GHz band 1 watt GaAs f.e.t. amplifier 212
Sorrentino, R., D'Inzeo, G., and Giannini, F. (see D'Inzeo, G.)
South, C.R. Total dispersion in step-index monomode fibres 394
South, C.R., Hoppitt, C.E., and Lewis, A.V. Adaptive filters to improve loudspeaker telephone 673
Spear, W.E., Le Comber, P.G., and Ghaith, A. (see Le Comber, P.G.)
Speight, J.D., McMahon, R.A., Ahmed, H., and Dobson, R.M. (see McMahon, R.A.)
Spirito, P., Caruso, A., and Vitale, G. (see Caruso, A.)
Srinivasan, S., and Radhakrishna Rao, K. Comment on Simulation of inductors and capacitors using operational amplifier compensation pole: a caution 472
Stahlmann, R., Tsironis, C., Ponse, F., and Beneking, H. Dual-gate m.e.s.f.e.t. self-oscillating X-band mixers 524
Stall, R., Wood, C.E.C., Board, K., and Eastman, L.F. Ultra low resistance ohmic contacts to n-GaAs 800
Steele, R., and Gharavi, H. (see Gharavi, H.)
Stephens, K.G., Badawi, M.H., Akintunde, J.A., and Sealy, B.J. (see Badawi, M.H.)
Stephens, K.G., Badawi, M.H., and Sealy, B.J. (see Badawi, M.H.)
Stephens, K.G., Kular, S.S., Sealy, B.J., Badawi, M.H., Sadana, D., and Booker, G.R. (see Kular, S.S.)
Stephenson, F.W., and Dunning-Davies, J. Simplified design procedures for a third-order system using current conveyors 215
Sterling, M.J.H., and Morris, A.S. (see Morris, A.S.)
Stockton, J.R., and Knight, R.B.D. Some proposals for improved forms of precision fast digital-analogue and analogue-digital converters Errata 166
Stojadinović, N.D. Effects of emitter edge dislocations on the low-frequency noise of silicon planar n-p-n transistors 340
Stojanović, V.S., and Pavlović, V.D. Transitional Murromaf-Murroer filters 356
Straus, J., Few, I.S., and Conradi, J. Measurement of frequency dependence of Rayleigh backscattering in bidirectional optical systems 306
Strnad, A.R., Tomlinson, W.J., Wagner, R.E., and Dunn, F.A. (see Tomlinson, W.J.)
Stromsmoe, K.A., and Filanovsky, I.M. (see Filanovsky, I.M.)
Stubkjaer, K. Distortion of light signals transmitted via multimode graded-index fibres 797
Stubkjr, K.E. Nonlinearity of d.h. GaAlAs lasers 61
Stuchly, M.A., Gajda, G., and Stuchly, S.S. (see Gajda, G.)
Stuchly, S.S., and Bahl, I.J. (see Bahl, I.J.)
Stuchly, S.S., Gajda, G., and Stuchly, M.A. (see Gajda, G.)
Stulz, L.W., Kaminow, I.P., Nahory, R.E., Pollack, M.A., and DeWinter, J.C. (see Kaminow, I.P.)
Sudo, S., Edahiro, T., Kawachi, M., Jinguji, K., and Inagaki, N. (see Edahiro, T.)
Sudo, S., Edahiro, T., Kawachi, M., and Takata, H. (see Edahiro, T.)
Sudo, S., Shibata, N., Kawachi, M., and Edahiro, T. (see Shibata, N.)
Suematsu, Y., Itaya, Y., and Katayama, S. (see Itaya, Y.)
Suematsu, Y., Kishino, K., and Itaya, Y. (see Kishino, K.)
Suematsu, Y., Sakakibara, Y., Furuya, K., and Itaya, Y. (see Sakakibara, Y.)
Sugawara, Y., Kawase, M., Yamashita, K., Nishimura, M., and Yamanishi, T. (see Kawase, M.)
Sugiyama, K., Tsubaki, K., and Kubota, E. (see Tsubaki, K.)
Sugiyama, K., Yamada, Jun-ichi., Machida, S., Mukai, T., and Kano, H. (see Yamada, Jun-ichi.)
Sun, C., Chang, K., and Ebert, R. (see Chang, K.)
Susa, N., Kanbe, H., Nishioka, T., and Ohmachi, Y. High-gain GaAs avalanche photodiodes with proton-implanted guard ring 535
Susa, N., Yamauchi, Y., and Kanbe, H. Planar photodiodes made from vapour-phase epitaxial $In_xGa_{1-x}As$ 238
Suto, K-I., Nakagawa, K., and Hakamada, Y. (see Nakagawa, K.)
Suzuki, M., Washisu, S., and Fukai, I. (see Washisu, S.)
Suzuki, N., Iwahara, Y., Saruwatari, M., and Nawata, K. Ceramic capillary connector for 1.3 μm single-mode fibres 809
Suzuki, N., Fujii, Y., and Minowa, J. (see Fujii, Y.)
Suzuki, N., Nawata, K., and Iwahara, Y. (see Nawata, K.)
Suzuki, S., Shinmyo, S., and Sasaki, J. Low-cost analogue voltage-voltage convertors with arbitrary transfer characteristics 170
Suzuki, T., Yoneyama, T., and Nishida, S. (see Yoneyama, T.)
Sychugov, V.A., Čtyroký, J., Čada, M., Lyndin, N.M., and Schroefel, J. (see Čtyroký, J.)

T

Tabuchi, T., Kinoshita, Y., Hikita, M., and Kojima, H. (see Kinoshita, Y.)
Tachikura, M., and Hatakeyama, I. Multimode fibre connectors fabricated with a self-aligning jig 34
Taguchi, K., Matsumoto, Y., and Nishida, K. InP-InGaAsP planar avalanche photodiodes with self-guard-ring effect 453
Takahei, K., Kawaguchi, H., Toyoshima, Y., Nagai, H., and Iwane, G. (see Kawaguchi, H.)
Takata, H., Edahiro, T., Kawachi, M., and Sudo, S. (see Edahiro, T.)
Takata, H., Ohmori, Y., Okazaki, H., and Hatakeyama, I. (see Ohmori, Y.)
Takata, H., Yamada, Jun-Ichi., Machida, S., and Kimura, T. (see Yamada, Jun-Ichi.)
Takayama, Y., Ogawa, T., and Aono, Y. 11 GHz and 12 GHz multiwatt internal matching for power GaAs f.e.t.s. 326
Takayama, Y., Furutsuka, T., Higashisaka, A., Aono, Y., and Hasegawa, F. (see Furutsuka, T.)
Takayama, Y., and Sone, J. (see Sone, J.)
Takayama, Y., Sone, J., and Aono, Y. (see Sone, J.)
Tamama, T., Yoshikawa, A., Mizushima, Y., Kudo, K., and Shigematsu, T. (see Yoshikawa, A.)
Tang, T.G., Yeow, Y.T., and Mavor, J. Coefficient correction in programmable c.c.d. recursive filters 630
Tanifuji, T., Horiguchi, T., and Tokuda, M. Baseband-frequency-response measurement of graded-index fibre using step-index fibre as an exciter 203
Tanikawa, K., Ito, Y., Yamamoto, T., Miura, S., Miyamoto, Y., and Kato, S. C.C.D. transversal filter with a three-level polysilicon structure 311
Tanikawa, K., Miyamoto, Y., Sei, H., and Kato, S. (see Miyamoto, Y.)
Tanski, W.J. S.A.W. resonators at 1.29 GHz with Q values approaching the material limit 339
Tanski, W.J., and Van de Vaart, H. Technique for triple-transit suppression in surface-acoustic-wave delay lines 312
Tasch, A.F. Jun., Holloway, T.C., Lee, K.F., and Gibbons, J.F. Silicon-on-insulator m.o.s.f.e.t.s. fabricated on laser-annealed polysilicon on SiO_2 435
Tatekura, K., Itoh, K., and Matsumoto, T. Quantitative estimations of mode-coupling mechanisms in an optical fibre 9
Temes, G.C., and Gregorian, R. Compensation for parasitic capacitances in switched-capacitor filters 377
Temes, G.C., and Jahanbegloo, M. Switched-capacitor circuits bilinearly equivalent to floating inductor or f.d.n.r. 87
Temes, G.C., and Gregorian, R. (see Gregorian, R.)
Terui, H., and Kobayashi, M. Fabrication of channel optical waveguide using CO_2 laser 79
Terunuma, Y., Miya, T., Hosaka, T., and Miyashita, T. (see Miya, T.)
Thajchayapong, P., and Cheevasuvit, F. Sine-cosine squared-magnitude function for maximally flat digital bandpass filters with adjustable skirt selectivities 345
Thanh, L.C. Similitude between ionic wind, discharge pattern and corona current 57
Thielen, H. Omnidirectional s.h.f. antenna consisting of horn radiators and plane reflectors 639
Thim, H.W., Deutsch, G., Lindner, G., and Lübke, K. (see Deutsch, G.)
Thim, H.W., Lechner, A., Kneidinger, M., Kuch, R., and Wernisch, J. (see Lechner, A.)
Thirlwell, J., and Bell, R.R. (see Bell, R.R.)
Thompson, G.H.B., Lovelace, D.F., and Turley, S.E.H. Twin-transverse-junction stripe laser with linear light/current characteristic and low threshold 133
Thompson, G.H.B., Turley, S.E.H., and Lovelace, D.F. (see Turley, S.E.H.)
Thorpe, P.L.M., and Downing, O.J. (see Downing, O.J.)

Thrush, E.J., Selway, P.R., and Henshall, G.D. Metalorganic c.v.d. growth of GaAs-GaAlAs double heterojunction lasers having low interfacial recombination and low threshold current 156
Thrush, E.J., and Whiteaway, J.E.A. Preliminary c.w. reliability measurements on GaAs-(GaAl)As stripe lasers grown by metal-organic c.v.d. 666
Titchmarsh, J.G. Signal-level dependence in the recovery rate of irradiated plastic-clad silica fibre 111
Tokuda, M., Tanifuji, T., and Horiguchi, T. (see Tanifuji, T.)
Tomlinson, W.J., Wagner, R.E., Strnad, A.R., and Dunn, F.A. Multiposition optical-fibre switch 192
Torii, Y., Iwamura, H., Iwasaki, H., Kubodera, K., and Noda, J. (see Iwamura, H.)
Toyoshima, Y., Kawaguchi, H., Takahei, K., Nagai, H., and Iwane, G. (see Kawaguchi, H.)
Trivedi, M., and Lever, K.V. Quantising error in a Dolph-Chebyshev data-window multiplier circuit 136
Truong, T.K., Miller, R.L., and Reed, I.S. Fast technique for computing syndromes of B.C.H. and Reed-Solomon codes 720
Truong, T.K., Reed, I.S., and Miller, R.L. (see Reed, I.S.)
Tsironis, C., Stahlmann, R., Ponse, F., and Beneking, H. (see Stahlmann, R.)
Tsividis, Y.P., Arreola, J.I., Sanchez-Sinencio, E., and Allen, P.E. (see Arreola, J.I.)
Tsoi, A.C. Inverse Routh-Hurwitz array solution to the inverse stability problem 575
Tsubaki, K., Kubota, E., and Sugiyama, K. Electron traps in n-InP grown by the synthesis solute-diffusion method 513
Tsuchiya, H., and Imoto, N. Dispersion-free single-mode fibre in 1.5 μm wavelength region 476
Tsuchiya, H., Machida, S., Yamada, J., Mukai, T., Horikoshi, Y., and Miya, T. (see Machida, S.)
Tsuchiya, H., Shimizu, N., and Izawa, T. (see Shimizu, N.)
Tuck, B., and Badawi, M.H. Surface stability of GaAs during tin diffusion 604
Turley, S.E.H., Thompson, G.H.B., and Lovelace, D.F. Effect of injection current on the dielectric constant of an inbuilt waveguide in twin-transverse-junction stripe lasers 256
Turley, S.E.H., Thompson, G.H.B., and Lovelace, D.F. (see Thompson, G.H.B.)
Turner, J.A., and Joshi, J.S. (see Joshi, J.S.)

U

Uchida, N., and Kashima, N. (see Kashima, N.)
Uchida, N., Kato, Y., Kitayama, K-I., and Seikai, S. (see Kato, Y.)
Underhill, M.J., and Jordan, P.A. Split-loop method for wide-range frequency synthesiser with good dynamic performance 391
Underhill, M.J., and Lewis, P.A. Quiet tuning of antennas 37
Underhill, M.J., and Scott, R.I.H. Wideband frequency modulation of frequency synthesisers 393
Upton, S.A.J., Evans, B.G., and Holt, A.R. Effects of drop size and temperature on forward and backward scattering of microwaves by raindrops 760

V

Van de Vaart, H., and Tanski, W.J. (see Tanski, W.J.)
Varga, A. Numerically reliable algorithm to test controllability 452
Varoufakis, S.J., and Paraskevopoulos, P.N. Mixed time/frequency domain approach to model reduction 789
Veen, R.J. Piezojunction effect of a planar n-p-n transistor for transducer aims 333
Velmre, E., and Freidin, B. Numerical analysis of forward-biased diode structures based on direct-gap semiconductors 383
Venkatesan, T.N.C., and Ogawa, K. Miniaturised, hybrid, 500 Mb/s optical receiver package for data-link applications 171
Vichr, M., Berenz, J.J., and Fank, F.B. (see Berenz, J.J.)
Vidimari, F. Improved ohmic properties of Au-Ge contacts to thin n-GaAs layers alloyed with an SiO_2 overlayer 674
Virr, L.E., Jack, M.A., and Milne, A.D. (see Jack, M.A.)
Viswanathan, T.R., Faruque, S.M., Singhal, K., and Vlach, J. M.O.S. switched-capacitor amplifiers 634
Viswanathan, T.R., Vlach, J., and Singhal, K. Switched-capacitor transconductance elements and gyrators 318
Vitale, G., Caruso, A., and Spirito, P. (see Caruso, A.)
Vlach, J., Viswanathan, T.R., Faruque, S.M., and Singhal, K. (see Viswanathan, T.R.)
Vlach, J., Viswanathan, T.R., and Singhal, K. (see Viswanathan, T.R.)
Vokes, J.C., Hughes, B.T., Wight, D.R., Dawsey, J.R., and Shrubb, S.J.W. Novel microwave GaAs field-effect transistors 627
Vokurka, V.J. Elliptical corrugated horn for broadcasting-satellite antennas 652
Voles, R. Optimal estimation of a common phase difference between pairs of fluctuating signals in noise 145
Vrba, J. Dynamic permittivity of microstrip ring resonator 504

W

Wada, T., and Frey, J. (see Frey, J.)
Wade, P.C., Rutkowski, D., and Drukier, I. Pulsed GaAs f.e.t. operation for high peak output powers 591
Wagner, R.E., Tomlinson, W.J., Strnad, A.R., and Dunn, F.A. (see Tomlinson, W.J.)
Wah, P.K.S. Simple adaptive vectors encoding for two-dimensional redundancy reduction (Saver) 221
Wait, J.R. Exact surface impedance for a cylindrical conductor 659
Wakefield, J., Armstrong, B.M., and Moore, R.A. (see Armstrong, B.M.)
Wallace, J.L., Calviello, J.A., and Bie, P.R. (see Calviello, J.A.)
Walpita, L.M., Neuman, V., and Parriaux, O. (see Neuman, V.)
Walton, A., Arlett, P.L., Elkins, K., and O'Neill, K. (see Arlett, P.L.)
Washio, K., Shimada, S., Matsumoto, T., Ito, T., Matsushita, S., and Minemura, K. (see Shimada, S.)
Washisu, S., Fukai, I., and Suzuki, M. Extension of finite-element method to unbounded field problems 772
Watanabe, K., Enomoto, T., and Yasumoto, M. (see Enomoto, T.)
Watanachaiprateep, C., Pookaiyaudom, S., and Dejhan, K. (see Pookaiyaudom, S.)
Wataze, M., Mitsui, Y., Kobiki, M., Otsubo, M., Ishii, T., and Mitsui, S. (see Mitsui, Y.)
Weidal, E., and Gruchmann, D. Tee-coupler for single-mode fibres 737
Weierholt, A. Modal dispersion of optical fibres with a composite α-profile graded-index core 733
Wernisch, J., Lechner, A., Kneidinger, M., Thim, H.W., and Kuch, R. (see Lechner, A.)
Wesolowski, K. Roll-off shaping filter design for improving adaptive equalisation 338
Wessels, B.W. Gettering of epitaxial gallium phosphide using phosphosilicate glass 748
Westbrook, L.D., Robson, P.N., and Majerfeld, A. Strain-induced optical waveguiding in GaAs epitaxial layers at 1.15 μm 99
Whight, K.R. Synthesis and analysis of d.l.t.s. spectra from m.o.s. surface states 744
Whitbread, T., and Chu, P.L. (see Chu, P.L.)
White, J.C., Hill, J.R., McCaughan, D.V., and Keen, J.M. (see Hill, J.R.)
White, J.C., Oliver, C.J., James, A.H., McCaughan, D.V., and Hill, J.R. (see Oliver, C.J.)
White, K.I., and Nelson, B.P. Zero total dispersion in step-index monomode fibres at 1.30 and 1.55 μm 396
Whiteaway, J.E.A., and Thrush, E.J. (see Thrush, E.J.)
Whittle, P., and Paige, E.G.S. (see Paige, E.G.S.)
Wight, D.R., Griffiths, R.J.M., and Blenkinsop, I.D. (see Griffiths, R.J.M.)
Wight, D.R., Vokes, J.C., Hughes, B.T., Dawsey, J.R., and Shrubb, S.J.W. (see Vokes, J.C.)
Wilkinson, C.D.W., and Yi Yan, A. (see Yi Yan, A.)
Williamson, S.E., Matley, W., and Bywater, R.E.H. Comment on Linear-phase digital anti-aliasing filter 793
Williamson, S.E., Matley, W., and Bywater, R.E.H. Linear-phase digital anti-aliasing filter 539
Wilson, I.H., and Belson, J. (see Belson, J.)
Wilson, I.H., and James, S. (see James, S.)
Wilson, M.G.F., Wright, S., and De Oliveira, A.D. (see Wright, S.)
Wisseman, W.R., Wu, Y.S., and Yuan, H.T. (see Wu, Y.S.)
Wölk, C., Marschall, P., and Schlosser, E. (see Marschall, P.)
Wood, C., Hall, P.S., and Garrett, C. (see Hall, P.S.)
Wood, C.E.C., Stall, R., Board, K., and Eastman, L.F. (see Stall, R.)
Woodard, D.W., Jervis, T.R., and Eastman, L.F. (see Jervis, T.R.)
Woods, D. Explicit solution of calibration equations for a dual 6-port network analyser 718
Worlock, J.M., Gordon, J.P., Nahory, R.E., and Pollack, M.A. (see Gordon, J.P.)
Worm, S.C.J. Compact dual-hybrid-mode feeds with low crosspolar radiation 740
Wright, S., De Oliveira, A.D., and Wilson, M.G.F. Optical waveguide polariser with synchronous absorption 510
Wrixon, G.T., Keen, N.J., and Kelly, W.M. (see Keen, N.J.)
Wu, Y.S., Yuan, H.T., and Wisseman, W.R. High-gain 9.25 GHz silicon bipolar transistor power amplifier 86

Y

Yamada, J., Machida, S., Mukai, T., Horikoshi, Y., Tsuchiya, H., and Miya, T. (see Machida, S.)
Yamada, Jun-Ichi., Machida, S., Kimura, T., and Takata, H. Dispersion-free single-mode fibre transmission experiments up to 1.6 Gbit/s 278
Yamada, Jun-ichi., Machida, S., Mukai, T., Kano, H., and Sugiyama, K. Modulation characteristics of 1.3 μm buried-stripe InGaAsP laser up to 2 Gbit/s data rates 596
Yamamoto, T., Akiba, S., Sakai, K., and Matsushima, Y. (see Akiba, S.)
Yamamoto, T., Tanikawa, K., Ito, Y., Miura, S., Miyamoto, Y., and Kato, S. (see Tanikawa, K.)
Yamanishi, T., Kawase, M., Yamashita, K., Nishimura, M., and Sugawara, Y. (see Kawase, M.)
Yamashita, K., Kawase, M., Nishimura, M., Yamanishi, T., and Sugawara, Y. (see Kawase, M.)
Yamauchi, Y., Susa, N., and Kanbe, H. (see Susa, N.)
Yasumoto, M., Enomoto, T., Ishihara, T., and Shida, S. (see Enomoto, T.)
Yasumoto, M., Enomoto, T., and Watanabe, K. (see Enomoto, T.)
Yates, K.W., and Holgate, D.J. Code modulation of m-sequences 836
Yavuz, D. Comment on Analytic expression for the frequency response and bandwidth of a spherical random array 585
Yavuz, D. Frequency response and bandwidth of a spherical random array 314
Yeats, R., Bhattacharya, P.K., Ku, J.W., Owen, S.J.T., and Chiao, S.H. (see Bhattacharya, P.K.)
Yen, K.H., Lau, K.F., and Kagiwada, R.S. Energy-trapped shallow bulk acoustic waves 206
Yeo, T.S., Kooi, P.S., and Leong, M.S. (see Kooi, P.S.)
Yeow, Y.T., Tang, T.G., and Mavor, J. (see Tang, T.G.)
Yi Yan, A., and Wilkinson, C.D.W. Optical frequency-selective filters in ion-exchanged waveguides 240
Yokoyama, H., Ito, H., Murata, S., and Inaba, H. (see Ito, H.)
Yoneyama, T., Suzuki, T., and Nishida, S. Electromagnetic power absorption in cylindrical tissue models excited by a loop antenna 125
Yong-Ching, L., and Constantinides, A.G. New integer programming scheme for nonrecursive digital filter design 812
Yoshikawa, A., Tamama, T., Mizushima, Y., Kudo, K., and Shigematsu, T. Properties of Se-Ge inorganic photoresist as an ion-implantation mask 499
Young, P. Self-adaptive Kalman filter 358
Young, P., and Jakeman, A. (see Jakeman, A.)
Yuan, H.T., Wu, Y.S., and Wisseman, W.R. (see Wu, Y.S.)

Z

Zakarevicius, R.A. Pulse-widening measurement 119
Zeitz, M. Rapidly converging observers involve high-order differentiations 708
Zimmer, G. Laser annealing of m.o.s.-transistor channel implantations 184
Zivaljevich, C.M., and Djurich, B.M. (see Djurich, B.M.)
Zoboli, M., Cancellieri, G., Mezzetti, M., and Someda, C.G. (see Cancellieri, G.)
Zwick, U., Auer, W., Riegl, I., Haupt, H., and Heitmann, W. Low-loss fibres for wavelengths beyond 1 μm 159

Subject index

100 km optical-fibre transmission system at 1.32 μm using high-power c.w. Nd-y.a.g. laser. S.Shimada, T.Matsumoto, T.Ito, S.Matsushita, K.Washio and K.Minemura 484

11 GHz and 12 GHz multiwatt internal matching for power GaAs f.e.t.s.. Y.Takayama, T.Ogawa and Y.Aono 326
14-GHz band 1 watt GaAs f.e.t. amplifier. J.Sone, Y.Takayama and Y.Aono 212

1.5 m optical transmission experiments using very low-loss single-mode fibres. S.Machida, J.Yamada, T.Mukai, Y.Horikoshi, H.Tsuchiya and T.Miya 219

1/f phase noise in quartz s.a.w. devices. T.E.Parker 296
2-f.s.k. traffic detection, quantitative analysis of. B.Forssell 386

800 Mb/s fibre transmission test using low-loss and low-dispersion single-mode cable. K.Nakagawa, Y.Hakamada and K-I.Suto 747
800 MHz v.c.o. for land mobile radio synthesisers. M.Makimoto, K.Nakabe and S.Nishiki 460

80 GHz silicon diamond-heatsink impatt diodes. M.Ino, T.Makimura, T.Ishibashi and M.Ohmori 2

A

A.D. convertor using digital discriminator: an experimental result. A.Akademir and C.S.Aitchison 379
Absorption, electromagnetic power, in cylindrical tissue models excited by a loop antenna. T.Yoneyama, T.Suzuki and S.Nishida 125
Accurate translinear sinusoidal frequency doubler. A.Nedungadi 228
Acoustic microscope, modulation transfer function for the. A.Atalar 321
Acoustic microscope, ray interpretation of the material signature in the. W.Parmon and H.L.Bertoni 684
Acoustic scanning, two-dimensional, of optical images. H.Gautier, P.Ledu and C.Maerfeld 186
Acoustic waves, energy-trapped shallow bulk. K.H.Yen, K.F.Lau and R.S.Kagiwada 206
Active C realisation for the general biquadratic voltage transfer functions. F.Anday 725
Errata 838
Active-filter applications, RC, novel g.i.c. suitable for. M.K.N.Rao, J.W.Haslett and L.T.Bruton 462
Active filters, certain RC, Q-sensitivity of, to gain-bandwidth product. P.V.Anandamohan 95
Active filters, economical, transfer functions with equiripple passband and very low Q-factor for. R.Marquardt 618
Active networks, inverse, noise relations of, and complementary networks. M.Nomair, Y.Z.Bahnas and A.M.Soliman 18
Active R filter, multifunction, with two operational amplifiers, comment on. R.Nandi 261
Active R filter, multifunction, with two operational amplifiers, comment on. E.Sánchez-Sinencio 262
Active R network:, voltage transfer function realisation using, flow-graph technique. S.Osowski 416
Active RC circuit, novel, for floating-inductor simulation. R.Senani 679
Active RC filters, more, using the d.v.c.c.s./d.v.c.v.s.. I.M.Filanovsky and K.A.Stromsmoe 466
Active simulation of inductors using current conveyor, comment on. A.Nedungadi 112
Adaptive cancellation of fixed-pattern noise in c.c.d. serial-parallel-serial memory. R.C.Geddes, C.F.N.Cowan, J.Mavor and J.F.Dickson 505
Adaptive filter, hybrid realisation of an, for real-time noise-cancelling applications. T.Schwarz and D.Malah 671
Adaptive filters to improve loudspeaker telephone. C.R.South, C.E.Hoppitt and A.V.Lewis 673
Adaptive lattice filters, convergence of. T.S.Durrani and N.L.M.Murukutla 833
Adaptive lattices, recursive algorithm for. T.S.Durrani and N.L.M.Murukutla 831
Adaptive observer for systems with pure time delay. Z.Iwai and Y.Kawaski 329
AlGaAs double-heterojunction devices, short-wavelength, internal stress and degradation in. I.Ladany, T.R.Furman and D.P.Marinelli 342
Air-pollution monitoring, optical-fibre network system for, over a wide area by optical absorption method. H.Inaba, T.Kobayasi, M.Hirama and M.Hamza 749
Alloyed planar diodes in indium antimonide. K.Riedling, F.Olcaytug and W.Fallmann 572
Alternative approach to the design of switched-capacitor filters. B.G.Pain 438
Alternative approach to the design of switched-capacitor filters, comment on. J.J.Hill 650
Alternative Kalman controllability criterion for nonderogatory systems. T.T.Ha and J.A.Gibson 451
Alternative multiplication configuration in microprocessor-based digital filters. P.J.Allen and A.G.J.Holt 481
Alternative realisations of switched-capacitor floating inductors. U.W.Brugger and B.J.Hosticka 698
Alumina substrates, spread in effective permittivity of. L.Accatino and A.Angelucci 64
Amorphous-silicon field-effect device and possible application. P.G.Le Comber, W.E.Spear and A.Ghaith 179
Amplification of magnetoelastic Love waves by interaction with carrier waves in a layered composite. Y.Ikuzawa, N.S.Chang and Y.Matsuo 17
Amplifier approximation, single-pole, inductance simulation and filter design using a, comment on. E.Sánchez-Sinencio and D.Báez-López 465
Amplifier, dynamic, for m.o.s. technology. M.A.Copeland and J.M.Rabaey 301
Amplifier, m.e.s.f.e.t., gain expansion and intermodulation in a. C.Blanco 31
Amplifier, novel dynamic c.m.o.s., for switched-capacitor integrators. B.J.Hosticka 532
Amplifier, reflection-mode, utilising GaAs active-medium-propagation devices. P.L.Fleming and H.E.Carlson 787
Amplifier, two-stage, utilising GaAs active-medium-propagation devices. P.L.Fleming and H.E.Carlson 406
Amplifiers, dynamic, in c.m.o.s. technology. B.J.Hosticka 819
Amplifiers, Ku- and K-band internally matched high-power GaAs f.e.t.. J.Sone and Y.Takayama 562
Amplifiers, m.o.s. switched-capacitor. T.R.Viswanathan, S.M.Faruque, K.Singhal and J.Vlach 634
Amplifiers, microwave m.e.s.f.e.t., improvement of intermodulation distortion in, using gate-bias compensation. R.K.Gupta, P.A.Goud and C.G.Englefield 741
Amplifiers, operational, resistive hybrid matrix realisation using. S.Osowski 426
Analogue baseband t.v. transmission experiments using semiconductor laser diodes. K-I.Sato and K.Asatani 794
Analogue-digital converters, some proposals for improved forms of precision fast digital-analogue and. J.R.Stockton and R.B.D.Knight Errata 166
Analogue links, determination of model from measurements on, validity of two-path model for calculating quality of digital radio links:. M.Rooryck 783
Analogue optical transmission of 26 t.v. channels. C.Baack, G.Elze, G.Grosskopf, G.Kraus, F.Krick and L.Küller 300
Errata 444
Analysis and measurement of modal noise in an optical fibre. B.Daino, G.De Marchis and S.Piazzolla 755
Analysis of approximations for the mode dispersion in monomode fibres. R.A.Sammut 590
Analytic expression for the frequency response and bandwidth of a spherical random array, comment on. D.Yavuz 585
Analytical relations between modal power distribution and near-field intensity in graded-index fibres. S.Piazzola and G.De Marchis 721
Angle distributions, canting, cumulative cross-polarisation and. I.J.Dilworth and B.G.Evans 603
Annealing behaviour, changes in, of SiO_2 on Si resulting from H_2^+ and D_2^+ ion bombardment. J.Belson and I.H.Wilson 420
Annealing, laser-, behaviour of GaAs, effect of Si_3N_4 encapsulation on the. M.H.Badawi, J.A.Akintunde, B.J.Sealy and K.G.Stephens 447
Annealing, scanning-electron-beam, of ion-implanted p-n junction diodes. R.A.McMahon, H.Ahmed, J.D.Speight and R.M.Dobson 433
Another method for the RC active simulation of double-terminated LC ladder filters. M.S.Piedade 571
Antenna, dipole-excited short backfire, with corrugated rim. P.S.Kooi, M.S.Leong and T.S.Yeo 421
Antenna elements, modified circular microstrip. J.McIlvenna and N.Kernweis 207
Antenna, elliptical corrugated-horn, crosspolar performance of an. R.F.E.Guy and R.W.Ashton 400
Antenna, long backfire, with insular image guide feed for dual frequency operation. R.N.Simons and D.T.Shahani 78
Antenna, omnidirectional s.h.f., consisting of horn radiators and plane reflectors. H.Thielen 639
Antenna radiation pattern, determination of, from frequency-domain measurements in reflecting environment. H.Chaloupka, M.Galka and A.Schlendermann 512
Antenna range, lens-type compact. A.D.Olver and A.A.Saleeb 409
Antenna, rectangular-waveguide-excited short backfire, with corrugated rim. M.S.Leong and P.S.Kooi 533
Antennas, broadcasting-satellite, elliptical corrugated horn for. V.J.Vokurka 652
Antennas, microstrip, improved theory for. W.F.Richards, Y.T.Lo and D.D.Harrison 42
Antennas, paraboloidal, phase centre of. Y.H.Ja 784
Antennas, quiet tuning of. M.J.Underhill and P.A.Lewis 37
Antennas, reflector and aperture, large, new approach to the analysis of, evanescent-wave tracking:. L.B.Felsen 531
Antennas, wide bandwidth microstrip, for circuit integration. P.S.Hall, C.Wood and C.Garrett 458
Application of the Cramer-Rao bound to target motion analysis. J.R.Moon 236
Appraisal of the inverted-mesa AT-cut quartz resonator for achieving low-inductance high-Q single-response crystal units. J.Birch and S.P.Marriott 641
Arbiter, one-step N-user programmable. M.Courvoisier 430
Arbitrary polarisation microwave receiver applied to OTS reception. A.P.Alves and N.J.McEwan 657
Arbitre N-utilisateurs, une ressource, programmable. M.Courvoisier 430
Arc splicing, electric, practical machine for, of optical fibres in the field. K.D.Khoe 152
Argon-ion bombardment effects on the electrical characteristics of platinum-silicon Schottky diodes. J.Garrido, E.Calleja and J.Piqueras 815
Array antennas, circularly polarised printed, composed of strips and slots. K.Ito, N.Aizawa and N.Goto 811
Array, large-bandwidth flat cylindrical, with circular polarisation and omnidirectional radiation. G.Dubost, J.Samson and R.Frin 102
Array, Routh-Hurwitz, stable reduced-order Pade approximants using the, comment on. S.A.Marshall 501
Array, spherical random, analytic expression for the frequency response and bandwidth of a, comment on. D.Yavuz 585
Array, spherical random, frequency response and bandwidth of a. D.Yavuz 314
Arrays, circular-loop Yagi, effect of reflector and exciter size on the radiation of. A.Shoamanesh and L.Shafai 103
As_2S_3-p.e.s. sandwich ribbon fibre for coupling high-refractive-index integrated optics. C.A.Millar and R.H.Hutchins 60
Asymptotic stability of differential multipass processes. D.H.Owens 446
Attenuation and depolarisation data obtained on 12GHz satellite-earth paths at four Canadian locations. P-K.Lau and J.Allnutt 565

Automatic electrochemical profiling of carrier concentration in indium phosphide. T.Ambridge and D.J.Ashen 647
Automatic electrochemical profiling of Hall mobility in semiconductors. T.Ambridge and C.J.Allen 648
Automatic selective equaliser for telephone facsimile transmission. Y.Eto and Y.Hirano 144
Avalanche photodetector, low-noise multistage. J.P.Gordon, R.E.Nahory, M.A.Pollack and J.M.Worlock 518
Avalanche photodiode, Ge, responsivity and noise characterisation of, throughout wavelength range 1.1-1.7 μm. M.C.Brain 821
Avalanche photodiodes, high-gain GaAs, with proton-implanted guard ring. N.Susa, H.Kanbe, T.Nishioka and Y.Ohmachi 535
Avalanche photodiodes, vapour-grown 1.3 μm InGaAsP/InP. G.H.Olsen and H.Kressel 141
Avoiding complex matrix manipulation for switched networks. B.G.Pain 7

B

Back-scattering technique, splice loss evaluation by means of the. B.Costa, F.Esposto, C.D'Orio and P.Morra 550
Backscatter, optimisation of, using the concept of complex characteristic polarisations. S.H.W.Simpson and B.Chambers 547
Backscattering measurements in optical fibres: separation of power decay from imperfection contribution. P.Di Vita and U.Rossi 467
Backscattering method, field measurement of splice loss applying the. P.Matthijsse and C.M.De Blok 795
Bandlimited signals, nonperiodic, general relations for, in three-dimensional electron flow. P.Proksch 328
Bandpass filters, digital, variable-centre-frequency constant-bandwidth linear-phase. S.S.Ahuja and S.C.Dutta Roy 245
Bandpass filters, maximally flat digital, sine-cosine squared-magnitude function for, with adjustable skirt selectivities. P.Thajchayapong and F.Cheevasuvit 345
Bandpass filters, two-dimensional variable f.i.r.. S.S.Ahuja 551
Bandwidth extension, method of, for the Ruthroff transformer. R.T.Irish 790
Bandwidth-limited operation of nonideal graded-index fibres. L.Jeunhomme 149
Baritt diodes, higher output power from, using ion implantation. B.M.Armstrong, R.A.Moore and J.Wakefield 153
Baseband compatible s.a.w. processors. G.F.Manes and C.Atzeni 661
Baseband-frequency-response measurement of graded-index fibre using step-index fibre as an exciter. T.Tanifuji, T.Horiguchi and M.Tokuda 203
Beam-lead mixer diodes, high-performance GaAs, for millimetre and submillimetre applications. J.A.Calviello, J.L.Wallace and P.R.Bie 509
Bidirectional analogue optical transmission using semiconductor junction transceivers. R.I.Macdonald 121
Bipolar transistor power amplifier, high-gain 9.25 GHz silicon. Y.S.Wu, H.T.Yuan and W.R.Wisseman 86
Birefringence in elliptically deformed optical fibres. J.D.Love, R.A.Sammut and A.W.Snyder 615
Birefringence in optical fibres with elliptical cross-section. M.J.Adams, D.N.Payne and C.M.Ragdale 298
Birefringence, single-mode fibres exhibiting extremely low polarisation, fabrication of. S.R.Norman, D.N.Payne, M.J.Adams and A.M.Smith 309
Bitaper star couplers with up to 100 fibre channels. E.G.Rawson and M.D.Bailey 432
Boolean function, distribution of symmetry information in spectrum of. D.M.Miller and J.C.Muzio 816
Boundedness properties of nonlinear multivariable feedback systems. D.P.Atherton and D.H.Owens 559
Boundedness properties of nonlinear multivariable systems. S.Mossaheb 803
Broadband amplifiers, matched b.j.t. cascode, synthesis of. D.J.Ahlgren 709
Broadband resonant filter using surface-shear-wave mode and twin-turn reflector. Y.Kinoshita, M.Hikita, T.Tabuchi and H.Kojima 130
Broadcasting-satellite antennas, elliptical corrugated horn for. V.J.Vokurka 652

C

C.C.D. adaptive filter, compact high-performance, noise cancellation and inverse filtering using a. C.F.N.Cowan, J.Mavor and J.W.Arthur 35
C.C.D. adaptive filter employing parallel coefficient updating. N.R.Massey, P.M.Grant and J.Mavor 573
C.C.D. channel filter, high-performance, for a p.c.m. codec. T.Enomoto, T.Ishihara, M.Yasumoto and S.Shida 817
C.C.D., integrating-input technique for. C.J.Oliver, A.H.James, D.V.McCaughan, J.R.Hill and J.C.White 497
C.C.D. (m.c.c.d.) recursive filter, meander-channel. Y.Miyamoto, K.Tanikawa, H.Sei and S.Kato 320
C.C.D. recursive filters, programmable, coefficient correction in. T.G.Tang, Y.T.Yeow and J.Mavor 630
C.C.D.S., floating-gate tapped, two-dimensional inverse filter using. T.Enomoto, M.Yasumoto and K.Watanabe 280
C.C.D. serial-parallel-serial memory, adaptive cancellation of fixed-pattern noise in. R.C.Geddes, C.F.N.Cowan, J.Mavor and J.F.Dickson 505
C.C.D. tapped delay lines, charge-splitting. J.R.Hill, D.V.McCaughan, J.M.Keen and J.C.White 204
C.C.D. transversal filter with a three-level polysilicon structure. K.Tanikawa, Y.Ito, T.Yamamoto, S.Miura, Y.Miyamoto and S.Kato 311
C.C.D. transversal filters, new charge-differencing technique for. J.Fox and J.F.Dickson 229
C.M.O.S. technology, dynamic amplifiers in. B.J.Hosticka 819
C.P.S.K. system, error performance of, in the presence of interference. S.G.Glišić 97
C.T.D.S., step and frequency responses of, with nonuniform transfer inefficiency. R.M.Barsan 389
C.V.D., metalorganic, growth of GaAs-GaAlAs double heterojunction lasers having low interfacial recombination and low threshold current. E.J.Thrush, P.R.Selway and G.D.Henshall 156
Cable, low-loss and low-dispersion single-mode, 800 Mb/s fibre transmission test using. K.Nakagawa, Y.Hakamada and K-I.Suto 747
Cables, braided coaxial, transfer impedance of, under applied longitudinal torsion. M.M.Rahman, J.E.Sitch and F.A.Benson 455
Calibration equations, explicit solution of, for a dual 6-port network analyser. D.Woods 718
Capacitance of a microstrip of unequal widths in a homogeneous medium. R.K.L.Poon 44
Capacitance techniques, transient, hole traps in n-InP by d.l.t.s. and. A.N.M.M.Choudhury and P.N.Robson 247
Capacitor floatation scheme, novel. D.Patranabis and A.N.Paul 688
Capacitor, m.o.s., measurement arrangement for direct capacitance/surface-potential recording on. H.C.G.Ligtenberg and J.Snijder 523
Capacitor simulation, insensitive grounded-, of grounded inductors using current conveyors. R.Nandi 693
Capacitors, simple implementation of sampled-data filters using current multipliers, switches and. J.I.Arreola, Y.P.Tsividis, E.Sanchez-Sinencio and P.E.Allen 780
Carrier concentration, automatic electrochemical profiling of, in indium phosphide. T.Ambridge and D.J.Ashen 647
Carrier concentration profiling, electrochemical, in silicon. C.D.Sharpe, P.Lilley, C.R.Elliott and T.Ambridge 622
Cauer continued fraction, modified, system reduction by Routh approximation and. S.(Mrs) John and R.Parthasarathy 691
CdTe/Langmuir-film m.i.s. structures. M.C.Petty and G.G.Roberts 335
Ceramic capillary connector for 1.3 μm single-mode fibres. N.Suzuki, Y.Iwahara, M.Saruwatari and K.Nawata 809
Ceramic capillary splices for optical fibres. K.Nawata, Y.Iwahara and N.Suzuki 470
Changes in annealing behaviour of SiO_2 on Si resulting from H_2^+ and D_2^+ ion bombardment. J.Belson and I.H.Wilson 420
Changes in the thermal oxidation of gallium arsenide induced by ion implantation. D.N.Butcher and B.J.Sealy 51
Channelled-substrate narrow-stripe GaAs/GaAlAs injection lasers with extremely low threshold currents. P.A.Kirkby 824
Characterisation of ternary threshold functions using a partial spectrum. C.Moraga 803
Characteristic function for quasielliptic filters. B.D.Rakovich and M.V.Popovich 292
Characteristics against length of silicone-clad silica optical fibres. I.Nouchi, A.Jacques and L.D'Auria 315
Charge-splitting c.c.d. tapped delay lines. J.R.Hill, D.V.McCaughan, J.M.Keen and J.C.White 204
Charge storage in s.a.w. memory correlators. M.El-Nokali and E.L.Adler 323
Charge-transfer devices, compact helium speech unscrambler using. M.A.Jack, A.D.Milne and L.E.Virr 548
Checking of square-law detectors used in Hartshorn and Ward dielectric measurements. R.N.Clarke 183
Chemical vapour deposition, organometallic, GaAs m.e.s.f.e.t. prepared by. H.Morkoc, J.Andrews and V.Aebi 105
Circuit principle:, translinear, a reformulation. B.L.Hart 801
Circuits, equivalent, for high-frequency sonar transducers. H.Koymen, B.V.Smith and B.K.Gazey 600
Circular waveguide system, v.l.a., TE_{on}-mode filters for the. J.W.Archer 343
Circularly polarised printed array antennas composed of strips and slots. K.Ito, N.Aizawa and N.Goto 811
Clocking systems, fault-tolerant digital. W.R.Moore 722
Code modulation of m-sequences. K.W.Yates and D.J.Holgate 836
Code, multilevel, for high information rates. D.Munoz-Rodriguez 272
Codes, B.C.H. and R.S., decoding of, with errors and erasures using continued fractions. I.S.Reed, T.K.Truong and R.L.Miller 542
Codes, B.C.H. and Reed-Solomon, fast technique for computing syndromes of. T.K.Truong, R.L.Miller and I.S.Reed 720
Coefficient correction in programmable c.c.d. recursive filters. T.G.Tang, Y.T.Yeow and J.Mavor 630
Coherent pulse generation with a GaAlAs laser by active modelocking. P-T.Ho 526
Combination of complex rectangular transforms and f.n.t. to implement fast convolution. N.S.Reddy and V.U.Reddy 716
Comment on Active simulation of inductors using current conveyor. A.Nedungadi 112
Comment on alternative approach to the design of switched-capacitor filters. J.J.Hill 650
Comment on Analytic expression for the frequency response and bandwidth of a spherical random array. D.Yavuz 585
Comment on D.C. solutions of bipolar-transistor circuits. C.J.F.Ridders 63
Comment on Inductance simulation and filter design using a single-pole amplifier approximation. E.Sánchez-Sinencio and D.Báez-López 465
Comment on Linear-phase digital anti-aliasing filter. S.E.Williamson, W.Matley and R.E.H.Bywater 793
Comment on multifunction active R filter with two operational amplifiers. R.Nandi 261
Comment on Multifunction active R filter with two operational amplifiers. E.Sánchez-Sinencio 262
Comment on practical aspects of filters using amplifier poles. R.Schaumann, J.R.Brand and K.R.Laker 493
Comment on Simple method for computing elements of order $2^p n$, where $n/2^{p-1}-1$ and $2 \leq k \leq p+1$, in $GF[(2^{p-1}-1)^2]$. D.V.Sarwate 69
Comment on Simulation of inductors and capacitors using operational amplifier compensation pole: a caution. S.Srinivasan and K.Radhakrishna Rao 472
Comment on Stable reduced-order Pade approximants using the Routh-Hurwitz array. S.A.Marshall 501
Communication, fibre-optic, low-loss 4 x 4 optical matrix switch for. Y.Fujii, J.Minowa, T.Aoyama and K.Doi 427
Communications, 800 MHz microwave mobile radiotelephone, user density for. D.R.Conn and R.Maciejko 516
Compact dual-hybrid-mode feeds with low crosspolar radiation. S.C.J.Worm 740
Compact helium speech unscrambler using charge-transfer devices. M.A.Jack, A.D.Milne and L.E.Virr 548
Compact polynomial forms of sensitivity criteria. C.L.Nikias and W.F.Fincham 23
Comparison of GaAs Impatt designs for 20 GHz. J.J.Berenz, M.Vichr and F.B.Fank 694
Compensation degradation mechanism for high-efficiency GaAs Impatt diodes. J.G.Smith 74
Compensation for parasitic capacitances in switched-capacitor filters. G.C.Temes and R.Gregorian 377
Compensation of profile dispersion in graded-index optical fibres. S.Geckeler 682
Concavity and sensitivity of electrical resistance functions. F.Reza 305
Conductor, cylindrical, exact surface impedance for a. J.R.Wait 659

Configurations for the complex-internal-reflection (c.i.r.) light modulator. T.W.Cole 217
Confined guided modes in W-fibre with square core. V.V.Cherny 281
Connector, ceramic capillary, for 1.3 μm single-mode fibres. N.Suzuki, Y.Iwahara, M.Saruwatari and K.Nawata 809
Connector, demountable multiple, with precise V-grooved silicon. Y.Fujii, J.Minowa and N.Suzuki 424
Connectors, fibre, wavelength-dependent transmission at. K.Petermann 706
Connectors, optical-fibre, minimisation of modal noise in. B.Culshaw 529
Contacts, improved ohmic properties of Au-Ge, to thin n-GaAs layers alloyed with an SiO_2 overlayer. F.Vidimari 674
Continuous measurement of electron density in unmagnetised plasmas by a self-oscillating probe. R.Debrie and J.Pignard 799
Contouring, proposed technique for reduction of, in quantised (monochrome) image signals. O.J.Downing and P.L.M.Thorpe 5
Contribution of the discrete modes to the current propagating along a wire parallel to a moderate conducting earth. G.Courbet, P.Degauque, B.Demoulin and R.Gabillard 174
Controllability, numerically reliable algorithm to test. A.Varga 452
Controller, optimally sensitive, for digital systems. W.F.Fincham and C.L.Nikias 537
Controller, self-tuning, steady-state error. A.Y.Allidina and F.M.Hughes 346
Convergence of adaptive lattice filters. T.S.Durrani and N.L.M.Murukutla 833
Conversion gain of m.e.s.f.e.t. drain mixers. G.Begemann and A.Jacob 567
Convertor technique, universal operational-amplifier, using supply-current sensing. B.L.Hart and R.W.J.Barker 496
Convertors, low-cost analogue voltage-voltage, with arbitrary transfer characteristics. S.Suzuki, S.Shinmyo and J.Sasaki 170
Conveyors, current, simplified design procedures for a third-order system using. F.W.Stephenson and J.Dunning-Davies 215
Convolution algorithm, remarks on the, of Agarwal and Cooley. J.M.Pollard 593
Corona current, similitude between ionic wind, discharge pattern and. L.C.Thanh 57
Correlation functions, discrete Fourier transform of. J.R.Jordan 196
Correlation technique for improved isolation of overlapping spectra in video modulators. A.J.Clapton 429
Correlators, s.a.w. memory, charge storage in. M.El-Nokali and E.L.Adler 323
Coupled-line circuit with adjustable input conductance. S.R.Mazumder and F.E.Gardiol 91
Coupler, novel beam-to-waveguide, for $LiNbO_3$ optical waveguides. J.Čtyroký, M.Cada, N.M.Lyndin, V.A.Sychugov and J.Schroefel 519
Coupler performance, multistrip, for surface-skimming bulk waves on lithium tantalate. E.G.S.Paige and P.Whittle 374
Coupler switches, electro-optically controlled directional, integrated bistable optical multi-vibrator using. H.Ito, Y.Ogawa, K.Makita and H.Inaba 791
Coupler, tee-, for single-mode fibres. E.Weidal and D.Gruchmann 737
Crosspolar performance of an elliptical corrugated-horn antenna. R.F.E.Guy and R.W.Ashton 400
Crosspolarisation, cumulative, and canting angle distributions. I.J.Dilworth and B.G.Evans 603
Crosstalk, near-end, error probability due to Gaussian noise and. R.J.S.Bates 116
Crosstalk, optimum p.c.m. regenerator performance in presence of. A.J.Gibbs, L.J.Millott and G.Nicholson 490
Crosstalk performance, p.c.m. regenerator, measurement of. A.J.Gibbs 82
Cryogenically cooled mixer, improvements on a, for 80-120 GHz. R.W.Haas 115
Crystal-oscillator-based device for remote power-line temperature sensing. P.L.Arlett, A.Walton, K.Elkins and K.O'Neill 93
Crystal units, achieving low-inductance high-Q single-response, appraisal of the inverted-mesa AT-cut quartz resonator for. J.Birch and S.P.Marriott 641
Cumulative crosspolarisation and canting angle distributions. I.J.Dilworth and B.G.Evans 603
Current conveyor, single, new canonic single-resistance-controlled sinusoidal oscillator using a. R.Senani 568
Current conveyors, insensitive grounded-capacitor simulation of grounded inductors using. R.Nandi 693
Current multipliers, switches, and capacitors, simple implementation of sampled-data filters using. J.I.Arreola, Y.P.Tsividis, E.Sanchez-Sinencio and P.E.Allen 780
Current, new representation for the, in a horizontal wire above ground. M.P.Carpentier and A.F.Dos Santos 554

D

D.C. solutions of bipolar-transistor circuits, comment on. C.J.F.Ridders 63
D.C. Squid with high energy resolution. P.Gutmann 372
D.F.T. computation by fast polynomial transform algorithms. H.J.Nussbaumer 701
D.L.T.S., effects of laser irradiation of GaAs observed by. N.G.Emerson and B.J.Sealy 553
D.L.T.S. experiments, physics, high-resolution analysis of exponentially decaying transients for. M.S.Hodgart 724
D.L.T.S. spectra, synthesis and analysis of, from m.o.s. surface states. K.R.Whight 744
D.P.C.M. of Pal signals, noninteger sampling to subcarrier frequency ratios in. H.Gharavi and R.Steele 483
D.V.C.C.S., one, floating ideal inductor with. D.Patranabis and A.N.Paul 545
Data-acquisition system, novel computer-based infrared pedestrian. S.S.Mudaly 371
Data-link applications, miniaturised, hybrid, 500 Mb/s optical receiver package for. T.N.C.Venkatesan and K.Ogawa 171
Data transmission, filters for, with minimum intersymbol interference. B.M.Djurich and C.M.Zivaljevich 288
Decentralised transmission zeros of linear multivariable continuous-time systems. B.Porter and A.Bradshaw 230
Decoding of B.C.H. and R.S. codes with errors and erasures using continued fractions. I.S.Reed, T.K.Truong and R.L.Miller 542
Decoding, soft-decision, of the teletext character code. R.M.F.Goodman 108
Decoupled contrcl of robot movement. J.R.Hewit 670
Deep levels, effects of ion implantation on, in GaAs. T.R.Jervis, D.W.Woodard and L.F.Eastman 619
Definitive profile-dispersion data for germania-doped silica fibres over an extended wavelength range. F.M.E.Sladen, D.N.Payne and M.J.Adams 469
Delay lines, charge-splitting c.c.d. tapped. J.R.Hill, D.V.McCaughan, J.M.Keen and J.C.White 204
Delay lines, surface-acoustic-wave, technique for triple-transit suppression in. W.J.Tanski and H.Van de Vaart 312
Demodulator, decision-directed c.p.s.k., performance degradation of, due to uncompensated time delay of decision circuitry. S.G.Glisić 331
Demountable multiple connector with precise V-grooved silicon. Y.Fujii, J.Minowa and N.Suzuki 424
Depletion-type m.o.s.f.e.t.s. for low-temperature operation. M.Kawashima, M.Kanamori and M.Matsumura 759
Depolarisation data, attenuation and, obtained on 12GHz satellite-earth paths at four Canadian locations. P-K.Lau and J.Allnutt 565
Design of f.i.r. direct-form digital filters with two quantisation steps. F.Grenez 124
Design of minimum-phase charge-transfer transversal filters. M.Feldmann, J.Henaff, B.Lacroix and J.C.Rebourg 226
Design of optimal controller for linear single-input system. LimChoo.Mim and B.S.Habibullah 660
Detailed evaluation of an attainable repeater spacing for fibre transmission at 1.3 μm and 1.55 μm wavelengths. K.Nakagawa and T.Ito 776
Detection of minority-carrier traps using transient spectroscopy. R.Brunwin, B.Hamilton, P.Jordan and A.R.Peaker 349
Detector, InGaAsP wavelength-demultiplexing, dual-channel 1.5 Mb/s lightwave receiver employing an. T.P.Lee, J.C.Campbell, K.Ogawa, A.R.McCormick, A.G.Dentai and C.A.Burrus 388
Detector, peak-amplitude, for sinusoidal signals. S.Pookaiyaudom, C.Watanachaiprateep and K.Dejhan 127
Detectors, square-law, checking of, used in Hartshorn and Ward dielectric measurements. R.N.Clarke 183
Determination of antenna radiation pattern from frequency-domain measurements in reflecting environment. H.Chaloupka, M.Galka and A.Schlendermann 512
Dielectric measurements, Hartshorn and Ward, checking of square-law detectors used in. R.N.Clarke 183
Dielectric waveguide, slab, new rigorous analysis of the step discontinuity in a. Ph.Gelin, M.Petenzi and J.Citerne 355
Dielectric waveguides, elliptical, higher-mode cutoff in. J.R.Cozens and R.B.Dyott 558
Differentiations, high-order, rapidly converging observers involve. M.Zeitz 708
Digital-analogue, precision fast, some proposals for improved forms of, and analogue-digital converters. J.R.Stockton and R.B.D.Knight Errata 166
Digital anti-aliasing filter, linear-phase. S.E.Williamson, W.Matley and R.E.H.Bywater 539
Digital anti-aliasing filter, linear-phase, comment on. S.E.Williamson, W.Matley and R.E.H.Bywater 793
Digital bandpass filters, maximally flat, sine-cosine squared-magnitude function for, with adjustable skirt selectivities. P.Thajchayapong and F.Cheevasuvit 345
Digital bandpass filters, variable-centre-frequency constant-bandwidth linear-phase. S.S.Ahuja and S.C.Dutta Roy 245
Digital discriminator:, a.d. convertor using, an experimental result. A.Akademir and C.S.Aitchison 379
Digital filter design, nonrecursive, new integer programming scheme for. L.Yong-Ching and A.G.Constantinides 812
Digital filters, bilinear, engineering approach to the L_∞-norm scaling of. D.T.Nguyen 353
Digital filters, designing recursive, method for, with short wordlength. H-K.Kwan 128 Errata 361
Digital filters, error-feedback. T-L.Chang 348
Digital filters, f.i.r. direct-form, design of, with two quantisation steps. F.Grenez 124
Digital filters, microprocessor-based, alternative multiplication configuration in. P.J.Allen and A.G.J.Holt 481
Digital frequency discriminator. F.G.A.Coupe 489
Digital pictures, streak and spot detection in. B.G.Batchelor 352
Digital processing technique for suppressing the interfering outputs in the image from an inline hologram. K.H.S.Marie, J.C.Bennett and A.P.Anderson 241
Digital radio links:, validity of two-path model for calculating quality of, determination of model from measurements on analogue links. M.Rooryck 783
Digital signal, balanced, power spectrum of the, generated by Markov source. G.Petrović 769
Digital systems, optimally sensitive controller for. W.F.Fincham and C.L.Nikias 537
Digital techniques, transmitter drive using, to give frequency modulation. P.Shelswell 68
Digraph analysis of large-scale systems: the system primitive. F.J.Evans and C.Schizas 613
Diode lasers, InP/InGaAsP/InP double heterostructure, room-temperature c.w. operation of, emitting at 1.55 μm. H.Kawaguchi, K.Takahei, Y.Toyoshima, H.Nagai and G.Iwane 669
Diode, small-area GaAs-GaAlAs heterostructure light-emitting, with improved current confinement. M.-C.Amann and W.Proebster 599
Diode structures, forward-biased, numerical analysis of, based on direct-gap semiconductors. E.Velmre and B.Freidin 383
Diodes, alloyed planar, in indium antimonide. K.Riedling, F.Olcaytug and W.Fallmann 572
Diodes, high-efficiency GaAs Impatt, compensation degradation mechanism for. J.G.Smith 74
Diodes, high-performance GaAs beam-lead mixer, for millimetre and submillimetre applications. J.A.Calviello, J.L.Wallace and P.R.Bie 509
Diodes, ion-implanted p-n junction, scanning-electron-beam annealing of. R.A.McMahon, H.Ahmed, J.D.Speight and R.M.Dobson 433
Diodes, low-barrier-height epitaxial Ge-GaAs mixer. A.Christou, J.E.Davey and Y.Anand 324
Dipole-excited short backfire antenna with corrugated rim. P.S.Kooi, M.S.Leong and T.S.Yeo 421
Dipoles, thin, input impedance of, by moment method. R.Neri 418
Direct jitter measurement technique. P.Cochrane, I.W.Barley and J.J.O'Reilly 774
Direct modulation characteristics of GaInAsP/InP d.h. lasers with various stripe widths measured by sharp-pulse method. Y.Sakakibara, K.Furuya, Y.Suematsu and Y.Itaya 594
Directional coupling of magnetostatic surface waves in layered magnetic thin films. H.Sasaki and N.Mikoshiba 172
Discharge mechanisms in floating-gate e.p.r.o.m. cells. J.R.Davis 20
Discharge pattern, similitude between ionic wind, and corona current. L.C.Thanh 57
Discrete Fourier transform of correlation functions. J.R.Jordan 196
Discrete frequency synthesis using an analogue r.o.m.. G.F.Manes and C.Atzeni 350

Discrete systems, stochastic linear, optimal input for, as a function of input and output variables. C.S.Berger 360
Discrete-time linear-quadratic optimal tracking problem using future desired output values. J.Karpinsky, T.Benes, V.Hlavaty, V.Rozkosny and P.Sejal 316
Discriminator, digital frequency. F.G.A.Coupe 489
Dispersion, chromatic, effect of, on pulses of arbitrary coherence. D.Gloge 686
Dispersion data, definitive profile-, for germania-doped silica fibres over an extended wavelength range. F.M.E.Sladen, D.N.Payne and M.J.Adams 469
Dispersion-free single-mode fibre in 1.5 μm wavelength region. H.Tsuchiya and N.Imoto 476
Dispersion-free single-mode fibre transmission experiments up to 1.6 Gbit/s. Jun-Ichi.Yamada, S.Machida, T.Kimura and H.Takata 278
Dispersion in graded single-mode fibres. A.W.Snyder and R.A.Sammut 269
Dispersion, material, influence of waveguide effects on pulse-delay measurements of, in optical fibres. A.H.Hartog 632
Dispersion minimisation in single-mode fibres between 1.3 μm and 1.7 μm. L.Jeunhomme 478
Dispersion minimisation in single-mode fibres over a wide spectral range. K.Okamoto, T.Edahiro, A.Kawana and T.Miya 729
Dispersion, minimum, at 1.55 μm for single mode step-index fibres. C.T.Chang 765
Dispersion, modal, of optical fibres with a composite α-profile graded-index core. A.Weierholt 733
Dispersion, mode, of trapezoidal cross-section dielectric optical waveguides by the effective-index method. J.G.Gallagher 734
Dispersion, total, in step-index monomode fibres. C.R.South 394
Dispersion, zero total, in graded-index single-mode fibres. W.A.Gambling, H.Matsumara and C.M.Ragdale 474
Dispersion, zero total, in step-index monomode fibres at 1.30 and 1.55 μm. K.I.White and B.P.Nelson 396
Distortion of light signals transmitted via multimode graded-index fibres. K.Stubkjaer 797
Distribution of symmetry information in spectrum of Boolean function. D.M.Miller and J.C.Muzio 816
Diversity reception for error-rate reduction in mobile-radio data links. J.D.Parsons and A.Pongsupaht 202
Doppler processing, form of, for radars of random p.r.i. and r.f.. R.Benjamin 782
Double-alkali effect: influence on index profile of ion-exchanged waveguides. V.Neuman, O.Parriaux and L.M.Walpita 704
Double-sided least-squares problem. K.V.M.Fernando and H.Nicholson 624
Drain mixers, m.e.s.f.e.t., conversion gain of. G.Begemann and A.Jacob 567
Drift velocity, transient, influence of central valley effective mass and alloy scattering on, in $Ga_{1-x}In_xP_{1-y}As_y$. M.A.Littlejohn, L.A.Arledge, T.H.Glisson and J.R.Hauser 586
Dual-channel 1.5 Mb/s lightwave receiver employing an InGaAsP wavelength-demultiplexing detector. T.P.Lee, J.C.Campbell, K.Ogawa, A.R.McCormick, A.G.Dentai and C.A.Burrus 388
Dual-gate m.e.s.f.e.t. self-oscillating X-band mixers. R.Stahlmann, C.Tsironis, F.Ponse and H.Beneking 524
Dual-mode transmission technique for Chinese ideographs in a teletext system. P.C.K.Kwok and J.P.K.Lai 268
Dynamic amplifier for m.o.s. technology. M.A.Copeland and J.M.Rabaey 301
Dynamic amplifiers in c.m.o.s. technology. B.J.Hosticka 819
Dynamic permittivity of microstrip ring resonator. J.Vrba 504
Dynamic programming, propagation delay optimisation in multistage GaAs m.e.s.f.e.t. combinational logic circuits by use of. A.Barna 147

E

E.P.R.O.M. cells, floating-gate, discharge mechanisms in. J.R.Davis 20
Effect of chromatic dispersion on pulses of arbitrary coherence. D.Gloge 686
Effect of feedback delay on tracking-loop frequency acquisition. C.P.Ashall and P.A.Matthews 231
Effect of finite size of ground plane on the impedance of a monopole immersed in a lossy medium. I.J.Bahl and S.S.Stuchly 728
Effect of injection current on the dielectric constant of an inbuilt waveguide in twin-transverse-junction stripe lasers. S.E.H.Turley, G.H.B.Thompson and D.F.Lovelace 256
Effect of ionising radiation on mobile-ion density in m.o.s. oxides. T.N.Bhar, R.Dat, R.Y.Koyama and K.F.Galloway 16
Effect of reflector and exciter size on the radiation of circular-loop Yagi arrays. A.Shoamanesh and L.Shafai 103
Effect of Si_3N_4 encapsulation on the laser-annealing behaviour of GaAs. M.H.Badawi, J.A.Akintunde, B.J.Sealy and K.G.Stephens 447
Effects of drop size and temperature on forward and backward scattering of microwaves by raindrops. S.A.J.Upton, B.G.Evans and A.R.Holt 760
Effects of emitter edge dislocations on the low-frequency noise of silicon planar n-p-n transistors. N.D.Stojadinović 340
Effects of ion implantation on deep levels in GaAs. T.R.Jervis, D.W.Woodard and L.F.Eastman 619
Effects of laser irradiation of GaAs observed by d.l.t.s.. N.G.Emerson and B.J.Sealy 553
Efficient transforms for multidimensional convolutions. B.Arambepolar and P.J.W.Rayner 189
Eigenvalues of noise covariance matrix of linear array in the presence of two directional interferences. P.C.K.Kwok and P.S.Brandon 50
Electrical properties of coplanar transmission lines on lossless and lossy substrates. J.-P.Becker and D.Jäger 88
Electrical properties of silicon-implanted furnace-annealed silicon-on-sapphire devices. M.E.Roulet, P.Schwob, I.Golecki and M.-A.Nicolet 527
Electro-optically controlled directional coupler switches, integrated bistable optical multivibrator using. H.Ito, Y.Ogawa, K.Makita and H.Inaba 791
Electrochemical carrier concentration profiling in silicon. C.D.Sharpe, P.Lilley, C.R.Elliott and T.Ambridge 622
Electrochemical profiling, automatic, of carrier concentration in indium phosphide. T.Ambridge and D.J.Ashen 647
Electrochemical profiling, automatic, of Hall mobility in semiconductors. T.Ambridge and C.J.Allen 648
Electromagnetic power absorption in cylindrical tissue models excited by a loop antenna. T.Yoneyama, T.Suzuki and S.Nishida 125
Electron-beam annealing of ion-implanted silicon. R.A.McMahon and H.Ahmed 45
Electron-beam, scanning-, annealing of ion-implanted p-n junction diodes. R.A.McMahon, H.Ahmed, J.D.Speight and R.M.Dobson 433
Electron density, continuous measurement of, in unmagnetised plasmas by a self-oscillating probe. R.Debrie and J.Pignard 799
Electron devices:, GaAs transferred-, frequency limitation of, influence of operating d.c. and r.f. field values. P.A.Rolland, E.Constant, G.Salmer and R.Fauquembergue 373
Electron flow, three-dimensional, general relations for nonperiodic bandlimited signals in. P.Proksch 328
Electron traps in n-InP grown by the synthesis solute-diffusion method. K.Tsubaki, E.Kubota and K.Sugiyama 513
Electrons, secondary, s.a.w. convolver using. A.A.Dobrovolsky, V.V.Lemanov, G.A.Smolensky and A.B.Sherman 437
Electrostatic probe, new, for absolute measurement of amplitude of surface acoustic wave. J.B.Moreau, R.Hashim and J.C.Neau 155
Elliptical corrugated horn for broadcasting-satellite antennas. V.J.Vokurka 652
Elliptical hollow conducting waveguides, surface impedance of. S.R.Rengarajan and J.E.Lewis 637
Encoding, simple adaptive vectors, for two-dimensional redundancy reduction (Saver). P.K.S.Wah 221
Energy and power of bandlimited fields in lossless nonlinear media. P.Proksch 521
Energy-trapped shallow bulk acoustic waves. K.H.Yen, K.F.Lau and R.S.Kagiwada 206
Engineering approach to the L_∞-norm scaling of bilinear digital filters. D.T.Nguyen 353
Enhancement- and depletion-mode vertical-channel m.o.s. gated thyristors. B.Baliga 645
Equalisation, adaptive, roll-off shaping filter design for improving. K.Wesolowski 338
Equaliser, automatic selective, for telephone facsimile transmission. Y.Eto and Y.Hirano 144
Equaliser, new adaptive, with infinite impulse response. Y.I.Jin 557
Equivalent circuits for high-frequency sonar transducers. H.Koymen, B.V.Smith and B.K.Gazey 600
Error-feedback digital filters. T-L.Chang 348
Error performance of c.p.s.k. system in the presence of interference. S.G.Glišić 97
Error probability due to Gaussian noise and near-end crosstalk. R.J.S.Bates 116
Error-rate reduction, diversity reception for, in mobile-radio data links. J.D.Parsons and A.Pongsupaht 202
Estimation of linearly constrained parameters via the Kalman filter. J.E.Hudson 319
Errata 478
Evaluation of the transient response of linear stationary systems to a class of excitations. M.M.Milić and M.V.Gmitrović 614
Evanescent-wave tracking: new approach to the analysis of large reflector and aperture antennas. L.B.Felsen 531
Evidence of collector-base junction burst noise. K.F.Knott 198
Evidence of trapping in device-quality liquid-phase-epitaxial $In_{1-x}Ga_xAs_yP_{1-y}$. P.K.Bhattacharya, J.W.Ku, S.J.T.Owen, S.H.Chiao and R.Yeats 753
Exact surface impedance for a cylindrical conductor. J.R.Wait 659
Experimental study of surface-wave propagation on a low-permittivity medium. J.Appel-Hansen and R.J.King 101
Explicit solution of calibration equations for a dual 6-port network analyser. D.Woods 718
Extending the low-frequency range of GaAs f.e.t. broadband microwave amplifiers using microstrip transmission lines. C.M.Krowne 197
Extension of finite-element method to unbounded field problems. S.Washisu, I.Fukai and M.Suzuki 772

F

F.E.T., 1 W, at 5 GHz, simple model of large-signal properties of. K.L.Kotzebue and E.R.Ehlers 237
F.E.T. amplifier, 14-GHz band 1 watt GaAs. J.Sone, Y.Takayama and Y.Aono 212
F.E.T. amplifiers, Kuand K-band internally matched high-power GaAs. J.Sone and Y.Takayama 562
F.E.T. broadband microwave amplifiers, GaAs, extending the low-frequency range of, using microstrip transmission lines. C.M.Krowne 197
F.E.T., GaAs heterojunction, with epitaxial Ge gate. Jun.Anderson,W.T., J.E.Davey, A.Christou, M.L.Bark, K.J.Sleger and H.B.Dietrich 11
F.E.T.-input operational amplifiers, nonlinear modelling of. P Bowron and A.Mohamed 473
F.E.T. operation, pulsed GaAs, for high peak output powers. P.C.Wade, D.Rutkowski and I.Drukier 591
F.E.T. oscillator, high peripheral power density GaAs. J.S.Joshi and J.A.Turner 163
F.E.T.S, GaAs, light-induced effects in. J.Graffeuil, P.Rossel and H.Martinot 439
F.E.T.S., GaAs microwave, trap localisation in the active layer of. D.Meignant, D.Bois-con-Gibod and J.M.Bourgeois 779
F.E.T.S., ion-implanted GaAs X-band power. F.H.Doerbeck, H.M.Macksey, G.E.Brehm and W.R.Frensley 576
F.E.T.S, low-noise microwave, fabricated by molecular-beam epitaxy. S.G.Bandy, D.M.Collins and C.K.Nishimoto 218
F.E.T.S., power GaAs, 11 GHz and 12 GHz multiwatt internal matching for. Y.Takayama, T.Ogawa and Y.Aono 326
F.E.T. structures, novel, preparation and properties of GaAs layers for. R.J.M.Griffiths, I.D.Blenkinsop and D.R.Wight 629
F.E.T. transimpedance front-end design, GaAs, for a wideband optical receiver. K.Ogawa and E.L.Chinnock 650
F.E.T., X- and KU-band internally matched packaged GaAs. H.Derewonko, M.Laviron and J.Lepage 8
Fabrication of channel optical waveguide using CO_2 laser. H.Terui and M.Kobayashi 79
Fabrication of single-mode fibres exhibiting extremely low polarisation birefringence. S.R.Norman, D.N.Payne, M.J.Adams and A.M.Smith 309
Fabry-Perot tuning, milliwave, and modulation by electrically variable external reactance. A.Godone, E.Bava and A.De Marchi 370
Facsimile transmission, telephone, automatic selective equaliser for. Y.Eto and Y.Hirano 144
Fast computation of s.a.w. filter responses including diffraction. E.B.Savage 538
Fast-Fourier-transform algorithm, multidimensional. B.Arambepola and P.J.W.Rayner 382
Fast on-line implementation of two-dimensional median filtering. G.Garibotto and L.Lambarelli

Fast s.a.w.-based discrete Fourier transformer. J.B.G.Roberts, B.J.Darby, R.A.Bale and R.Eames Errata 262
Fast technique for computing syndromes of B.C.H. and Reed-Solomon codes. T.K.Truong, R.L.Miller and I.S.Reed 720
Fault detection in Moore-model sequential machine using counter-cycle technique. A.Bhattacharyya 402
Fault-tolerant digital clocking systems. W.R.Moore 722
Feasibility of focused microwave array system for tumour irradiation. A.P.Anderson, M.Melek and B.H.Brown 564
Feed position for a parabolic reflector with offset pattern. S.Cornbleet 211
Feedback delay, effect of, on tracking-loop frequency acquisition. C.P.Ashall and P.A.Matthews 231
Feedback digital filters, error-,. T-L.Chang 348
Feedback systems, nonlinear multivariable, boundedness properties of. D.P.Atherton and D.H.Owens 559
Feeds, compact dual-hybrid-mode, with low crosspolar radiation. S.C.J.Worm 740
Ferrite device, a new multipurpose, nonreciprocal directional filter:. R.R.Bonetti 233
FEXT calculations, simplified. R.V.McLachlan 545
Fibre baseband frequency response measurement, multimode, with single frequency output extracted from modulated InGaAsP laser. S.Machida, N.Imoto and Y.Ohmori 607
Fibre channels, 100, bitaper star couplers with up to. E.G.Rawson and M.D.Bailey 432
Fibre connectors, low-loss single-mode. N.Shimizu, H.Tsuchiya and T.Izawa 28
Fibre connectors, multimode, fabricated with a self-aligning jig. M.Tachikura and I.Hatakeyama 34
Fibre connectors, wavelength-dependent transmission at. K.Petermann 706
Fibre, dispersion-free single-mode, in 1.5 μm wavelength region. H.Tsuchiya and N.Imoto 476
Fibre, graded-index, baseband-frequency-response measurement of, using step-index fibre as an exciter. T.Tanifuji, T.Horiguchi and M.Tokuda 203
Fibre, graded-index, propagation constants of guided modes in, with polynomial-profile core. H.Ikuno 762
Fibre, irradiated plastic-clad silica, signal-level dependence in the recovery rate of. J.G.Titchmarsh 111
Fibre-optic communication, low-loss 4 x 4 optical matrix switch for. Y Fujii, J.Minowa, T.Aoyama and K.Doi 427
Fibre-optic systems, long-wavelength, $In_{0.53}Ga_{0.47}As$ p-i-n photodiodes for. R.F.Leheny, R.E.Nahory and M.A.Pollack 713
Fibre transmission, detailed evaluation of an attainable repeater spacing for, at 1.3 μm and 1.55 μm wavelengths. K.Nakagawa and T.Ito 776
Fibre transmission experiments, dispersion-free single-mode, up to 1.6 Gbit/s. Jun-Ichi.Yamada, S.Machida, T.Kimura and H.Takata 278
Fibre transmission test, 800 Mb/s, using low-loss and low-dispersion single-mode cable. K.Nakagawa, Y.Hakamada and K-I.Suto 747
Fibre, ultimate low-loss single-mode, at 1.55 μm. T.Miya, Y.Terunuma, T.Hosaka and T.Miyashita 106
Fibre, ultra-low-loss single-mode, preparation of long lengths of. B.J.Ainslie, C.R.Day, P.W.France, K.J.Beales and G.R.Newns 411
Fibres, 1.3 μm single-mode, ceramic capillary connector for. N.Suzuki, Y.Iwahara, M.Saruwatari and K.Nawata 809
Fibres, $GeO_2-P_2O_5$-doped silica graded-index, spectral loss characteristics of, in long-wavelength band. T.Edahiro, M.Horiguchi, K.Chida and Y.Ohmori 274
Fibres, germanium borosilicate, optical transmission loss of, as a function of drawing conditions. D.H.Smithgall, M.A.Saifi and M.J.Andrejco 56
Fibres, graded-index, analytical relations between modal power distribution and near-field intensity in. S.Piazzola and G.De Marchis 721
Fibres, graded-index single-mode, zero total dispersion in. W.A.Gambling, H.Matsumara and C.M.Ragdale 474
Fibres, graded single-mode, dispersion in. A.W.Snyder and R.A.Sammut 269
Fibres, low-loss, for wavelengths beyond 1 μm. U.Zwick, W.Auer, I.Riegl, H.Haupt and W.Heitmann 159
Fibres, multimode graded-index, distortion of light signals transmitted via. K.Stubkjaer 797
Fibres, nonideal graded-index, bandwidth-limited operation of. L.Jeunhomme 149
Fibres, single-mode, dispersion minimisation in, between 1.3 μm and 1.7 μm. L.Jeunhomme 478
Fibres, single-mode, dispersion minimisation in, over a wide spectral range. K.Okamoto, T.Edahiro, A.Kawana and T.Miya 729
Fibres, single-mode, fabrication of, exhibiting extremely low polarisation birefringence. S.R.Norman, D.N.Payne, M.J.Adams and A.M.Smith 309
Fibres, single-mode step-index, minimum dispersion at 1.55 μm for. C.T.Chang 765
Fibres, single-mode, tailoring zero chromatic dispersion into the 1.5-1.6 μm low-loss spectral region of. L.G.Cohen, C.Lin and W.G.French 334
Fibres, single-mode, tee-coupler for. E.Weidal and D.Gruchmann 737
Fibres, step-index monomode, total dispersion in. C.R.South 394
Fibres, step-index monomode, zero total dispersion in, at 1.30 and 1.55 μm. K.I.White and B.P.Nelson 396
Fibres, v.a.d., phosphor-doped silica cladding. T.Edahiro, S.Sudo, M.Kawachi, K.Jinguji and N.Inagaki 726
Fibres, very low-loss single-mode, 1.5 m optical transmission experiments using. S.Machida, J.Yamada, T.Mukai, Y.Horikoshi, H.Tsuchiya and T.Miya 219
Field-effect device, amorphous-silicon, and possible application. P.G.Le Comber, W.E.Spear and A.Ghaith 179
Field measurement of splice loss applying the backscattering method. P.Matthijsse and C.M.De Blok 795
Field problems, unbounded, extension of finite-element method to. S.Washisu, I.Fukai and M.Suzuki 772
Fields, bandlimited, energy and power of, in lossless nonlinear media. P.Proksch 521
Filter, broadband resonant, using surface-shear-wave mode and twin-turn reflector. Y.Kinoshita, M.Hikita, T.Tabuchi and H.Kojima 130
Filter, c.c.d. adaptive, employing parallel coefficient updating. N.R.Massey, P.M.Grant and J.Mavor 573
Filter, c.c.d. transversal, with a three-level polysilicon structure. K.Tanikawa, Y.Ito, T.Yamamoto, S.Miura, Y.Miyamoto and S.Kato 311
Filter, compact high-performance c.c.d. adaptive, noise cancellation and inverse filtering using a. C.F.N.Cowan, J.Mavor and J.W.Arthur 35
Filter design, inductance simulation and, using a single-pole amplifier approximation, comment on. E.Sánchez-Sinencio and D.Báez-López 465
Filter design, roll-off shaping, for improving adaptive equalisation. K.Wesolowski 338
Filter, linear-phase digital anti-aliasing. S.E.Williamson, W.Matley and R.E.H.Bywater 539
Filter, linear-phase digital anti-aliasing, comment on. S.E.Williamson, W.Matley and R.E.H.Bywater 793
Filter, meander-channel c.c.d. (m.c.c.d.) recursive. Y.Miyamoto, K.Tanikawa, H.Sei and S.Kato 320
Filter, mode, single-mode propagation in 2-mode region of optical fibre by using. Y.Katsuyama 442
Filter:, nonreciprocal directional, a new multipurpose ferrite device. R.R.Bonetti 233
Filter, two-dimensional inverse, using floating-gate tapped c.c.d.s.. T.Enomoto, M.Yasumoto and K.Watanabe 280
Filtering out intersymbol interference of spread-spectrum communication systems. L.Alcuri, G.Mamola and E.Randazzo 397
Filters, adaptive, to improve loudspeaker telephone. C.R.South, C.E.Hoppitt and A.V.Lewis 673
Filters, c.c.d. transversal, integrated n.m.o.s. operational amplifier for. P.U.Calzolari, G.Masetti and M.Severi 29
Filters, c.c.d. transversal, new charge-differencing technique for. J.Fox and J.F.Dickson 229
Filters for data transmission with minimum intersymbol interference. B.M.Djurich and C.M.Zivaljevich 288
Filters, interference, multireflection optical multi/demultiplexer using. K.Nosu, H.Ishio and K.Hashimoto 414
Filters, minimum-phase charge-transfer transversal, design of. M.Feldmann, J.Henaff, B.Lacroix and J.C.Rebourg 226
Filters, more active RC, using the d.v.c.c.s./d.v.c.v.s.. I.M.Filanovsky and K.A.Stromsmoe 466
Filters, N-path, some comments on notch capability of. B.G.Pain 486
Filters, novel microwave integrated lowpass. G.D'Inzeo, F.Giannini and R.Sorrentino 258
Filters, optical frequency-selective, in ion-exchanged waveguides. A.Yi Yan and C.D.W.Wilkinson 240
Filters, practical aspects of, using amplifier poles, comment on. R.Schaumann, J.R.Brand and K.R.Laker 493
Filters, programmable c.c.d. recursive, coefficient correction in. T.G.Tang, Y.T.Yeow and J.Mavor 630
Filters, quasielliptic, characteristic function for. B.D.Rakovich and M.V.Popovich 292
Filters, sampled-data, simple implementation of, using current multipliers, switches, and capacitors. J.I.Arreola, Y.P.Tsividis, E.Sanchez-Sinencio and P.E.Allen 780
Filters, switched-capacitor, alternative approach to the design of. B.G.Pain 438
Filters, TE_{on}-mode, for the v.l.a. circular waveguide system. J.W.Archer 343
Filters, transitional Murromaf-Murroer. V.S.Stojanović and V.D.Pavlović 356
Fine tuning of s.a.w. resonators using argon ion bombardment. S.James and I.H.Wilson 683
Finite-element method, extension of, to unbounded field problems. S.Washisu, I.Fukai and M.Suzuki 772
Finite-element method, three-dimensional 'sandwich' transducer modelling by. H.Carru 805
Flip-chip mounted GaAs power f.e.t. with improved performance in X- to Ku-band. Y.Mitsui, M.Kobiki, M.Wataze, M.Otsubo, T.Ishii and S.Mitsui 461
Floating ideal inductor with one d.v.c.c.s.. D.Patranabis and A.N.Paul 545
Floating inductors, switched-capacitor, alternative realisations of. U.W.Brugger and B.J.Hosticka 698
Flow graph technique, voltage transfer function realisation using active R network:. S.Osowski 416
Flowmeter, optical-fibre. B.Culshaw and M.J.Hutchings 659
Form of Doppler processing for radars of random p.r.i. and r.f.. R.Benjamin 782
Fourier-series representation for phase density of sum of signal, noise and interference. I.M.Kostić 541 Errata 731
Fourier transform, discrete, of correlation functions. J.R.Jordan 196
Fourier transform, two-dimensional high-speed acoustic, of optical images. H.Gautier, P.Ledu and C.Maerfeld 177
Fourier transformer, fast s.a.w.-based discrete. J.B.G.Roberts, B.J.Darby, R.A.Bale and R.Eames Errata 262
Frequency doubler, accurate translinear sinusoidal,. A.Nedungadi 228
Frequency limitation of GaAs transferred-electron devices: influence of operating d.c. and r.f. field values. P.A.Rolland, E.Constant, G.Salmer and R.Fauquembergue 373
Frequency modulation, wideband, of frequency synthesisers. M.J.Underhill and R.I.H.Scott 393
Frequency multiplying, high-performance aperiodic. R.Konn and R.Genin 187
Frequency response, analytic expression for the, and bandwidth of a spherical random array, comment on. D.Yavuz 585
Frequency response and bandwidth of a spherical random array. D.Yavuz 314
Frequency response, improved high-, noninverting integrators with. W.Kellner 257
Frequency response measurement, multimode fibre baseband, with single frequency output extracted from modulated InGaAsP laser. S.Machida, N.Imoto and Y.Ohmori 607
Frequency synthesis, discrete, using an analogue r.o.m.. G.F.Manes and C.Atzeni 350
Frequency synthesiser, wide-range, split-loop method for, with good dynamic performance. M.J.Underhill and P.A.Jordan 391
Frequency synthesisers, wideband frequency modulation of. M.J.Underhill and R.I.H.Scott 393
Front ends for Doppler with-sense radar. K.Holford 75
Fundamental charge distributions for surface-wave interdigital transducer analysis. D.P.Morgan, B.Lewis and J.G.Metcalfe 583
Fusion splicing of optical fibres. G.K.Pacey and J.F.Dalgleish 32

G

$Ga_{1-x}In_xP_{1-y}As_y$, influence of central valley effective mass and alloy scattering on transient drift velocity in. M.A.Littlejohn, L.A.Arledge, T.H.Glisson and J.R.Hauser 586
GaAlAs laser, coherent pulse generation with a, by active modelocking. P-T.Ho 526

GaAs active-medium-propagation devices, reflection-mode amplifier utilising. P.L.Fleming and H.E.Carlson 787
GaAs, capped and uncapped, laser annealing of. S.S.Kular, B.J.Sealy, M.H.Badawi, K.G.Stephens, D.Sadana and G.R.Booker 413
GaAs, effects of ion implantation on deep levels in. T.R.Jervis, D.W.Woodard and L.F.Eastman 619
GaAs, effects of laser irradiation of, observed by d.l.t.s.. N.G.Emerson and B.J.Sealy 553
GaAs f.e.t. operation, pulsed, for high peak output powers. P.C.Wade, D.Rutkowski and I.Drukier 591
GaAs f.e.t. transimpedance front-end design for a wideband optical receiver. K.Ogawa and E.L.Chinnock 650
GaAs field-effect transistors, novel microwave. J.C.Vokes, B.T.Hughes, D.R.Wight, J.R.Dawsey and S.J.W.Shrubb 627
GaAs/GaAlAs injection lasers, channelled-substrate narrow-stripe, with extremely low threshold currents. P.A.Kirkby 824
GaAs-GaAlAs double heterojunction lasers, metalorganic c.v.d. growth of, having low interfacial recombination and low threshold current. E.J.Thrush, P.R.Selway and G.D.Henshall 156
GaAs heterojunction f.e.t. with epitaxial Ge gate. Jun.Anderson,W.T., J.E.Davey, A.Christou, M.L.Bark, K.J.Sleger and H.B.Dietrich 11
GaAs intrinsic avalanche response time, n-type, orientation dependance of. J.J.Berenz, J.Kinoshita, T.L.Hierl and C.A.Lee 150
GaAs, laser-annealing behaviour of, effect of Si_3N_4 encapsulation on the. M.H.Badawi, J.A.Akintunde, B.J.Sealy and K.G.Stephens 447
GaAs layers, preparation and properties of, for novel f.e.t. structures. R.J.M.Griffiths, I.D.Blenkinsop and D.R.Wight 629
GaAs m.e.s.f.e.t. prepared by organometallic chemical vapour deposition. H.Morkoc, J.Andrews and V.Aebi 105
GaAs m.e.s.f.e.t.s., substrate conduction in. P.G.Borden 307
GaAs m.e.s.f.e.t. structure, V.P.E., using oxygen injection during buffer layer growth. H.Bruch, L.Palm, F.Ponse and P.Balk 246
GaAs power m.e.s.f.e.t.s. with a graded recess structure. T.Furutsuka, A.Higashisaka, Y.Aono, Y.Takayama and F.Hasegawa 417
GaAs, surface stability of, during tin diffusion. B.Tuck and M.H.Badawi 604
GaAs, temperature dependence of impact ionisation rates in, between 20° and 200° C. F.Capasso, R.E.Nahory and M.A.Pollack 117 Errata 507
GaAs, vaporisation of, during laser annealing. M.H.Badawi, B.J.Sealy and K.G.Stephens 786
Gain expansion and intermodulation in a m.e.s.f.e.t. amplifier. C.Blanco 31
Gallium arsenide, changes in the thermal oxidation of, induced by ion implantation. D.N.Butcher and B.J.Sealy 51
Gallium phosphide, epitaxial, gettering of, using phosphosilicate glass. B.W.Wessels 748
Gallium phosphide, recombination in, via a deep state associated with nickel. A.R.Peaker, R.F.Brunwin, P.Jordan and B.Hamilton 663
General class of multisection quarter-wave transformers for impedance matching at microwave frequencies. P.A.Massaro and V.Picciarelli 222
General relations for nonperiodic bandlimited signals in three-dimensional electron flow. P.Proksch 328
Generalised correlation model for designing 2-dimensional image coders. W.Mauersberger 664
Generator, waveform, rotation of a. B.Z.Kaplan 158
Gettering of epitaxial gallium phosphide using phosphosilicate glass. B.W.Wessels 748
Grating coupler, stigmatically focusing. M.Miler and M.Skalsky 275
Groove-guide connection losses at 100 GHz. D.J.Harris and Y.M.Choi 687
Grounded inductors, insensitive grounded-capacitor simulation of, using current conveyors. R.Nandi 693
Gunn device, planar, high-bit-rate pulse regeneration and modulation of injection lasers with a. G.Deutsch, G.Lindner, K.Lübke and H.W.Thim 285
Gyrators, switched-capacitor simulation of floating inductors using. U.W.Brugger, B.J.Hosticka and G.S.Moschytz 494
Gyrotrons, circular cylindrical cavity, simple derivation of the expression for the synchronous field in. M.K.Haldar and A.H.Beck 487
Gyrotropic waveguide switching elements at optical wavelengths. P.Hlawiczka 109

H

Hall mobility, automatic electrochemical profiling of, in semiconductors. T.Ambridge and C.J.Allen 648
Hardware implementation of generalised Petri nets. M.Courvoisier and J.P.Seck 770
Harmonic generators, overlength-mode transferred-electron. A.M.Mazzone and H.D.Rees 813
Heterojunction devices, double-, short-wavelength AlGaAs, internal stress and degradation in. I.Ladany, T.R.Furman and D.P.Marinelli 342
Heterojunctions, n-GaAs/N-GaAlAs, microwave detection with. A.Lechner, M.Kneidinger, H.W.Thim, R.Kuch and J.Wernisch 254
Heterojunctions, n-n GaAs: (Ga, Al)As, rectification at. A.Chandra and L.F.Eastman 90 Errata 216
High-bit-rate pulse regeneration and modulation of injection lasers with a planar Gunn device. G.Deutsch, G.Lindner, K.Lübke and H.W.Thim 285
High-efficiency superluminescent diodes for optical-fibre transmission. M.-C.Amann and J.Boeck 41
High-gain 9.25 GHz silicon bipolar transistor power amplifier. Y.S.Wu, H.T.Yuan and W.R.Wisseman 86
High-gain GaAs avalanche photodiodes with proton-implanted guard ring. N.Susa, H.Kanbe, T.Nishioka and Y.Ohmachi 535
High-linearity multimode optical fibre sensor. T.J.Hall 405
High-performance aperiodic frequency multiplying. R.Konn and R.Genin 187
High-performance c.c.d. channel filter for a p.c.m. codec. T.Enomoto, T.Ishihara, M.Yasumoto and S.Shida 817
High-performance GaAs beam-lead mixer diodes for millimetre and submillimetre applications. J.A.Calviello, J.L.Wallace and P.R.Bie 509
High peripheral power density GaAs F.e.t. oscillator. J.S.Joshi and J.A.Turner 163
High-power 11 GHz GaAs hi-lo Impatt diodes with titanium Schottky barriers. J.R.Grierson, K.Cooper, P.A.Leigh, P.J.O'Sullivan and P.W.Huish 13
High-power pulsed GaAs double-drift hybrid-Read Impatt diodes for X-band. J.J.Berenz, J.Kinoshita, T.L.Hierl and F.B.Fank 277
High-resolution analysis of exponentially decaying transients for physics d.l.t.s. experiments. M.S.Hodgart 724
Higher-mode cutoff in elliptical dielectric waveguides. J.R.Cozens and R.B.Dyott 558
Higher output from Baritt diodes using ion implantation. B.M.Armstrong, R.A.Moore and J.Wakefield 153
Hole traps in n-InP by d.l.t.s. and transient capacitance techniques. A.N.M.M.Choudhury and P.N.Robson 247
Hologram, inline, digital processing technique for suppressing the interfering outputs in the image from an. K.H.S.Marie, J.C.Bennett and A.P.Anderson 241
Hybrid realisation of an adaptive filter for real-time noise-cancelling applications. T.Schwarz and D.Malah 671

I

Identification, initial state, transition matrices in multiple preset experiments and, of synchronous sequential machines. S.R.Das, P.Chao and Z.Chen 777
Image coders, designing 2-dimensional, generalised correlation model for. W.Mauersberger 664
Impact ionisation rates, temperature dependence of, in GaAs between 20° and 200° C. F.Capasso, R.E.Nahory and M.A.Pollack 117 Errata 507
Impatt designs, GaAs, comparison of, for 20 GHz. J.J.Berenz, M.Vichr and F.B.Fank 694
Impatt diodes, 80 GHz silicon diamond-heatsink. M.Ino, T.Makimura, T.Ishibashi and M.Ohmori 2
Impatt diodes, high-efficiency GaAs, compensation degradation mechanism for. J.G.Smith 74
Impatt diodes, high-power 11 GHz GaAs hi-lo, with titanium Schottky barriers. J.R.Grierson, K.Cooper, P.A.Leigh, P.J.O'Sullivan and P.W.Huish 13
Impatt diodes, high-power pulsed GaAs double-drift hybrid-Read, for X-band. J.J.Berenz, J.Kinoshita, T.L.Hierl and F.B.Fank 277
Impedance, exact surface, for a cylindrical conductor. J.R.Wait 659
Impedance, input, of thin dipoles by moment method. R.Neri 418
Impedance matching at microwave frequencies, general class of multisection quarter-wave transformers for. P.A.Massaro and V.Picciarelli 222
Improved algorithm for probe-corrected spherical near-field/far-field transformation. F.H.Larsen 588
Improved ohmic properties of Au-Ge contacts to thin n-GaAs layers alloyed with an SiO_2 overlayer. F.Vidimari 674
Improved theory for microstrip antennas. W.F.Richards, Y.T.Lo and D.D.Harrison 42
Improvement of intermodulation distortion in microwave m.e.s.f.e.t. amplifiers using gate-bias compensation. R.K.Gupta, P.A.Goud and C.G.Englefield 741
Improvements on a cryogenically cooled mixer for 80-120 GHz. R.W.Haas 115
$In_{0.53}Ga_{0.47}As$ p-i-n photodiodes for long-wavelength fibre-optic systems. R.F.Leheny, R.E.Nahory and M.A.Pollack 713
$In_{1-x}Ga_xAs_yP_{1-y}$ device-quality liquid-phase-epitaxial, evidence of trapping in. P.K.Bhattacharya, J.W.Ku, S.J.T.Owen, S.H.Chiao and R.Yeats 753
Incorporation of bromine into Si-SiO_2 interfaces and effects on interface state distributions. T.C.Poon and H.C.Card 756
Increase to inverse beta of Si transistors due to low-temperature treatments. M.Aceves and D.L.Kendall 282
Indium antimonide, alloyed planar diodes in. K.Riedling, F.Olcaytug and W.Fallmann 572
Indium phosphide, automatic electrochemical profiling of carrier concentration in. T.Ambridge and D.J.Ashen 647
Inductance realisation, low-sensitivity high-frequency, without capacitor. M.T.Ahmed and M.A.Siddiqui 260
Inductor, floating ideal, with one, d.v.c.c.s.. D.Patranabis and A.N.Paul 545
Inductor simulation, floating-, novel active RC circuit for. R.Senani 679
Inductors, floating, switched-capacitor simulation of, using gyrators. U.W.Brugger, B.J.Hosticka and G.S.Moschytz 494
Inductors, grounded, switched-capacitor simulation of, using operational-amplifier pole. E.Sánchez-Sinencio and J.L.Gómez-Oserio 169
Inductors, switched-capacitor floating, alternative realisations of. U.W.Brugger and B.J.Hosticka 698
Influence of central valley effective mass and alloy scattering on transient drift velocity in $Ga_{1-x}In_xP_{1-y}As_y$. M.A.Littlejohn, L.A.Arledge, T.H.Glisson and J.R.Hauser 586
Influence of waveguide effects on pulse-delay measurements of material dispersion in optical fibres. A.H.Hartog 632
Information retrieval in the presence of speckle and quantum noise. P.Mohana Shankar and H.M.Gupta 464
Infrared pedestrian data-acquisition system, novel computer-based. S.S.Mudaly 371
InGaAsP p-i-n photodiodes with low dark current and small capacitance. C.A.Burrus, A.G.Dentai and T.P.Lee 655
InGaP/InGaAs solar cell, low-bandgap (1.15 eV). R.R.Saxena and R.L.Moon 826
Injection lasers, channelled-substrate narrow-stripe GaAs/GaAlAs, with extremely low threshold currents. P.A.Kirkby 824
Injection priming of a pulsed molecular-beam maser oscillator. D.C.Lainé and A.M.Al-Jumaily 21
Injection transistor-transistor logic (i.t.t.l.). J.Furlan 223
InP/Al_2O_3 n-channel inversion-mode m.i.s.f.e.t.s. using sulphur-diffused source and drain. T.Kawakami and M.Okamura 502
InP-InGaAsP planar avalanche photodiodes with self-guard-ring effect. K.Taguchi, Y.Matsumoto and K.Nishida 453
InP, n-type, electron traps in, grown by the synthesis solute-diffusion method. K.Tsubaki, E.Kubota and K.Sugiyama 513
InP surface, semi-insulating, n-channel formation on, by m.i.s.f.e.t.. T.Kawakami and M.Okamura 743
Input impedance of thin dipoles by moment method. R.Neri 418
Insensitive grounded-capacitor simulation of grounded inductors using current conveyors. R.Nandi 693
Insulator m.o.s.f.e.t.s., silicon-on-, fabricated on laser-annealed polysilicon on SiO_2. A.F.Jun.Tasch, T.C.Holloway, K.F.Lee and J.F.Gibbons 435
Integer programming scheme, new, for nonrecursive digital filter design. L.Yong-Ching and A.G.Constantinides 812
Integrated bistable optical device using Mach-Zehnder interferometric optical waveguide. H.Ito, Y.Ogawa and H.Inaba 283

Integrated bistable optical multi-vibrator using electro-optically controlled directional coupler switches. H.Ito, Y.Ogawa, K.Makita and H.Inaba 791
Integrated-circuit fabrication flaw detected using the supply-current analysis technique. M.G.Rowlands 745
Integrated-circuit relay correlator for measurement-system applications. J.R.Jordan 366
Integrated n.m.o.s. operational amplifier for c.c.d. transversal filters. P.U.Calzolari, G.Masetti and M.Severi 29
Integrating-input technique for c.c.d.. C.J.Oliver, A.H.James, D.V.McCaughan, J.R.Hill and J.C.White 497
Integrators, noninverting, with improved high-frequency response. W.Kellner 257
Intensity, near-field, analytical relations between modal power distribution and, in graded-index fibres. S.Piazzola and G.De Marchis 721
Interfaces, Si-SiO_2, incorporation of bromine into, and effects on interface state distributions. T.C.Poon and H.C.Card 756
Interference, error performance of c.p.s.k. system in the presence of. S.G.Glišić 97
Interference, Fourier-series representation for phase density of sum of signal, noise and. I.M.Kostić 541 Errata 731
Interferences, two directional, optimal radiation pattern of an array in the presence of. P.C.K.Kwok and P.S.Brandon 251
Intermodulation distortion, improvement of, in microwave m.e.s.f.e.t. amplifiers using gate-bias compensation. R.K.Gupta, P.A.Goud and C.G.Englefield 741
Intermodulation improvement for multichannel television distribution by appropriate channel allocations and the use of 1/3rd line offsets. J.M.Griffiths 162
Internal stress and degradation in short-wavelength AlGaAs double-heterojunction devices. I.Ladany, T.R.Furman and D.P.Marinelli 342
Intersymbol interference, filtering out, in spread-spectrum communication systems. L.Alcuri, G.Mamola and E.Randazzo 397
Inverse Routh-Hurwitz array solution to the inverse stability problem. A.C.Tsoi 575
Ion bombardment, H_2^+ and D_2^+, changes in annealing behaviour of SiO_2 on Si resulting from. J.Belson and I.H.Wilson 420
Ion-exchanged waveguides, influence on index profile of, double-alkali effect:. V.Neuman, O.Parriaux and L.M.Walpita 704
Ion implantation, changes in the thermal oxidation of gallium arsenide induced by. D.N.Butcher and B.J.Sealy 51
Ion implantation, effects of, on deep levels in GaAs. T.R.Jervis, D.W.Woodard and L.F.Eastman 619
Ion implantation, higher output power from Baritt diodes using. B.M.Armstrong, R.A.Moore and J.Wakefield 153
Ion-implantation mask, properties of Se-Ge inorganic photoresist as an. A.Yoshikawa, T.Tamama, Y.Mizushima, K.Kudo and T.Shigematsu 499
Ion-implanted GaAs X-band power f.e.t.s.. F.H.Doerbeck, H.M.Macksey, G.E.Brehm and W.R.Frensley 576
Irradiation, tumour, feasibility of focused microwave array system for. A.P.Anderson, M.Melek and B.H.Brown 564

J

Jitter accumulation, simple formulas for, in a chain of regenerative repeaters in optical-fibre transmission systems. U.Mengali and G.Pirani 561
Jitter measurement technique, direct. P.Cochrane, I.W.Barley and J.J.O'Reilly 774
Joint parameter/state estimation. A.Jakeman and P.Young 582
Junction stripe lasers, twin-transverse-, effect of injection current on the dielectric constant of an inbuilt waveguide in. S.E.H.Turley, G.H.B.Thompson and D.F.Lovelace 256

K

Kalman filter, estimation of linearly constrained parameters via the. J.E.Hudson 319 Errata 478
Kalman filter, extended, model tuning using the. A.S.Morris and M.J.H.Sterling 201
Kalman filter, self-adaptive. P.Young 358
Ku- and K-band internally matched high-power GaAs f.e.t. amplifiers. J.Sone and Y.Takayama 562

L

L.E.D.S., InGaAsP/InP, modulation characteristics of, at 1.5 μm wavelength. S.Machida, H.Nagai and T.Kimura 175
L.E.D.S., Mg-doped InGaAsP/InP, for high-bit-rate optical-communication systems. H.Grothe, W.Proebster and W.Harth 702
L.P.E., low-threshold (Ga, In) (As, P) d.h. lasers emitting at 1.55 μm grown by. G.D.Henshall and P.D.Greene 621
Ladder filters, double-terminated LC, another method for the RC active simulation of. M.S.Piedade 571
Lange-coupler geometry, variation of, with dielectric constant. R.Horton 643
Langmuir-film, CdTe/, m.i.s. structures. M.C.Petty and G.G.Roberts 335
Large-bandwidth flat cylindrical array with circular polarisation and omnidirectional radiation. G.Dubost, J.Samson and R.Frin 102
Large-scale systems:, digraph analysis of, the system primitive. F.J.Evans and C.Schizas 613
Laser, 1.3 μm buried-stripe InGaAsP, modulation characteristics of, up to 2 Gbit/s data rates. Jun-ichi.Yamada, S.Machida, T.Mukai, H.Kano and K.Sugiyama 596
Laser-anneal technology, back-surface, silicon-on-sapphire m.o.s.f.e.t.s. fabricated by. S.Iwamatsu and M.Ogawa 827
Laser-annealing behaviour, effect of Si_3N_4 encapsulation on the, of GaAs. M.H.Badawi, J.A.Akintunde, B.J.Sealy and K.G.Stephens 447
Laser annealing of capped and uncapped GaAs. S.S.Kular, B.J.Sealy, M.H.Badawi, K.G.Stephens, D.Sadana and G.R.Booker 413
Laser annealing of m.o.s.-transistor channel implantations. G.Zimmer 184
Laser annealing, vaporisation of GaAs during. M.H.Badawi, B.J.Sealy and K.G.Stephens 786
Laser characteristics, InGaAsP double-heterostructure, temperature dependence of. R.E.Nahory, M.A.Pollock and J.C.DeWinter 695
Laser, CO_2, fabrication of channel optical waveguide using. H.Terui and M.Kobayashi 79
Laser diode, structure simplification of optical isolator coupled with. T.Matsumoto 625
Laser, GaAlAs, coherent pulse generation with a, by active modelocking. P-T.Ho 526
Laser, high-power c.w. Nd-y.a.g., 100 km optical-fibre transmission system at 1.32 μm using. S.Shimada, T.Matsumoto, T.Ito, S.Matsushita, K.Washio and K.Minemura 484
Laser irradiation, effects of, of GaAs observed by d.l.t.s.. N.G.Emerson and B.J.Sealy 553
Laser, modulated InGaAsP, multimode fibre baseband frequency response measurement with single frequency output extracted from. S.Machida, N.Imoto and Y.Ohmori 607
Laser, new diffusion-type stripe-geometry injection. P.Marschall, E.Schlosser and C.Wölk 38
Laser, new stripe-geometry, with simplified fabrication process. M-C.Amann 441
Laser, r.f. modulated AlGaAs d.h. diode, picosecond optical pulse generation from an. H.Ito, H.Yokoyama, S.Murata and H.Inaba 738
Laser, single-mode c.w. ridge-waveguide, emitting at 1.55 μm. I.P.Kaminow, R.E.Nahory, M.A.Pollack, L.W.Stulz and J.C.DeWinter 763
Laser, twin-transverse-junction stripe, with linear light/current characteristic and low threshold. G.H.B.Thompson, D.F.Lovelace and S.E.H.Turley 133
Lasers, d.h. GaAlAs, nonlinearity of. K.E.Stubkjr 61
Lasers, d.h. GaAlAs, simple system for broad-band single-mode tuning of. D.Renner and J.E.Carroll 73
Lasers emitting, low-threshold (Ga, In) (As, P) d.h., at 1.55 μm grown by l.p.e.. G.D.Henshall and P.D.Greene 621
Lasers, GaAs-(GaAl)As stripe, preliminary c.w. reliability measurements on, grown by metal-organic c.v.d.. E.J.Thrush and J.E.A.Whiteaway 666
Lasers, GaAs-GaAlAs double heterojunction, metalorganic c.v.d. growth of, having low interfacial recombination and low threshold current. E.J.Thrush, P.R.Selway and G.D.Henshall 156
Lasers, GaInAsP/InP d.h., direct modulation characteristics of, with various stripe widths measured by sharp-pulse method. Y.Sakakibara, K.Furuya, Y.Suematsu and Y.Itaya 594
Lasers, InGaAsP/InP heterostructure, room temperature c.w. operation of, emitting at 1.56 μm. S.Akiba, K.Sakai, Y.Matsushima and T.Yamamoto 606
Lasers, injection, high-bit-rate pulse regeneration and modulation of, with a planar Gunn device. G.Deutsch, G.Lindner, K.Lübke and H.W.Thim 285
Lasers, InP/InGaAsP/InP double heterostructure diode, room-temperature c.w. operation of, emitting at 1.55 μm. H.Kawaguchi, K.Takahei, Y.Toyoshima, H.Nagai and G.Iwane 669
Lasers, low-threshold GaInAsP/InP double-heterostructure, narrow-beam divergence of the emission from. Y.Itaya, S.Katayama and Y.Suematsu 123
Lasers, mesa-substrate buried-heterostructure GaInAsP/InP injection. K.Kishino, Y.Suematsu and Y.Itaya 134
Lattice filters, adaptive, convergence of. T.S.Durrani and N.L.M.Murukutla 833
Lattices, adaptive, recursive algorithm for. T.S.Durrani and N.L.M.Murukutla 831
Least-squares problem, double-sided. K.V.M.Fernando and H.Nicholson 624
Lens-type compact antenna range. A.D.Olver and A.A.Saleeb 409
Libido using Eros: halfduplex optical link. L.d'Auria, G.Chevalier and P.Maillot 820
Light-emitting diode, small-area GaAs-GaAlAs heterostructure, with improved current confinement. M.-C.Amann and W.Proebster 599
Light-induced effects in GaAs f.e.t.s.. J.Graffeuil, P.Rossel and H.Martinot 439
Light signals, distortion of, transmitted via multimode graded-index fibres. K.Stubkjaer 797
Linear discrete systems, stochastic, optimal input for, as a function of input and output variables. C.S.Berger 360
Linear estimation, recursive, of linearly constrained parameters. J.P.Norton 715
Linear-phase digital anti-aliasing filter. S.E.Williamson, W.Matley and R.E.H.Bywater 539
Linear-phase digital anti-aliasing filter, comment on. S.E.Williamson, W.Matley and R.E.H.Bywater 793
Linear single-input system, design of optimal controller for. LimChoo.Mim and B.S.Habibullah 660
Linear stationary systems, evaluation of the transient response of, to a class of excitations. M.M.Milić and M.V.Gmitrović 614
Linearly constrained parameters, recursive linear estimation of. J.P.Norton 715
Liquid-crystal light deflector. A.Sasaki and T.Ishibashi 293
Logic circuits, multistage GaAs m.e.s.f.e.t. combinational, propagation delay optimisation in, by use of dynamic programming. A.Barna 147
Long backfire antenna with insular image guide feed for dual frequency operation. R.N.Simons and D.T.Shahani 78
Loss change, optical, caused by hydraulic pressure in multimode optical fibres. M.Kawase, K.Yamashita, M.Nishimura, T.Yamanishi and Y.Sugawara 208
Loss, optical transmission, of germanium borosilicate fibres as a function of drawing conditions. D.H.Smithgall, M.A.Saifi and M.J.Andrejco 56
Loss, splice, field measurement of, applying the backscattering method. P.Matthijsse and C.M.De Blok 795
Love waves, magnetoelastic, amplification of, by interaction with carrier waves in a layered composite. Y.Ikuzawa, N.S.Chang and Y.Matsuo 17
Low-bandgap (1.15 eV) InGaP/InGaAs solar cell. R.R.Saxena and R.L.Moon 826
Low-barrier-height epitaxial Ge-GaAs mixer diodes. A.Christou, J.E.Davey and Y.Anand 324
Low-cost analogue voltage-voltage convertors with arbitrary transfer characteristics. S.Suzuki, S.Shinmyo and J.Sasaki 170
Low-loss 4 x 4 optical matrix switch for fibre-optic communication. Y Fujii, J.Minowa, T.Aoyama and K.Doi 427
Low-loss fibres for wavelengths beyond 1 μm. U.Zwick, W.Auer, I.Riegl, H.Haupt and W.Heitmann 159
Low-loss high-numerical-aperture optical fibre fabricated by v.a.d. method. N.Shibata, M.Kawachi, S.Sudo and T.Edahiro 680
Low-loss optical-fibre connection systems. G.Le Noane 12
Low-loss optical Y-branch. D.Opielka and D.Rittich 757
Low-loss single-mode fibre connectors. N.Shimizu, H.Tsuchiya and T.Izawa 28
Low-noise microwave f.e.t.s fabricated by molecular-beam epitaxy. S.G.Bandy, D.M.Collins and C.K.Nishimoto 218
Low-noise multistage avalanche photodetector. J.P.Gordon, R.E.Nahory, M.A.Pollack and J.M.Worlock 518
Low-noise optical detection of a 1.1 Gb/s optical data stream. S.M.Abbott and W.M.Muska 250

Low-sensitivity high-frequency inductance realisation without capacitor. M.T.Ahmed and M.A.Siddiqui 260
Low-threshold (Ga, In) (As, P) d.h. lasers emitting at 1.55 μm grown by l.p.e.. G.D.Henshall and P.D.Greene 621
Low-to-high voltage-level shifter and waveform synthesiser. C.J.Georgopoulos 178

M

M.E.S.F.E.T. amplifier, gain expansion and intermodulation in a. C.Blanco 31
M.E.S.F.E.T. amplifiers, microwave, improvement of intermodulation distortion in, using gate-bias compensation. R.K.Gupta, P.A.Goud and C.G.Englefield 741
M.E.S.F.E.T. combinational logic circuits, multistage GaAs, propagation delay optimisation in, by use of dynamic programming. A.Barna 147
M.E.S.F.E.T. drain mixers, conversion gain of. G.Begemann and A.Jacob 567
M.E.S.F.E.T. dual-gate, self-oscillating X-band mixers. R.Stahlmann, C.Tsironis, F.Ponse and H.Beneking 524
M.E.S.F.E.T. output nonlinearity, modelling the. R.A.Minasian 515
M.E.S.F.E.T.S., GaAs power, with a graded recess structure. T.Furutsuka, A.Higashisaka, Y.Aono, Y.Takayama and F.Hasegawa 417
M.E.S.F.E.T.S., GaAs, substrate conduction in. P.G.Borden 307
M.E.S.F.E.T.S., submicrometre-gate-length, mobility, transit-time and transconductance in. J.Frey and T.Wada 26
M.E.S.F.E.T., V.P.E. GaAs, structure using oxygen injection during buffer layer growth. H.Bruch, L.Palm, F.Ponse and P.Balk 246
M.I.S.F.E.T., n-channel enhancement-mode InP, microwave gain from an. L.G.Meiners, D.L.Lile and D.A.Collins 578
M.I.S.F.E.T., n-channel formation on semi-insulating InP surface by. T.Kawakami and M.Okamura 743
M.I.S.F.E.T.S., InP/Al_2O_3 n-channel inversion-mode, using sulphur-diffused source and drain. T.Kawakami and M.Okamura 502
M.O.S.F.E.T.S., depletion-type, for low-temperature operation. M.Kawashima, M.Kanamori and M.Matsumura 759
M.O.S.F.E.T.S., silicon-on-insulator, fabricated on laser-annealed polysilicon on SiO_2. A.F.Jun.Tasch, T.C.Holloway, K.F.Lee and J.F.Gibbons 435
M.O.S.F.E.T.S., silicon-on-sapphire, fabricated by back-surface laser-anneal technology. S.Iwamatsu and M.Ogawa 827
M.O.S. neural pulse modulator. Z.Czarnul, G.Kiruthi and R.W.Newcomb 823
M.O.S. oxides, effect of ionising radiation on mobile-ion density in. T.N.Bhar, R.Dat, R.Y.Koyama and K.F.Galloway 16
M.O.S. switched-capacitor amplifiers. T.R.Viswanathan, S.M.Faruque, K.Singhal and J.Vlach 634
M.O.S.-transistor channel implantations, laser annealing of. G.Zimmer 184
m-sequences, code modulation of. K.W.Yates and D.J.Holgate 836
Magnetic field distributions, microwave, new resonant scatterer for measuring. M.Galka 243
Magnetic thin films, layered, directional coupling of magnetostatic surface waves in. H.Sasaki and N.Mikoshiba 172
Magnetoelastic Love waves, amplification of, by interaction with carrier waves in a layered composite. Y.Ikuzawa, N.S.Chang and Y.Matsuo 17
Magnetostatic surface waves, directional coupling of, in layered magnetic thin films. H.Sasaki and N.Mikoshiba 172
Mapping of the near-field pattern in simulated biological tissues. G.Gajda, M.A.Stuchly and S.S.Stuchly 120
Maser oscillator, pulsed molecular-beam, injection priming of a. D.C.Lainé and A.M.Al-Jumaily 21
Mask, ion-implantation, properties of Se-Ge inorganic photoresist as an. A.Yoshikawa, T.Tamama, Y.Mizushima, K.Kudo and T.Shigematsu 499
Meander-channel c.c.d. (m.c.c.d.) recursive filter. Y.Miyamoto, K.Tanikawa, H.Sei and S.Kato 320
Measurement and simulation of satellite systems single-channel-per-carrier frequency-modulation spectra. B.G.Evans, H.Ganem and J.Dutronc 194
Measurement arrangement for direct capacitance/surface-potential recording on m.o.s. capacitor. H.C.G.Ligtenberg and J.Snijder 523
Measurement of frequency dependence of Rayleigh backscattering in bidirectional optical systems. J.Straus, I.S.Few and J.Conradi 306
Measurement of p.c.m. regenerator crosstalk performance. A.J.Gibbs 82
Measurement of refractive-index profile of optical-fibre preform. P.L.Chu and T.Whitbread 295
Measurement of the extinction cross-sections of dry and wet ice spheres at 35 GHz. D.L.Bryant and L.J.Auchterlonie 52
Measurement-system applications, integrated-circuit relay correlator for. J.R.Jordan 366
Measurements performed on l.e.d. 4-level digital optical-fibre system for 68 Mbit/s. M.Rocks 676
Memories, monolithic, optimal radix for. E.Seevinck 736
Mesa-substrate buried-heterostructure GaInAsP/InP injection lasers. K.Kishino, Y.Suematsu and Y.Itaya 134
Metalorganic c.v.d. growth of GaAs-GaAlAs double heterojunction lasers having low interfacial recombination and low threshold current. E.J.Thrush, P.R.Selway and G.D.Henshall 156
Method for designing recursive digital filters with short wordlength. H-K.Kwan 128
Errata 361
Method of bandwidth extension for the Ruthroff transformer. R.T.Irish 790
Method of calculating the modal delay for optical fibres with arbitrary refractive-index profiles. D.H.Irving and A.E.Karbowiak 160
Mg-doped InGaAsP/InP l.e.d.s. for high-bit-rate optical-communication systems. H.Grothe, W.Proebster and W.Harth 702
Microelectrodes for contacting semiconductor devices. M.V.Schneider and H.Berger 450
Microscope, photoacoustic. M.Luukkala and A.Penttinen 325
Microstrip antenna elements, modified circular. J.McIlvenna and N.Kernweis 207
Microstrip antennas, improved theory for. W.F.Richards, Y.T.Lo and D.D.Harrison 42
Microstrip antennas, wide bandwidth, for circuit integration. P.S.Hall, C.Wood and C.Garrett 458
Microstrip, capacitance of a, of unequal widths in a homogeneous medium. R.K.L.Poon 44
Microstrip transmission lines, extending the low-frequency range of GaAs f.e.t. broadband microwave amplifiers using. C.M.Krowne 197
Microwave amplifiers, GaAs f.e.t. broadband, extending the low-frequency range of, using microstrip transmission lines. C.M.Krowne 197
Microwave array system, focused, feasibility of, for tumour irradiation. A.P.Anderson, M.Melek and B.H.Brown 564
Microwave detection with n-GaAs/N-GaAlAs heterojunctions. A.Lechner, M.Kneidinger, H.W.Thim, R.Kuch and J.Wernisch 254
Microwave gain from an n-channel enhancement-mode InP m.i.s.f.e.t.. L.G.Meiners, D.L.Lile and D.A.Collins 578
Microwave integrated circuits, monolithic GaAs, periodic slow-wave low-loss structures for. E.M.Bastida and G.P.Donzelli 581
Microwave magnetic field distributions, new resonant scatterer for measuring. M.Galka 243
Microwave mobile radiotelephone communications, 800 MHz, user density for. D.R.Conn and R.Maciejko 516
Microwave, novel, integrated lowpass filters. G.D'Inzeo, F.Giannini and R.Sorrentino 258
Microwave receiver, arbitrary polarisation, applied to OTS reception. A.P.Alves and N.J.McEwan 657
Microwaves, effects of drop size and temperature on forward and backward scattering of, by raindrops. S.A.J.Upton, B.G.Evans and A.R.Holt 760
Millimetre-wave phase modulators with lumped-element circuitry. E.Kpodzo, G.Begemann and K.Schünemann 48
Milliwave Fabry-Perot tuning and modulation by electrically variable external reactance. A.Godone, E.Bava and A.De Marchi 370
Miniaturised, hybrid, 500 Mb/s optical receiver package for data-link applications. T.N.C.Venkatesan and K.Ogawa 171
Minimisation of incompletely specified sequential machines: the 'really' excluded compatibility classes. G.Palama and G.V.Russo 690
Minimisation of modal noise in optical-fibre connectors. B.Culshaw 529
Minimum dispersion at 1.55 μm for single-mode step-index fibres. C.T.Chang 765
Minority-carrier traps, detection of, using transient spectroscopy. R.Brunwin, B.Hamilton, P.Jordan and A.R.Peaker 349
Mixed time/frequency domain approach to model reduction. S.J.Varoufakis and P.N.Paraskevopoulos 789
Mixer, cryogenically cooled, improvements on a, for 80-120 GHz. R.W.Haas 115
Mixer diodes, high-performance GaAs beam-lead, for millimetre and submillimetre applications. J.A.Calviello, J.L.Wallace and P.R.Bie 509
Mixer diodes, low-barrier-height epitaxial Ge-GaAs. A.Christou, J.E.Davey and Y.Anand 324
Mixers, dual-gate m.e.s.f.e.t. self-oscillating X-band. R.Stahlmann, C.Tsironis, F.Ponse and H.Beneking 524
Mobile-radio data links, diversity reception for error-rate reduction in. J.D.Parsons and A.Pongsupaht 202
Mobile radio synthesisers, land, 800 MHz v.c.o. for. M.Makimoto, K.Nakabe and S.Nishiki 460
Mobile radiotelephone communications, 800 MHz microwave, user density for. D.R.Conn and R.Maciejko 516
Mobility, transit time and transconductance in submicrometre-gate-length m.e.s.f.e.t.s.. J.Frey and T.Wada 26
Modal dispersion of optical fibres with a composite α-profile graded-index core. A.Weierholt 733
Modal noise, analysis and measurement of, in an optical fibre. B.Daino, G.De Marchis and S.Piazzolla 755
Modal power distribution, analytical relations between, and near-field intensity in graded-index fibres. S.Piazzola and G.De Marchis 721
Mode dispersion, analysis of approximations for the, in monomode fibres. R.A.Sammut 590
Mode dispersion of trapezoidal cross-section dielectric optical waveguides by the effective-index method. J.G.Gallagher 734
Model reduction, mixed time/frequency domain approach to. S.J.Varoufakis and P.N.Paraskevopoulos 789
Model tuning using the extended Kalman filter. A.S.Morris and M.J.H.Sterling 201
Modelling the m.e.s.f.e.t. output nonlinearity. R.A.Minasian 515
Modes, HE_{21}-, TE_{01}- and TM_{01}-, novel method for measuring cutoff wavelength of. Y.Kato, K-I.Kitayama, S.Seikai and N.Uchida 410
Modified circular microstrip antenna elements. J.McIlvenna and N.Kernweis 207
Modulation characteristics, direct, of GaInAsP/InP d.h. lasers with various stripe widths measured by sharp-pulse method. Y.Sakakibara, K.Furuya, Y.Suematsu and Y.Itaya 594
Modulation characteristics of 1.3 μm buried-stripe InGaAsP laser up to 2 Gbit/s data rates. Jun-ichi.Yamada, S.Machida, T.Mukai, H.Kano and K.Sugiyama 596
Modulation characteristics of InGaAsP/InP l.e.d.s. at 1.5 μm wavelength. S.Machida, H.Nagai and T.Kimura 175
Modulation, milliwave Fabry-Perot tuning and, by electrically variable external reactance. A.Godone, E.Bava and A.De Marchi 370
Modulation transfer function for the acoustic microscope. A.Atalar 321
Modulator, complex internal-reflection (c.i.r.) light, configurations for the. T.W.Cole 217
Modulators, millimetre-wave phase, with lumped-element circuitry. E.Kpodzo, G.Begemann and K.Schünemann 48
Modulators, video, correlation technique for improved isolation of overlapping spectra in. A.J.Clapton 429
Modulo-N counter technique for the u.h.f. band. J.B.Hughes, E.S.Eilley and G.J.Glynn 640
Molecular-beam epitaxy, low noise microwave f.e.t.s fabricated by. S.G.Bandy, D.M.Collins and C.K.Nishimoto 218
Monolithic 256-point programmable transversal filter. P.B.Denyer and J.Mavor 710
Monolithic GaAs microwave integrated circuits, periodic slow-wave low-loss structures for. E.M.Bastida and G.P.Donzelli 581
Monomode fibres, analysis of approximations for the mode dispersion in. R.A.Sammut 590
Monopole, effect of finite size of ground plane on the impedance of a, immersed in a lossy medium. I.J.Bahl and S.S.Stuchly 728
More active RC filters using the d.v.c.c.s./d.v.c.v.s.. I.M.Filanovsky and K.A.Strömsmoe 466
Moulded optical-fibre connectors using rods and balls. H.Murata 369
Multi/demultiplexer, multireflection optical, using interference filters. K.Nosu, H.Ishio and K.Hashimoto 414
Multi-vibrator, integrated bistable optical, using electro-optically controlled directional coupler switches. H.Ito, Y.Ogawa, K.Makita and H.Inaba 791

Multidimensional fast-Fourier-transform algorithm. B.Arambepola and P.J.W.Rayner 382
Multilevel code for high information rates. D.Munoz-Rodriguez 272
Multimode fibre baseband frequency response measurement with single frequency output extracted from modulated InGaAsP laser. S.Machida, N.Imoto and Y.Ohmori 607
Multimode fibre connectors fabricated with a self-aligning jig. M.Tachikura and I.Hatakeyama 34
Multipass processes, differential, asymptotic stability of. D.H.Owens 446
Multipath propagation in line-of-sight links. L.Boithias 209
Multiplier circuit, Dolph-Chebyshev data-window, quantising error in a. M.Trivedi and K.V.Lever 136
Multiposition optical-fibre switch. W.J.Tomlinson, R.E.Wagner, A.R.Strnad and F.A.Dunn 192
Multireflection optical multi/demultiplexer using interference filters. K.Nosu, H.Ishio and K.Hashimoto 414
Multistrip coupler performance for surface-skimming bulk waves on lithium tantalate. E.G.S.Paige and P.Whittle 374
Multivariable feedback systems, nonlinear, boundedness properties of. D.P.Atherton and D.H.Owens 559
Multivariable systems, nonlinear, boundedness properties of. S.Mossaheb 803

N

n-channel formation of semi-insulating InP surface by m.i.s.f.e.t.. T.Kawakami and M.Okamura 743
n-GaAs layers, thin, improved ohmic properties of Au-Ge contacts to, alloyed with an SiO_2 overlayer. F.Vidimari 674
n-GaAs, ultra low resistance ohmic contacts to. R.Stall, C.E.C.Wood, K.Board and L.F.Eastman 800
Narrow-beam divergence of the emission from low-threshold GaInAsP/InP double-heterostructure lasers. Y.Itaya, S.Katayama and Y.Suematsu 123
Near-field/far-field transformation, probe-corrected spherical, improved algorithm for. F.H.Larsen 588
Network analyser, dual 6-port, explicit solution of calibration equations for a. D.Woods 718
Network condition for counter-clockwise reflection-coefficient behaviour: application to oscillators. C.M.Krowne 114
Network, new equal-valued earthed-capacitor notch, using d.v.c.c.s./d.v.c.v.s.. R.Nandi 667
Network optimisation, ladder-, recursive formulae for. E.Olcayto 249
Neural pulse modulator, m.o.s.. Z.Czarnul, G.Kiruthi and R.W.Newcomb 823
New adaptive equaliser with infinite impulse response. Y.T.Jin 557
New approach to discrete phase-locked loop based on digital measurement of time intervals. D.Perisic 445
New automatic-gain-control system for optical receivers. M.Eve and D.W.Smith 146
New canonic single-resistance-controlled sinusoidal oscillator using a single current conveyor. R.Senani 568
New charge-differencing technique for c.c.d. transversal filters. J.Fox and J.F.Dickson 229
New diffusion-type stripe-geometry injection laser. P.Marschall, E.Schlosser and C.Wölk 38
New electrostatic probe for absolute measurement of amplitude of surface acoustic wave. J.B.Moreau, R.Hashim and J.C.Neau 155
New equal-valued earthed-capacitor notch network using d.v.c.c.s./d.v.c.v.s.. R.Nandi 667
New integer programming scheme for nonrecursive digital filter design. L.Yong-Ching and A.G.Constantinides 812
New representation for the current in a horizontal wire above ground. M.P.Carpentier and A.F.Dos Santos 554
New resonant scatterer for measuring microwave magnetic field distributions. M.Galka 243
New rigorous analysis of the step discontinuity in a slab dielectric waveguide. Ph.Gelin, M.Petenzi and J.Citerne 355
New s.a.w. time-inversion system. H.Messer, Y.Bar-Ness and H.Gilboa 214
New semiconductor active device: the conductivity-controlled transistor. A.Caruso, P.Spirito and G.Vitale 267
New stripe-geometry laser with simplified fabrication process. M-C.Amann 441
Noise, 1/f phase, in quartz s.a.w. devices. T.E.Parker 296
Noise and interference, sum of signal, Fourier-series representation for phase density of. I.M.Kostić 541 Errata 731
Noise cancellation and inverse filtering using a compact high-performance c.c.d. adaptive filter. C.F.N.Cowan, J.Mavor and J.W.Arthur 35
Noise-cancelling applications, real-time, hybrid realisation of an adaptive filter for. T.Schwarz and D.Malah 671
Noise, collector-base junction burst, evidence of. K.F.Knott 198
Noise covariance matrix, eigenvalues of, of linear array in the presence of two directional interferences. P.C.K.Kwok and P.S.Brandon 50
Noise, fixed-pattern, adaptive cancellation of, in c.c.d. serial-parallel-serial memory. R.C.Geddes, C.F.N.Cowan, J.Mavor and J.F.Dickson 505
Noise, low-frequency, effects of emitter edge dislocations on the, of silicon planar n-p-n transistors. N.D.Stojadinović 340
Noise, modal, analysis and measurement of, in an optical fibre. B.Daino, G.De Marchis and S.Piazzolla 755
Noise, optimal estimation of a common phase difference between pairs of fluctuating signals in. R.Voles 145
Noise relations of inverse active networks and complementary networks. M.Nomair, Y.Z.Bahnas and A.M.Soliman 18
Noise, speckle and quantum, information retrieval in the presence of. P.Mohana Shankar and H.M.Gupta 464
Noise, variance, and temperature fluctuations in semiconductors. S.Rahal and A.Chovet 271
Nondestructive determination of refractive-index profile and cross-sectional geometry of optical-fibre preform. P.L.Chu and C.Saekeang 635
Nondestructive refractive-index profile measurement of elliptical optical fibre or preform. P.L.Chu 357
Noninteger sampling to subcarrier frequency ratios in d.p.c.m. of Pal signals. H.Gharavi and R.Steele 483
Noninverting integrators with improved high-frequency response. W.Kellner 257
Nonlinear circuit analysis through periodic spline approximation. F.Filicori, M.R.Scalas and C.Naldi 597
Nonlinear modelling of f.e.t.-input operational amplifiers. P Bowron and A.Mohamed 473
Nonlinearity of d.h. GaAlAs lasers. K.E.Stubkjr 61
Nonreciprocal directional filter: a new multi-purpose ferrite device. R.R.Bonetti 233
Novel active RC circuit for floating-inductor simulation. R.Senani 679
Novel beam-to-waveguide coupler for $LiNbO_3$ optical waveguides. J.Ctyroký, M.Cada, N.M.Lyndin, V.A.Sychugov and J.Schroefel 519
Novel capacitor floatation scheme. D.Patranabis and A.N.Paul 688
Novel computer-based infrared pedestrian data-acquisition system. S.S.Mudaly 371
Novel dynamic c.m.o.s. amplifier for switched-capacitor integrators. B.J.Hosticka 532
Novel g.i.c. suitable for RC active-filter applications. M.K.N.Rao, J.W.Haslett and L.T.Bruton 462
Novel method for measuring cutoff wavelength of HE_{21}-, TE_{01}-and TM_{01}- modes. Y.Kato, K-I.Kitayama, S.Seikai and N.Uchida 410
Novel microwave GaAs field-effect transistors. J.C.Vokes, B.T.Hughes, D.R.Wight, J.R.Dawsey and S.J.W.Shrubb 627
Novel microwave integrated lowpass filters. G.D'Inzeo, F.Giannini and R.Sorrentino 258
Novel technique for eliminating the ambiguity in p.s.k. signal detection. A.Pongsupaht and J.D.Parsons 385
Numerical analysis of forward-biased diode structures based on direct-gap semiconductors. E.Velmre and B.Freidin 383
Numerical evaluation of phase centres of corner reflector antennas. Y.H.Ja 1
Numerically reliable algorithm to test controllability. A.Varga 452

O

Observers, rapidly converging, involve high-order differentiations. M.Zeitz 708
OH-ion reduction in v.a.d. optical fibres. T.Edahiro, M.Kawachi, S.Sudo and H.Takata 482
Ohmic contacts, ultra low resistance, to n-GaAs. R.Stall, C.E.C.Wood, K.Board and L.F.Eastman 800
Omnidirectional s.h.f. antenna consisting of horn radiators and plane reflectors. H.Thielen 639
On-resistance of V-v.m.o.s. power transistors. W.A.Lane, C.A.T.Salama and S.Dmitrevsky 601
One-step N-user programmable arbiter (Arbitre N-utilisateurs, une ressource, programmable). M.Courvoisier 430
Open-circuit to short-circuit switching: method for lifetime measurement in solar cells. S.R.Dhariwal, N.Basu and R.Gadre 456
Operational amplifier compensation pole:, simulation of inductors and capacitors using, a caution. S.Srinivasan and K.Radhakrishna Rao 472
Operational-amplifier convertor technique, universal, using supply-current sensing. B.L.Hart and R.W.J.Barker 496
Operational-amplifier pole, switched-capacitor simulation of grounded inductors using. E.Sánchez-Sinencio and J.L.Gómez-Oserio 169
Operational amplifiers, f.e.t.-input, nonlinear modelling of. P Bowron and A.Mohamed 473
Operational amplifiers, two, rational admittance function realisation using. S.Osowski 85
Optical circulator, simple polarisation-independent, for optical transmission systems. H.Iwamura, H.Iwasaki, K.Kubodera, Y.Torii and J.Noda 830
Optical-communication systems, high-bit-rate, Mg-doped InGaAsP/InP l.e.d.s. for. H.Grothe, W.Proebster and W.Harth 702
Optical data stream, 1.1 Gb/s, low-noise optical detection of a. S.M.Abbott and W.M.Muska 250
Optical detection, low-noise, of a 1.1 Gb/s optical data stream. S.M.Abbott and W.M.Muska 250
Optical fibre, analysis and measurement of modal noise in an. B.Daino, G.De Marchis and S.Piazzolla 755
Optical-fibre connection systems, low-loss. G.Le Noane 12
Optical-fibre connectors, minimisation of modal noise in. B.Culshaw 529
Optical-fibre connectors, moulded, using rods and balls. H.Murata 369
Optical fibre, elliptical, nondestructive refractive-index profile measurement of, or preform. P.L.Chu 357
Optical-fibre flowmeter. B.Culshaw and M.J.Hutchings 659
Optical fibre, graded-index, relation between splice loss and mode conversion in a. N.Kashima and N.Uchida 336
Optical fibre, low-loss high-numerical-aperture, fabricated by v.a.d. method. N.Shibata, M.Kawachi, S.Sudo and T.Edahiro 680
Optical-fibre network system for air-pollution monitoring over a wide area by optical absorption method. H.Inaba, T.Kobayasi, M.Hirama and M.Hamza 749
Optical fibre, plastic, with improved transmittance. S.Oikawa, M.Fujiki and Y.Katayama 829
Optical-fibre preform, measurement of refractive-index profile of. P.L.Chu and T.Whitbread 295
Optical-fibre preform, nondestructive determination of refractive-index profile and cross-sectional geometry of. P.L.Chu and C.Saekeang 635
Optical fibre, quantitative estimations of mode-coupling mechanisms in an. K.Tatekura, K.Itoh and T.Matsumoto 9
Optical fibre sensor, high-linearity multimode. T.J.Hall 405
Optical fibre, single-mode propagation in 2-mode region of, by using mode filter. Y.Katsuyama 442
Optical fibre, single-mode, suitable parameters of. Y.Katsuyama, Y.Ishida, K.Ishihara and T.Miyashita 94
Optical-fibre switch, multiposition. W.J.Tomlinson, R.E.Wagner, A.R.Strnad and F.A.Dunn 192
Optical-fibre system, l.e.d. 4-level digital, measurements performed on, for 68 Mbit/s. M.Rocks 676
Optical-fibre tap with low insertion loss. F.R.Gfeller and U.Bapst 448
Optical-fibre transfer functions, simplified procedure for indirect tests of. G.Cancellieri, M.Mezzetti, C.G.Someda and M.Zoboli 234
Optical-fibre transmission, high-efficiency superluminescent diodes for. M.-C.Amann and J.Boeck 41
Optical-fibre transmission system, 100 km, at 1.32 μm using high-power c.w. Nd-y.a.g. laser. S.Shimada, T.Matsumoto, T.Ito, S.Matsushita, K.Washio and K.Minemura 484
Optical-fibre transmission systems, simple formulas for jitter accumulation in a chain of regenerative repeaters in. U.Mengali and G.Pirani 561

Optical-fibre waveguides, preservation of polarisation in, with elliptical cores. R.B.Dyott, J.R.Cozens and D.G.Morris 380
Optical fibres:, backscattering measurements in, separation of power decay from imperfection contribution. P.Di Vita and U.Rossi 467
Optical fibres, birefringence in, with elliptical cross-section. M.J.Adams, D.N.Payne and C.M.Ragdale 298
Optical fibres, ceramic capillary splices for. K.Nawata, Y.Iwahara and N.Suzuki 470
Optical fibres, elliptically deformed, birefringence in. J.D.Love, R.A.Sammut and A.W.Snyder 615
Optical fibres, fusion splicing of. G.K.Pacey and J.F.Dalgleish 32
Optical fibres, graded-index, compensation of profile dispersion in. S.Geckeler 682
Optical fibres, influence of waveguide effects on pulse-delay measurements of material dispersion in. A.H.Hartog 632
Optical fibres, method of calculating the modal delay for, with arbitrary refractive-index profiles. D.H.Irving and A.E.Karbowiak 160
Optical fibres, modal dispersion of, with a composite α-profile graded-index core. A.Weierholt 733
Optical fibres, multimode, optical loss change caused by hydraulic pressure in. M.Kawase, K.Yamashita, M.Nishimura, T.Yamanishi and Y.Sugawara 208
Optical fibres, practical machine for electric arc splicing of, in the field. K.D.Khoe 152
Optical fibres prepared by plasma-augmented vapour deposition. J.Irven and A.Robinson 252
Optical fibres, silicone-clad silica, characteristics against length of. I.Nouchi, A.Jacques and L.D'Auria 315
Optical fibres, single-mode, vibration-induced polarisation modulation of light guided in. A.Papp and H.Harms 76
Optical fibres, single-polarisation germanosilicate, strain birefringence in. I.P.Kaminow, J.R.Simpson, H.M.Presby and J.B.MacChesney 677
Optical fibres, v.a.d., OH-ion reduced in. T.Edahiro, M.Kawachi, S.Sudo and H.Takata 482
Optical frequency-selective filters in ion-exchanged waveguides. A.Yi Yan and C.D.W.Wilkinson 240
Optical images, two-dimensional acoustic scanning of. H.Gautier, P.Ledu and C.Maerfeld 186
Optical images, two-dimensional high-speed acoustic Fourier transform of. H.Gautier, P.Ledu and C.Maerfeld 177
Optical isolator, structure simplification of, coupled with laser diode. T.Matsumoto 625
Optical link, half-duplex, libido using Eros:. L.d'Auria, G.Chevalier and P.Maillot 820
Optical loss change caused by hydraulic pressure in multimode optical fibres. M.Kawase, K.Yamashita, M.Nishimura, T.Yamanishi and Y.Sugawara 208
Optical matrix switch, low-loss 4 x 4, for fibre-optic communication. Y Fujii, J.Minowa, T.Aoyama and K.Doi 427
Optical probe for absolute measurement of surface-acoustic-wave amplitude. F.Azan, J.M.Mouly and J.Salset 80
Optical pulse generation, picosecond, from an r.f. modulated AlGaAs d.h. diode laser. H.Ito, H.Yokoyama, S.Murata and H.Inaba 738
Optical receiver package, miniaturised, hybrid, 500 Mb/s, for data-link applications. T.N.C.Venkatesan and K.Ogawa 171
Optical receiver, wideband, GaAs f.e.t. transimpedance front-end design for a. K.Ogawa and E.L.Chinnock 650
Optical receivers, new automatic-gain-control system for. M.Eve and D.W.Smith 146
Optical systems, bidirectional, measurement of frequency dependence of Rayleigh backscattering in. J.Straus, I.S.Few and J.Conradi 306
Optical transmission, analogue, of 26 t.v. channels. C.Baack, G.Elze, G.Grosskopf, G.Kraus, F.Krick and L.Küller 300
Errata 444
Optical transmission, bidirectional analogue, using semiconductor junction transceivers. R.I.Macdonald 121
Optical transmission experiments, 1.5 m, using very low-loss single-mode fibres. S.Machida, J.Yamada, T.Mukai, Y.Horikoshi, H.Tsuchiya and T.Miya 219
Optical transmission loss of germanium borosilicate fibres as a function of drawing conditions. D.H.Smithgall, M.A.Saifi and M.J.Andrejco 56
Optical transmission systems, simple polarisation-independent optical circulator for. H.Iwamura, H.Iwasaki, K.Kubodera, Y.Torii and J.Noda 830
Optical waveguide, Mach-Zehnder interferometric, integrated bistable optical device using. H.Ito, Y.Ogawa and H.Inaba 283
Optical waveguide polariser with synchronous absorption. S.Wright, A.D.De Oliveira and M.G.F.Wilson 510
Optical waveguides, $LiNbO_3$, novel beam-to-waveguide coupler for. J.Čtyroký, M.Cada, N.M.Lyndin, V.A.Sychugov and J.Schroefel 519
Optical waveguides:, radiation from, leaky-mode interpretation. A.W.Snyder and R.A.Sammut 58
Optical waveguides, radiation modes of. A.W.Snyder and R.A.Sammut 4
Optical waveguides, trapezoidal cross-section dielectric, mode dispersion of, by the effective-index method. J.G.Gallagher 734
Optical waveguiding, strain induced, in GaAs epitaxial layers at 1.15 μm. L.D.Westbrook, P.N.Robson and A.Majerfeld 99
Optical Y-branch, low-loss. D.Opielka and D.Rittich 757
Optics, coupling high-refractive-index integrated, As_2S_3-p.e.s. sandwich ribbon fibre for. C.A.Millar and R.H.Hutchins 60
Optimal controller, design of, for linear single-input system. LimChoo.Mim and B.S.Habibullah 660
Optimal estimation of a common phase difference between pairs of fluctuating signals in noise. R.Voles 145
Optimal input for stochastic linear discrete systems as a function of input and output variables. C.S.Berger 360
Optimal radiation pattern of an array in the presence of two directional interferences. P.C.K.Kwok and P.S.Brandon 251
Optimal radix for monolithic memories. E.Seevinck 736
Optimal regulator, P.I.D. equivalent of. S.Mukhopadhyay Errata 578
Optimal tracking problem, discrete-time linear-quadratic, using future desired output values. J.Karpinsky, T.Benes, V.Hlavaty, V.Rozkosny and P.Sajal 316
Optimally sensitive controller for digital systems. W.F.Fincham and C.L.Nikias 537
Optimisation of backscatter using the concept of complex characteristic polarisations. S.H.W.Simpson and B.Chambers 547
Optimum p.c.m. regenerator performance in presence of crosstalk. A.J.Gibbs, L.J.Millott and G.Nicholson 490
Orientation dependance of n-type GaAs intrinsic avalanche response time. J.J.Berenz, J.Kinoshita, T.L.Hierl and C.A.Lee 150
Oscillator, high peripheral power density GaAs f.e.t.. J.S.Joshi and J.A.Turner 163
Oscillator, new canonic single-resistance-controlled sinusoidal, using a single current conveyor. R.Senani 568
Oscillator, pulsed molecular-beam maser, injection priming of a. D.C.Lainé and A.M.Al-Jumaily 21
Oscillators, application to, Network condition for counter-clockwise reflection-coefficient behaviour:,. C.M.Krowne 114
Overlength-mode transferred-electron harmonic generators. A.M.Mazzone and H.D.Rees 813

P

P.C.M. codec, high-performance c.c.d. channel filter for a. T.Enomoto, T.Ishihara, M.Yasumoto and S.Shida 817
P.C.M. regenerator crosstalk performance, measurement of. A.J.Gibbs 82
P.C.M. regenerator, optimum, performance in presence of crosstalk. A.J.Gibbs, L.J.Millott and G.Nicholson 490
P.I.D. equivalent of optimal regulator. S.Mukhopadhyay Errata 578
P.S.K. signal detection, novel technique for eliminating the ambiguity in. A.Pongsupaht and J.D.Parsons 385
Paraboloidal antennas, phase centre of. Y.H.Ja 784
Parameter/state estimation, joint. A.Jakeman and P.Young 582
Peak-amplitude detector for sinusoidal signals. S.Pookaiyaudom, C.Watanachaiprateep and K.Dejhan 127
Performance degradation of decision-directed c.p.s.k. demodulator due to uncompensated time delay of decision circuitry. S.G.Glisic 331
Performance of interframe predictive coders for television signals under various conditions of motion. D.E.Pearson and T.J.Dennis 66
Periodic slow-wave low-loss structures for monolithic GaAs microwave integrated circuits. E.M.Bastida and G.P.Donzelli 581
Permittivity, dynamic, of microstrip ring resonator. J.Vrba 504
Petri nets, generalised, hardware implementation of. M.Courvoisier and J.P.Seck 770
Phase centre of paraboloidal antennas. Y.H.Ja 784
Phase-locked loop, discrete, new approach to, based on digital measurement of time intervals. D.Perisic 445
Phosphor-doped silica cladding v.a.d. fibres. T.Edahiro, S.Sudo, M.Kawachi, K.Jinguji and N.Inagaki 726
Phosphosilicate glass, gettering of epitaxial gallium phosphide using. B.W.Wessels 748
Photoacoustic microscope. M.Luukkala and A.Penttinen 325
Photoconductive detectors, ultraviolet, in Zn_3P_2. K.G.Irwin, N.S.Kopeika and R.G.Hunsperger 718
Photodetector, avalanche, low-noise multistage. J.P.Gordon, R.E.Nahory, M.A.Pollack and J.M.Worlock 518
Photodiodes, avalanche, high-gain GaAs, with proton-implanted guard ring. N.Susa, H.Kanbe, T.Nishioka and Y.Ohmachi 535
Photodiodes, $In_{0.53}Ga_{0.47}As$ p-i-n, for long-wavelength fibre-optic systems. R.F.Leheny, R.E.Nahory and M.A.Pollack 713
Photodiodes, InGaAsP p-i-n, with low dark current and small capacitance. C.A.Burrus, A.G.Dentai and T.P.Lee 655
Photodiodes, InP-InGaAsP planar avalanche, with self-guard-ring effect. K.Taguchi, Y.Matsumoto and K.Nishida 453
Photodiodes, planar, made from vapour-phase epitaxial $In_xGa_{1-x}As$. N.Susa, Y.Yamauchi and H.Kanbe 238
Photoresist, Se-Ge inorganic, properties of, as an ion-implantation mask. A.Yoshikawa, T.Tamama, Y.Mizushima, K.Kudo and T.Shigematsu 499
Picosecond optical pulse generation from an r.f. modulated AlGaAs d.h. diode laser. H.Ito, H.Yokoyama, S.Murata and H.Inaba 738
Piezoelectric PVF_2 films, ultrasonic attenuation of, at high frequencies. B.T.Khuri-Yakub and C.H.Chou 308
Piezojunction effect of a planar n-p-n transistor for transducer aims. R.J.Veen 333
Planar photodiodes made from vapour-phase epitaxial $In_xGa_{1-x}As$. N.Susa, Y.Yamauchi and H.Kanbe 238
Plasmas, unmagnetised, continuous measurement of electron density in, by a self-oscillating probe. R.Debrie and J.Pignard 799
Plastic optical fibre with improved transmittance. S.Oikawa, M.Fujiki and Y.Katayama 829
Polar-loop transmitter. V.Petrovic and W.Gosling 286
Polarisation microwave receiver, arbitrary, applied to OTS reception. A.P.Alves and N.J.McEwan 657
Polarisation radar, dual-, relationship of differential reflectivity to correlation in. G.C.McCormick 265
Polariser, optical waveguide, with synchronous absorption. S.Wright, A.D.De Oliveira and M.G.F.Wilson 510
Polarisers, reflection circular. E.V.Jull 423
Pole:, simulation of inductors and capacitors using operational amplifier compensation, a caution. S.Srinivasan and K.Radhakrishna Rao 472
Poles, amplifier, practical aspects of filters using, comment on. R.Schaumann, J.R.Brand and K.R.Laker 493
Polynomial, compact, forms of sensitivity criteria. C.L.Nikias and W.F.Fincham 23
Polynomial transform algorithms, fast, D.F.T. computation by. H.J.Nussbaumer 701
Power amplifier, high-gain 9.25 GHz silicon bipolar transistor. Y.S.Wu, H.T.Yuan and W.R.Wisseman 86
Power combiner, W-band two-diode. K.Chang, R.Ebert and C.Sun 403
Power f.e.t., flip-chip mounted GaAs, with improved performance in X- to Ku-band. Y.Mitsui, M.Kobiki, M.Wataze, M.Otsubo, T.Ishii and S.Mitsui 461
Power GaAs f.e.t.s., 11 GHz and 12 GHz multiwatt internal matching for. Y.Takayama, T.Ogawa and Y.Aono 326
Power-line temperature sensing, remote, crystal-oscillator-based device for. P.L.Arlett, A.Walton, K.Elkins and K.O'Neill 93
Power spectrum of the balanced digital signal generated by Markov source. G.Petrović 769
Power transistors, V-v.m.o.s., on-resistance of. W.A.Lane, C.A.T.Salama and S.Dmitrevsky 601
Practical machine for electric arc splicing of optical fibres in the field. K.D.Khoe 152
Preliminary c.w. reliability measurements on GaAs-(GaAl)As stripe lasers grown by metal-organic c.v.d.. E.J.Thrush and J.E.A.Whiteaway 666
Preparation and properties of GaAs layers for novel f.e.t. structures. R.J.M.Griffiths, I.D.Blenkinsop and D.R.Wight 629

Preparation of long lengths of ultra-low-loss single-mode fibre. B.J.Ainslie, C.R.Day, P.W.France, K.J.Beales and G.R.Newns 411
Preservation of polarisation in optical-fibre waveguides with elliptical cores. R.B.Dyott, J.R.Cozens and D.G.Morris 380
Probe, self-oscillating, continuous measurement of electron density in unmagnetised plasmas by a. R.Debrie and J.Pignard 799
Processors, baseband compatible s.a.w.. G.F.Manes and C.Atzeni 661
Propagation constants of guided modes in graded-index fibre with polynomial-profile core. H.Ikuno 762
Propagation delay optimisation in multistage GaAs m.e.s.f.e.t. combinational logic circuits by use of dynamic programming. A.Barna 147
Propagation, multipath, in line-of-sight links. L.Boithias 209
Propagation, surface-wave, experimental study of, on a low-permittivity medium. J.Appel-Hansen and R.J.King 101
Properties of Se-Ge inorganic photoresist as an ion-implantation mask. A.Yoshikawa, T.Tamama, Y.Mizushima, K.Kudo and T.Shigematsu 499
Proposed technique for reduction of contouring in quantised (monochrome) image signals. O.J.Downing and P.L.M.Thorpe 5
Pulse code modulation, interframe differential, quantiser selection for, of television pictures. T.J.Dennis 142
Pulse modulator, m.o.s. neural. Z.Czarnul, G.Kiruthi and R.W.Newcomb 823
Pulse-widening measurement. R.A.Zakarevicius 119
Pulsed GaAs f.e.t. operation for high peak output powers. P.C.Wade, D.Rutkowski and I.Drukier 591
Pumped Schottky diodes with noise temperatures of less than 100 K at 115 GHz. N.J.Keen, W.M.Kelly and G.T.Wrixon 689

Q

Q-sensitivity of certain RC active filters to gain-bandwidth product. P.V.Anandamohan 95
Quadratic phase error loss in circular apertures. A.W.Love 276
Quadrature references, digitally generated, resolved component indicator based on. T.G.Izatt and E.Ball 83
Quality test of semiconductor memories by jitter measurement. H.Röder 428
Quantisation effect in data windows. K.M.M.Prabhu and J.P.Agrawal 25
Quantiser selection for interframe differential pulse code modulation of television pictures. T.J.Dennis 142
Quantising error in a Dolph-Chebyshev data-window multiplier circuit. M.Trivedi and K.V.Lever 136
Quantitative analysis of 2-f.s.k. traffic detection. B.Forssell 386
Quantitative estimations of mode-coupling mechanisms in an optical fibre. K.Tatekura, K.Itoh and T.Matsumoto 9
Quartz resonator, inverted-mesa AT-cut, appraisal of the, for achieving low-inductance high-Q single-response crystal units. J.Birch and S.P.Marriott 641
Quiet tuning of antennas. M.J.Underhill and P.A.Lewis 37

R

Radar, dual-polarisation, relationship of differential reflectivity to correlation in. G.C.McCormick 265
Radars, form of Doppler processing for, of random p.r.i. and r.f.. R.Benjamin 782
Radiation, effect of ionising, on mobile-ion density in m.o.s. oxides. T.N.Bhar, R.Dat, R.Y.Koyama and K.F.Galloway 16
Radiation from optical waveguides: leaky-mode interpretation. A.W.Snyder and R.A.Sammut 58
Radiation modes of optical waveguides. A.W.Snyder and R.A.Sammut 4
Radiation pattern, optimal, of an array in the presence of two directional interferences. P.C.K.Kwok and P.S.Brandon 251
Radio links:, digital, validity of two-path model for calculating quality of, determination of model from measurements on analogue links. M.Rooryck 783
Radiometers, 20 and 30 GHz passive, satellite slant-path attenuation statistics obtained using, at Martlesham Heath. R.R.Bell and J.Thirlwell 181
Radiotelephone communications, 800 MHz microwave mobile, user density for. D.R.Conn and R.Maciejko 516
Rain attenuation of 12/14 GHz satellite video transmissions. O.G.Nackoney and D.Davidson 703
Raindrops, effects of drop size and temperature on forward and backward scattering of microwaves by. S.A.J.Upton, B.G.Evans and A.R.Holt 760
Rapidly converging observers involve high-order differentiations. M.Zeitz 708
Rational admittance function realisation using two operational amplifiers. S.Osowski 85
Ray interpretation of the material signature in the acoustic microscope. W.Parmon and H.L.Bertoni 684
Rayleigh backscattering, measurement of frequency dependence of, in bidirectional optical systems. J.Straus, I.S.Few and J.Conradi 306
Realisation materielle des reseaux de Petri generalises. M.Courvoisier and J.P.Seck 770
Receiver, dual-channel 1.5 Mb/s lightwave, employing an InGaAsP wavelength-demultiplexing detector. T.P.Lee, J.C.Campbell, K.Ogawa, A.R.McCormick, A.G.Dentai and C.A.Burrus 388
Recombination in gallium phosphide via a deep state associated with nickel. A.R.Peaker, R.F.Brunwin, P.Jordan and B.Hamilton 663
Rectangular-waveguide-excited short backfire antenna with corrugated rim. M.S.Leong and P.S.Kooi 533
Rectification at n-n GaAs: (Ga, Al)As heterojunctions. A.Chandra and L.F.Eastman 90 Errata 216
Recursive algorithm for adaptive lattices. T.S.Durrani and N.L.M.Murukutla 831
Recursive formulae for ladder-network optimisation. E.Olcayto 249
Recursive linear estimation of linearly constrained parameters. J.P.Norton 715
Redundancy reduction (Saver), two dimensional, simple adaptive vectors encoding for. P.K.S.Wah 221
Reflection circular polarisers. E.V.Jull 423
Reflection-mode amplifier utilising GaAs active-medium-propagation devices. P.L.Fleming and H.E.Carlson 787
Reflectivity, differential, relationship of, to correlation in dual-polarisation radar. G.C.McCormick 265
Reflector and aperture antennas, large, new approach to the analysis of, evanescent-wave tracking:. L.B.Felsen 531
Reflector antennas, corner, numerical evaluation of phase centres of. Y.H.Ja 1
Reflector, effect of, and exciter size on the radiation of circular-loop Yagi arrays. A.Shoamanesh and L.Shafai 103
Reflector, parabolic, feed position for a, with offset pattern. S.Cornbleet 211
Refractive-index profile measurement, nondestructive, of elliptical optical fibre or preform. P.L.Chu 357
Refractive-index profile, measurement of, of optical-fibre preform. P.L.Chu and T.Whitbread 295
Refractive-index profile, nondestructive determination of, and cross-sectional geometry of optical-fibre preform. P.L.Chu and C.Saekeang 635
Relation between splice loss and mode conversion in a graded-index optical fibre. N.Kashima and N.Uchida 336
Relationship of differential reflectivity to correlation in dual-polarisation radar. G.C.McCormick 265
Reliability measurements, preliminary c.w., on GaAs-(GaAl)As stripe lasers grown by metal-organic c.v.d.. E.J.Thrush and J.E.A.Whiteaway 666
Remarks on the convolution algorithm of Agarwal and Cooley. J.M.Pollard 593
Resistance functions, electrical, concavity and sensitivity of. F.Reza 305
Resistance measurements, spreading-, resolution of, on shallow layers. S.A.Abbasi and A.Brunnschweiler 290
Resistive hybrid matrix realisation using operational amplifiers. S.Osowski 426
Resolution of spreading-resistance measurements on shallow layers. S.A.Abbasi and A.Brunnschweiler 290
Resolved component indicator based on digitally generated quadrature references. T.G.Izatt and E.Ball 83
Resonator, microstrip ring, dynamic permittivity of. J.Vrba 504
Resonators, s.a.w., at 1.29 GHz with Q values approaching the material limit. W.J.Tanski 339
Resonators, s.a.w., fine tuning of, using argon ion bombardment. S.James and I.H.Wilson 683
Response, transient, evaluation of the, of linear stationary systems to a class of excitations. M.M.Milić and M.V.Gmitrović 614
Responsivity and noise characterisation of Ge avalanche photodiode throughout wavelength range 1.1-1.7 μm. M.C.Brain 821
Robot movement, decoupled control of. J.R.Hewit 670
Roll-off shaping filter design for improving adaptive equalisation. K.Wesolowski 338
Room temperature c.w. operation of InGaAsP/InP heterostructure lasers emitting at 1.56 μm. S.Akiba, K.Sakai, Y.Matsushima and T.Yamamoto 606
Room-temperature c.w. operation of InP/InGaAsP/InP double heterostructure diode lasers emitting at 1.55 μm. H.Kawaguchi, K.Takahei, Y.Toyoshima, H.Nagai and G.Iwane 669
Rotation of a waveform generator. B.Z.Kaplan 158

S

S.A.W.-based discrete Fourier transformer, fast. J.B.G.Roberts, B.J.Darby, R.A.Bale and R.Eames Errata 262
S.A.W. convolver using secondary electrons. A.A.Dobrovolsky, V.V.Lemanov, G.A.Smolensky and A.B.Sherman 437
S.A.W. devices, quartz, 1/f phase noise in. T.E.Parker 296
S.A.W. filter responses, fast computation of, including diffraction. E.B.Savage 538
S.A.W. memory correlators, charge storage in. M.El-Nokali and E.L.Adler 323
S.A.W. processors, baseband compatible. G.F.Manes and C.Atzeni 661
S.A.W. resonators at 1.29 GHz with Q values approaching the material limit. W.J.Tanski 339
S.A.W. resonators, fine tuning of, using argon ion bombardment. S.James and I.H.Wilson 683
S.A.W. time-inversion system, new. H.Messer, Y.Bar-Ness and H.Gilboa 214
Sample-and-hold circuits, self-equalising. R.Gregorian and G.C.Temes 367
Satellite link, millimetre-wave earth-, seasonal variations of attenuation statistics in, due to bright-band height. M.Fujita, K.Nakamura, T.Ihara and R.Hayashi 654
Satellite slant-path attenuation statistics obtained using 20 and 30 GHz passive radiometers at Martlesham Heath. R.R.Bell and J.Thirlwell 181
Satellite systems single-channel-per-carrier frequency-modulation spectra, measurement and simulation of. B.G.Evans, H.Ganem and J.Dutronc 194
Satellite video transmissions, 12/14 GHz, rain attenuation of. O.G.Nackoney and D.Davidson 703
Scanning-electron-beam annealing of ion-implanted p-n junction diodes. R.A.McMahon, H.Ahmed, J.D.Speight and R.M.Dobson 433
Scattering, alloy, influence of central valley effective mass and, on transient drift velocity in $Ga_{1-x}In_xP_{1-y}As_y$. M.A.Littlejohn, L.A.Arledge, T.H.Glisson and J.R.Hauser 586
Scattering, effects of drop size and temperature on forward and backward, of microwaves by raindrops. S A.J.Upton, B.G.Evans and A.R.Holt 760
Schottky diodes, platinum-silicon, argon-ion bombardment effects on the electrical characteristics of. J.Garrido, E.Calleja and J.Piqueras 815
Schottky diodes, pumped, with noise temperatures of less than 100 K at 115 GHz. N.J.Keen, W.M.Kelly and G.T.Wrixon 689
Seasonal variations of attenuation statistics in millimetre-wave earth-satellite link due to bright-band height. M.Fujita, K.Nakamura, T.Ihara and R.Hayashi 654
Self-adaptive Kalman filter. P.Young 358
Self-equalising sample-and-hold circuits. R.Gregorian and G.C.Temes 367
Self-tuning controller steady-state error. A.Y.Allidina and F.M.Hughes 346
Semiconductor devices, microelectrodes for contacting. M.V.Schneider and H.Berger 450
Semiconductor isolator based on cyclotron resonance phenomenon. A.Laurinvičius and V.Balynas 15
Semiconductor laser diodes, analogue baseband t.v. transmission experiments using. K-I.Sato and K.Asatani 794
Semiconductor memories, quality test of, by jitter measurement. H.Röder 428
Semiconductors, automatic electrochemical profiling of Hall mobility in. T.Ambridge and C.J.Allen 648
Semiconductors, direct-gap, numerical analysis of forward-biased diode structures based on. E.Velmre and B.Freidin 383
Semiconductors, variance noise and temperature fluctuations in. S.Rahal and A.Chovet 271
Sensitivity, concavity and, of electrical resistance functions. F.Reza 305
Sensitivity criteria, compact polynomial forms of. C.L.Nikias and W.F.Fincham 23

Sensitivity measure, a new, slope-normalised sensitivity;. J.K.Fidler and C.Nightingale 54
Sequential machine, Moore-model, fault detection in, using counter-cycle technique. A.Bhattacharyya 402
Sequential machine, very easily testable/diagnosable. A.Bhattacharyya 190
Sequential machines:, minimisation of incompletely specified, the 'really' excluded compatibility classes. G.Palama and G.V.Russo 690
Sequential machines, synchronous, transition matrices in multiple preset experiments and initial state identification of. S.R.Das, P.Chao and Z.Chen 777
Sequential voltage-inversion principle for switched-capacitor filters. J.Pandel 399
Shear surface acoustic waves at the periodically nonuniform boundary between two solids. Y.V.Gulyaev and V.P.Plessky 63
Sidetone expansion for the regulation of talker loudness. D.J.Goodman and J.D.Johnston 492
Signal detection, p.s.k., novel technique for eliminating the ambiguity in. A.Pongsupaht and J.D.Parsons 385
Signal-level dependence in the recovery rate of irradiated plastic-clad silica fibre. J.G.Titchmarsh 111
Signal-processing operations on A-law companded speech. P.Bylanski 697
Signals, fluctuating, in noise, optimal estimation of a common phase difference between pairs of. R.Voles 145
Silica fibres, germania-doped, definitive profile-dispersion data for, over an extended wavelength range. F.M.E.Sladen, D.N.Payne and M.J.Adams 469
Silica fibres, very low OH content P_2O_5-doped. Y.Ohmori, H.Okazaki, I.Hatakeyama and H.Takata 616
Silica graded-index fibres, $GeO_2-P_2O_5$-doped, spectral loss characteristics of, in long-wavelength band. T.Edahiro, M.Horiguchi, K.Chida and Y.Ohmori 274
Silicon, electrochemical carrier concentration profiling in. C.D.Sharpe, P.Lilley, C.R.Elliott and T.Ambridge 622
Silicon field-effect device, amorphous-, and possible application. P.G.Le Comber, W.E.Spear and A.Ghaith 179
Silicon, ion-implanted, electron-beam annealing of. R.A.McMahon and H.Ahmed 45
Silicon-on-insulator m.o.s.f.e.t.s. fabricated on laser-annealed polysilicon on SiO_2. A.F.Jun.Tasch, T.C.Holloway, K.F.Lee and J.F.Gibbons 435
Silicon-on-sapphire devices, silicon-implanted furnace-annealed, electrical properties of. M.E.Roulet, P.Schwob, I.Golecki and M.-A.Nicolet 527
Silicon-on-sapphire m.o.s.f.e.t.s. fabricated by back-surface laser-anneal technology. S.Iwamatsu and M.Ogawa 827
Similitude between ionic wind, discharge pattern and corona current. L.C.Thanh 57
Simple adaptive vectors encoding for two-dimensional redundancy reduction (Saver). P.K.S.Wah 221
Simple derivation of the expression for the synchronous field in circular cylindrical cavity gyrotrons. M.K.Haldar and A.H.Beck 487
Simple formulas for jitter accumulation in a chain of regenerative repeaters in optical-fibre transmission systems. U.Mengali and G.Pirani 561
Simple implementation of sampled-data filters using current multipliers, switches, and capacitors. J.I.Arreola, Y.P.Tsividis, E.Sanchez-Sinencio and P.E.Allen 780
Simple method for computing elements of order $2^k n$, where $n/2^{p-1}-1$ and $2 \leq k \leq p+1$, in $GF[(2^{p-1}-1)^2]$, Comment on. D.V.Sarwate 69
Simple model of large-signal properties of 1 W f.e.t. at 5 GHz. K.L.Kotzebue and E.R.Ehlers 237
Simple modification to circuit enumeration algorithm for better efficiency. J.P.Char and S.D.Dadheech 191
Simple polarisation-independent optical circulator for optical transmission systems. H.Iwamura, H.Iwasaki, K.Kubodera, Y.Torii and J.Noda 830
Simple system for broad-band single-mode tuning of d.h. GaAlAs lasers. D.Renner and J.E.Carroll 73
Simplified design procedures for a third-order system using current conveyors. F.W.Stephenson and J.Dunning-Davies 215
Simplified FEXT calculations. R.V.McLachlan 545
Simplified procedure for indirect tests of optical-fibre transfer functions. G.Cancellieri, M.Mezzetti, C.G.Someda and M.Zoboli 234
Simulation circuits, floating-inductance, switched-capacitor filters using. ManShek Lee 644
Simulation, measurement and, of satellite systems single-channel-per-carrier frequency-modulation spectra. B.G.Evans, H.Ganem and J.Dutronc 194
Simultaneous dehydration with consolidation for v.a.d. method. K.Chida, F.Hanawa, M.Nakahara and N.Inagaki 835
Sine-cosine squared-magnitude function for maximally flat digital bandpass filters with adjustable skirt selectivities. P.Thajchayapong and F.Cheevasuvit 345
Single-mode c.w. ridge-waveguide laser emitting at 1.55 μm. I.P.Kaminow, R.E.Nahory, M.A.Pollack, L.W.Stulz and J.C.DeWinter 763
Single-mode propagation in 2-mode region of optical fibre by using mode filter. Y.Katsuyama 442
Single-pole amplifier approximation inductance simulation and filter design using a, comment on. E.Sánchez-Sinencio and D.Báez-López 465
Sinusoidal frequency doubler. R.Genin and R.Konn 47
Slope-normalised sensitivity: a new sensitivity measure. J.K.Fidler and C.Nightingale 54
Small-area GaAs-GaAlAs heterostructure light-emitting diode with improved current confinement. M.-C.Amann and W.Proebster 599
Soft-decision decoding of the teletext character code. R.M.F.Goodman 108
Solar cell, low-bandgap (1.15 eV) InGaP/InGaAs. R.R.Saxena and R.L.Moon 826
Solar-cell panel simulator. D.Baert 53
Solar cells, method for lifetime measurement in, open-circuit to short-circuit switching:. S.R.Dhariwal, N.Basu and R.Gadre 456
Some comments on notch capability of N-path filters. B.G.Pain 486
Some proposals for improved forms of precision fast digital-analogue and analogue-digital converters. J.R.Stockton and R.B.D.Knight Errata 166
Sonar transducers, high-frequency, equivalent circuits for. H.Koymen, B.V.Smith and B.K.Gazey 600
Speckle and quantum noise, information retrieval in the presence of. P.Mohana Shankar and H.M.Gupta 464
Spectral characterisation of ternary threshold functions. C.Moraga 712
Spectral loss characteristics of $GeO_2-P_2O_5$-doped silica graded-index fibres in long-wavelength band. T.Edahiro, M.Horiguchi, K.Chida and Y.Ohmori 274
Spectrum, distribution of symmetry information in, of Boolean function. D.M.Miller and J.C.Muzio 816
Speech, A-law companded, signal-processing operations on. P.Bylanski 697
Speech unscrambler, compact helium, using charge-transfer devices. M.A.Jack, A.D.Milne and L.E.Virr 548
Splice loss evaluation by means of the back-scattering technique. B.Costa, F.Esposto, C.D'Orio and P.Morra 550
Splice loss, relation between, and mode conversion in a graded-index optical fibre. N.Kashima and N.Uchida 336
Spline approximation, periodic, nonlinear circuit analysis through. F.Filicori, M.R.Scalas and C.Naldi 597
Split-loop method for wide-range frequency synthesiser with good dynamic performance. M.J.Underhill and P.A.Jordan 391
Spread in effective permittivity of alumina substrates. L.Accatino and A.Angelucci 64
Spread-spectrum communication systems, filtering out intersymbol interference in. L.Alcuri, G.Mamola and E.Randazzo 397
Squid, d.c., with high energy resolution. P.Gutmann 372
Stability, asymptotic, of differential multipass processes. D.H.Owens 446
Stability problem, inverse, inverse Routh-Hurwitz array solution to the. A.C.Tsoi 575
Stable reduced-order Pade approximants using the Routh-Hurwitz array, comment on. S.A.Marshall 501
Stable reduced-order pade approximants using the Routh-Hurwitz array. J.Pal 225
State estimation, joint parameter/. A.Jakeman and P.Young 582
Step and frequency responses of c.t.d.s. with nonuniform transfer inefficiency. R.M.Barsan 389
Stigmatically focusing grating coupler. M.Miler and M.Skalsky 275
Stochastic linear discrete systems, optimal input for, as a function of input and output variables. C.S.Berger 360
Strain birefringence in single-polarisation germanosilicate optical fibres. I.P.Kaminow, J.R.Simpson, H.M.Presby and J.B.MacChesney 677
Strain-induced optical waveguiding in GaAs epitaxial layers at 1.15 μm. L.D.Westbrook, P.N.Robson and A.Majerfeld 99
Strays-insensitive switched-capacitor filters based on bilinear Z-transform. K.Martin and A.S.Sedra 365
Streak and spot detection in digital pictures. B.G.Batchelor 352
Strips and slots, circularly polarised printed array antennas composed of. K.Ito, N.Aizawa and N.Goto 811
Structure simplification of optical isolator coupled with laser diode. T.Matsumoto 625
Structures, novel f.e.t., preparation and properties of GaAs layers for. R.J.M.Griffiths, I.D.Blenkinsop and D.R.Wight 629
Substrate conduction in GaAs m.e.s.f.e.t.s.. P.G.Borden 307
Substrates, lossy, electrical properties of coplanar transmission lines on lossless and. J.-P.Becker and D.Jäger 88
Suitable parameters of single-mode optical fibre. Y.Katsuyama, Y.Ishida, K.Ishihara and T.Miyashita 94
Supply-current analysis technique, integrated-circuit fabrication flaw detected using the. M.G.Rowlands 745
Surface-acoustic-wave amplitude, optical probe for absolute measurement of. F.Azan, J.M.Mouly and J.Salset 80
Surface-acoustic-wave delay lines, technique for triple-transit suppression in. W.J.Tanski and H.Van de Vaart 312
Surface acoustic wave, new electrostatic probe for absolute measurement of amplitude of. J.B.Moreau, R.Hashim and J.C.Neau 155
Surface acoustic waves, shear, at the periodically nonuniform boundary between two solids. Y.V.Gulyaev and V.P.Plessky 63
Surface impedance of elliptical hollow conducting waveguides. S.R.Rengarajan and J.E.Lewis 637
Surface reactance of corrugated planes. G.L.James 751
Surface stability of GaAs during tin diffusion. B.Tuck and M.H.Badawi 604
Surface states, m.o.s., synthesis and analysis of d.l.t.s. spectra from. K.R.Wright 744
Surface-wave interdigital transducer analysis, fundamental charge distributions for. D.P.Morgan, B.Lewis and J.G.Metcalfe 583
Switch, multiposition optical-fibre. W.J.Tomlinson, R.E.Wagner, A.R.Strnad and F.A.Dunn 192
Switched-capacitor circuits bilinearly equivalent to floating inductor or f.d.n.r.. G.C.Temes and M.Jahanbegloo 87
Switched-capacitor filters, alternative approach to the design of. B.G.Pain 438
Switched-capacitor filters, alternative approach to the design of, comment on. J.J.Hill 650
Switched-capacitor filters, compensation for parasitic capacitances in. G.C.Temes and R.Gregorian 377
Switched-capacitor filters, sequential voltage-inversion principle for. J.Pandel 399
Switched-capacitor filters, strays-insensitive, based on bilinear Z-transform. K.Martin and A.S.Sedra 365
Switched-capacitor filters using floating-inductance simulation circuits. ManShek Lee 644
Switched-capacitor floating inductors, alternative realisations of. U.W.Brugger and B.J.Hosticka 698
Switched-capacitor integrators, novel dynamic c.m.o.s. amplifier for. B.J.Hosticka 532
Switched-capacitor simulation of floating inductors using gyrators. U.W.Brugger, B.J.Hosticka and G.S.Moschytz 494
Switched-capacitor simulation of grounded inductors using operational-amplifier pole. E.Sánchez-Sinencio and J.L.Gómez-Oserio 169
Switched-capacitor transconductance elements and gyrators. T.R.Viswanathan, J.Vlach and K.Singhal 318
Switched networks, avoiding complex matrix manipulation for. B.G.Pain 7
Switches, and capacitors, current multipliers, simple implementation of sampled-data filters using. J.I.Arreola, Y.P.Tsividis, E.Sanchez-Sinencio and P.E.Allen 780
Switching:, open-circuit to short-circuit, method for lifetime measurement in solar cells. S.R.Dhariwal, N.Basu and R.Gadre 456
Symmetry information, distribution of, in spectrum of Boolean function. D.M.Miller and J.C.Muzio 816
Synthesis and analysis of d.l.t.s. spectra from m.o.s. surface states. K.R.Wright 744
Synthesis of matched b.j.t. cascode broadband amplifiers. D.J.Ahlgren 709
Synthesisers, land mobile radio, 800 MHz v.c.o. for. M.Makimoto, K.Nakabe and S.Nishiki 460
System reduction by Routh approximation and modified Cauer continued fraction. S.(Mrs) John and R.Parthasarathy 691
Systems:, digraph analysis of large-scale, the system primitive. F.J.Evans and C.Schizas 613

Systems, linear stationary, evaluation of the transient response of, to a class of excitations. M.M.Milić and M.V.Gmitrović 614
Systems, nonderogatory, alternative Kalman controllability criterion for. T.T.Ha and J.A.Gibson 451

T

Tailoring zero chromatic dispersion into the 1.5-1.6 μm low-loss spectral region of single-mode fibres. L.G.Cohen, C.Lin and W.G.French 334
Talker loudness, sidetone expansion for the regulation of. D.J.Goodman and J.D.Johnston 492
Technique for triple-transit suppression in surface-acoustic-wave delay lines. W.J.Tanski and H.Van de Vaart 312
Tee-coupler for single-mode fibres. E.Weidal and D.Gruchmann 737
Telephone, loudspeaker, adaptive filters to improve. C.R.South, C.E.Hoppitt and A.V.Lewis 673
Teletext system, dual-mode transmission technique for Chinese ideographs in a. P.C.K.Kwok and J.P.K.Lai 268
Television distribution, intermodulation improvement for multichannel, by appropriate channel allocations and the use of 1/3rd line offsets. J.M.Griffiths 162
Television pictures, quantiser selection for interframe differential pulse code modulation of. T.J.Dennis 142
Temperature dependence of impact ionisation rates in GaAs between 20° and 200° C. F.Capasso, R.E.Nahory and M.A.Pollack 117 Errata 507
Temperature dependence of InGaAsP double-heterostructure laser characteristics. R.E.Nahory, M.A.Pollock and J.C.DeWinter 695
Temperature sensing, remote power-line, crystal-oscillator-based device for. P.L.Arlett, A.Walton, K.Elkins and K.O'Neill 93
TE_{on}-mode filters for the v.l.a. circular waveguide system. J.W.Archer 343
Ternary threshold functions, characterisation of, using a partial spectrum. C.Moraga 803
Ternary threshold functions, spectral characterisation of. C.Moraga 712
Three-dimensional 'sandwich' transducer modelling by finite-element method. H.Carru 805
Threshold functions, ternary, characterisation of, using a partial spectrum. C.Moraga 803
Thyristors, depletion-mode vertical-channel m.o.s. gated, enhancement-and. B.Baliga 645
Time delay, pure, adaptive observer for systems with. Z.Iwai and Y.Kawaski 329
Time delay, uncompensated, of decision circuitry, performance degradation of decision-directed c.p.s.k. demodulator due to. S.G.Glisić 331
Time moments and Markov parameters of composite systems. Y.Shamash 131
Tin diffusion, surface stability of GaAs during. B.Tuck and M.H.Badawi 604
Total dispersion in step-index monomode fibres. C.R.South 394
Tracking-loop frequency acquisition, effect of feedback delay on. C.P.Ashall and P.A.Matthews 231
Tracking problem, optimal, discrete-time linear-quadratic, using future desired output values. J.Karpinsky, T.Benes, V.Hlavaty, V.Rozkosny and P.Sajai 316
Traffic detection, 2-f.s.k., quantitative analysis of. B.Forssell 386
Transceivers, semiconductor junction, bidirectional analogue optical transmission using. R.I.Macdonald 121
Transducer aims, piezojunction effect of a planar n-p-n transistor for. R.J.Veen 333
Transducer analysis, surface-wave interdigital, fundamental charge distributions for. D.P.Morgan, B.Lewis and J.G.Metcalfe 583
Transducer modelling, three-dimensional 'sandwich', by finite-element method. H.Carru 805
Transducers, high-frequency sonar, equivalent circuits for. H.Koymen, B.V.Smith and B.K.Gazey 600
Transfer function, modulation, for the acoustic microscope. A.Atalar 321
Transfer functions, optical-fibre, simplified procedure for indirect tests of. G.Cancellieri, M.Mezzetti, C.G.Someda and M.Zoboli 234
Transfer functions with equiripple passband and very low Q-factor for economical active filters. R.Marquardt 618
Transfer impedance of braided coaxial cables under applied longitudinal torsion. M.M.Rahman, J.E.Sitch and F.A.Benson 455
Transformer, Ruthroff, method of bandwidth extension for the. R.T.Irish 790
Transformers, multisection quarter-wave, general class of, for impedance matching at microwave frequencies. P.A.Massaro and V.Picciarelli 222
Transforms, complex rectangular, combination of, and f.n.t. to implement fast convolution. N.S.Reddy and V.U.Reddy 716
Transforms, efficient, for multidimensional convolutions. B.Arambepolar and P.J.W.Rayner 189
Transient response, evaluation of the, of linear stationary systems to a class of excitations. M.M.Milić and M.V.Gmitrović 614
Transient spectroscopy, detection of minority-carrier traps using. R.Brunwin, B.Hamilton, P.Jordan and A.R.Peaker 349
Transistor channel implantations, m.o.s.-, laser annealing of. G.Zimmer 184
Transistor, planar n-p-n, piezojunction effect of a, for transducer aims. R.J.Veen 333
Transistor, the conductivity-controlled, new semiconductor active device;. A.Caruso, P.Spirito and G.Vitale 267
Transistor-transistor logic (i.t.t.l.), injection. J.Furlan 223
Transistors, novel microwave GaAs field-effect. J.C.Vokes, B.T.Hughes, D.R.Wight, J.R.Dawsey and S.J.W.Shrubb 627
Transistors, Si, increase to inverse beta of, due to low-temperature treatments. M.Aceves and D.L.Kendall 282
Transistors, silicon planar n-p-n, effects of emitter edge dislocations on the low-frequency noise of. N.D.Stojadinović 340
Transition matrices in multiple preset experiments and initial state identification of synchronous sequential machines. S.R.Das, P.Chao and Z.Chen 777
Transitional Murromaf-Murroer filters. V.S.Stojanović and V.D.Pavlović 356
Translinear circuit principle: a reformulation. B.L.Hart 801
Transmission experiments, analogue baseband t.v., using semiconductor laser diodes. K-I.Sato and K.Asatani 794
Transmission experiments, dispersion-free single-mode fibre, up to 1.6 Gbit/s. Junichi.Yamada, S.Machida, T.Kimura and H.Takata 278
Transmission lines, coplanar, electrical properties of, on lossless and lossy substrates. J.-P.Becker and D.Jäger 88
Transmitter drive using digital techniques to give frequency modulation. P.Shelswell 68
Transmitter, polar-loop. V.Petrovic and W.Gosling 286
Transversal filter, monolithic 256-point programmable. P.B.Denyer and J.Mavor 710
Trap localisation in the active layer of GaAs microwave f.e.t.s.. D.Meignant, D.Boccon-Gibod and J.M.Bourgeois 779
Trapping, evidence of, in device-quality liquid-phase-epitaxial $In_{1-x}Ga_xAs_yP_{1-y}$. P.K.Bhattacharya, J.W.Ku, S.J.T.Owen, S.H.Chiao and R.Yeats 753
Tuning, fine, of s.a.w. resonators using argon ion bombardment. S.James and I.H.Wilson 683
Twin-transverse-junction stripe laser with linear light/current characteristic and low threshold. G.H.B.Thompson, D.F.Lovelace and S.E.H.Turley 133
Two-dimensional acoustic scanning of optical images. H.Gautier, P.Ledu and C.Maerfeld 186
Two-dimensional high-speed acoustic Fourier transform of optical images. H.Gautier, P.Ledu and C.Maerfeld 177
Two-dimensional inverse filter using floating-gate tapped c.c.d.s.. T.Enomoto, M.Yasumoto and K.Watanabe 280
Two-dimensional variable f.i.r. bandpass filters. S.S.Ahuja 551
Two-diode power combining near 140 GHz. Y.C.Ngan 376
Two-stage amplifier utilising GaAs active-medium-propagation devices. P.L.Fleming and H.E.Carlson 406

U

Ultimate low-loss single-mode fibre at 1.55 μm. T.Miya, Y.Terunuma, T.Hosaka and T.Miyashita 106
Ultra low resistance ohmic contacts to n-GaAs. R.Stall, C.E.C.Wood, K.Board and L.F.Eastman 800
Ultrasonic attenuation of piezoelectric PVF_2 films at high frequencies. B.T.Khuri-Yakub and C.H.Chou 308
Ultraspherical tapers. P.A.Massaro and V.Picciarelli 289
Ultraviolet photoconductive detectors in Zn_3P_2. K.G.Irwin, N.S.Kopeika and R.G.Hunsperger 718
Universal operational-amplifier convertor technique using supply-current sensing. B.L.Hart and R.W.J.Barker 496
User density for 800 MHz microwave mobile radiotelephone communications. D.R.Conn and R.Maciejko 516

V

V.A.D. fibres, phosphor-doped silica cladding. T.Edahiro, S.Sudo, M.Kawachi, K.Jinguji and N.Inagaki 726
V.A.D. method, simultaneous dehydration with consolidation for. K.Chida, F.Hanawa, M.Nakahara and N.Inagaki 835
V.C.O., 800 MHz, for land mobile radio synthesisers. M.Makimoto, K.Nakabe and S.Nishiki 460
V.P.E. GaAs m.e.s.f.e.t. structure using oxygen injection during buffer layer growth. H.Bruch, L.Palm, F.Ponse and P.Balk 246
Validity of two-path model for calculating quality of digital radio links: determination of model from measurements on analogue links. M.Rooryck 783
Vaporisation of GaAs during laser annealing. M.H.Badawi, B.J.Sealy and K.G.Stephens 786
Vapour deposition, plasma-augmented, optical fibres prepared by. J.Irven and A.Robinson 252
Vapour-grown 1.3 μm InGaAsP/InP avalanche photodiodes. G.H.Olsen and H.Kressel 141
Variable-centre-frequency constant-bandwidth linear-phase digital bandpass filters. S.S.Ahuja and S.C.Dutta Roy 245
Variance noise and temperature fluctuations in semiconductors. S.Rahal and A.Chovet 271
Variation of Lange-coupler geometry with dielectric constant. R.Horton 643
Very easily testable/diagnosable sequential machine. A.Bhattacharyya 190
Very low OH content P_2O_5-doped silica fibres. Y.Ohmori, H.Okazaki, I.Hatakeyama and H.Takata 616
Vibration-induced polarisation modulation of light guided in single-mode optical fibres. A.Papp and H.Harms 76
Video modulators, correlation technique for improved isolation of overlapping spectra in. A.J.Clapton 429
Voltage transfer function realisation using active R network: flow-graph technique. S.Osowski 416
Voltage transfer functions, general biquadratic, active C realisation for the. F.Anday 725 Errata 838

W

W-band two-diode power combiner. K.Chang, R.Ebert and C.Sun 403
W-fibre, confined guided modes in, with square core. V.V.Cherny 281
Waveform synthesiser, low-to-high voltage-level shifter and. C.J.Georgopoulos 178
Waveguide, channel optical, fabrication of, using CO_2 laser. H.Terui and M.Kobayashi 79
Waveguide, inbuilt, in twin-transverse-junction stripe lasers, effect of injection current on the dielectric constant of an. S.E.H.Turley, G.H.B.Thompson and D.F.Lovelace 256
Waveguide switching elements, gyrotropic, at optical wavelengths. P.Hlawiczka 109
Waveguides, ion-exchanged, influence on index profile of, double-alkali effect:. V.Neuman, O.Parriaux and L.M.Walpita 704
Waveguides, ion-exchanged, optical frequency-selective filters in. A.Yi Yan and C.D.W.Wilkinson 240
Wavelength-dependent transmission at fibre connectors. K.Petermann 706
Wide bandwidth microstrip antennas for circuit integration. P.S.Hall, C.Wood and C.Garrett 458
Wideband frequency modulation of frequency synthesisers. M.J.Underhill and R.I.H.Scott 393
Wire, horizontal, new representation for the current in a, above ground. M.P.Carpentier and A.F.Dos Santos 554

X

X- and KU-Band internally matched packaged GaAs F.E.T.. H.Derewonko, M.Laviron and J.Lepage 8

Z

Zero total dispersion in graded-index single-mode fibres. W.A.Gambling, H.Matsumara and C.M.Ragdale 474
Zero total dispersion in step-index monomode fibres at 1.30 and 1.55 μm. K.I.White and B.P.Nelson 396

PRINTED BY Unwin Brothers Limited
THE GRESHAM PRESS OLD WOKING SURREY ENGLAND